		Water Well Record	Form WWC-5	KSA 82a-1212	· · · · · · · · · · · · · · · · · · ·	1	
1 LOCATION OF WATER WELL:	FRACTION		_	Section Number	Township Number	Range Number	
Sedgwick	NE 1/4	NE 1/4 SV	1/4	22	т 26 в	R 1E E/W	
Distance and direction frem nearest town				a.,	**		
	d N. on Hydra		Park	City,	Kansas		
water Well OWNER: PARK CITY, City of RR#, ST. ADRESS, BOX#: 6110 N. Hydraulic Board of Agriculture, Divivsion of Water Resource							
CITY, STATE, ZIP CODE: Park City, Kar				Application Number: 990101			
LOCATE WELL'S LOCATION WITH		rggod WELL	40		LEVATION:		
AN "X" IN SECTION BOX:	Depth(s) groundw		1	ft.	2 ft.	3 ft.	
	WELL'S STATIC W	ATER LEVEL 15	FT.	BELOW LAND S	BURFACE MEASURED ON mo/day/yr	08/02/1999	
NWNE	Pump tes	t data: Well wa	iter was	ft.	after hours pun		
	Est. Yield	O1	ater was	ſt.	after hours pun	iping gpm	
w X	E Bore Hole Diameter	anknown in. t	0	ft.	and in.	to ft.	
-	WELL WATER TO		Public water		•	njection well	
	1 Domestic		Oil field water		-	Other (Specify below)	
	2 Irrigation	•	Lawn and ga	•	10 Monitoring well	- /3 /	
S	was a cnemical/bacto	eriological sample sub	mitted to Del		No X; II yes, n /ater Weil Disinfected? Yes	no/day/yr sample was X No	
5 TYPE OF CASING USED:		5 Wrought iron	8 (Concrete tile	C. L. C. T. L. C. T. C.	Slued Clamped	
1 Steel 3 RMP (SR) 6 Asbestos-Cement			o concrete the				
2 PVC 4 ABS		7 Fiberglass		`	7	hreaded	
Biank casing Diameter 5	in. to	ft., Dia	in.	to	ft., Dia in.	to ft.	
Casing height and surface		weight	•	lbs. / ft.	Wall thickness or gauge No.		
TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement							
1 Steel 3 Stainless Steel 5 Fiberglass 2 Brass 4 Calvanized steel 6 Concrete til			8 RMP (SR) 11 other (speci 9 ABS 12 None used (· N/A	
2 Diass 4 Call and Section					12 None used (o) 8 Saw cut	•	
SCREEN OR PERFORATION OPENING ARE: 1 Continous slot 3 Mill slot			5 Gauzeu wrappeu		9 Drilled holes	11 None (open hole)	
1 Continous slot 3 Mill slot 2 Louvered shutter 4 Key punched						/3	
SCREEN-PERFORATION INT	-	7 Torch of the t		6 F	14,	/A n.	
SCREEN-I ERFORATION IN	from	n. c		ft., Fro			
GRAVEL PACK INTERVALS: from		ft.		ft., Fro ft., Fro		ft. ft.	
	from	ft.	to	ft., Fr			
6 GROUT MATERIAL: 1	Neat cement 2 (Cement grout	3 Bent	onlte	4 Other bentonite	hole plug	
Grout Intervals: From 0 ft. to 6 ft. From				0	ft. From 6	ft. to 15 ft.	
What is the nearest source of possible contamination:		7 Di4	10 Livesto		- 14 Abandon water wen		
1 Septic tank 4 Lateral lines		8 Sewage lagoo	• •		el storage 15 Oil well/Gas well		
2 Sewer lines 5 Cess pool 3 Watertight sewer lines 6 Seepage pit		0 0	8 Sewage lagoon 12 Fertilizer storage 9 Feedvard 13 Insecticide storage		rticida etoroga	16 Other (specify below)	
3 Watertight sewer lines 6 Direction from well?	Seepage pit	9 reedyard				Apparent	
FROM TO	LITHOLOGIC LOG		FROM	ТО	How many feet? PLUGGING INTE	RVALS	
			0	6	cement grout		
			6	15	bentonite hole		
			15	40	chlorinated san	d and gravel	
		·		ļ l			
				 			
			 	 			
			 	1			
			<u> </u>				
					100.00		
			 				
			<u> </u>	<u> </u>			
					tructed, or (3) plugged under		
was completed on (mo/day/	/year)	1222	and this reco	ord is true to	the best of my knowledge and	l belief. Kansas Water	
Well Contractor's License No. 1 Under the business name o	GKXXX	Pump Servi	cord was co ce. In	enpieted on ((mo/day/yr)08 <u>/0</u>	エ/ス. ス	
Onder the publicas lighte o				DJ (31	Jodd L	. Harn	