,			Water Well Record	Form WWC-5	KSA 82a-1212			
1 LOCATION	OF WATER WELL:	FRACTION			Section Numbe	Township Number	Range Number	
Se	dgwick	NE 1/4	NE 1/4 S	SW 1/4	22	т 26 s	R 1E E/W	
Distance and di	irection frem nearest town or ci	ty street address of well if lo	cated within city?					
1/2	S. of 53rd	N. on Hydr	aulic	Park	City,	Kansas		
		K CITY, Cit						
RR#, ST. AI		0 N. Hydrau				Board of Agriculture, D	ivivsion of Water Resource	
CITY, STAT		k City, Kar			67219	Application Numbe	r: 990101	
LOCATE WE	LL'S LOCATION WITH	4 DEPTH OF CO	HELL WELL	40	ft. F	ELEVATION:		
AN "X" IN S	ECTION BOX:		vater Encountered	1	ft.	2 ft.	3 ft.	
l 1 🗀	; ; ; ; ; ;	WELL'S STATIC W	VATER LEVEL 1!	5 FT.	BELOW LAND	SURFACE MEASURED ON mo/day/yr	08/02/1999	
		Pump tes		vater was	ft.	after hours pum		
	-NWPE	Est. Yield		water was	ft.	after hours pum		
w X		Bore Hole Diameter	DI	to	ft.	and in.	to ft.	
ĭ w X	E	WELL WATER	SELICED AC	5 Public wate			njection well	
1		1 Domestic		6 Oil field wa		•	Other (Specify below)	
	-sw	2 Irrigation		7 Lawn and g		10 Monitoring well	odici (Specify delo)	
		I -			•	=	- /d/	
, , , , , , , , , , , , , , , , , , ,		Was a chemical/bact	eriological sample su	bmitted to De			io/day/yr sample was	
4 TVDE O	F CASING USED:	submitted				Water Well Disinfected? Yes		
			5 Wrought iron		Concrete tile	_	lued Clamped	
1 Steel	3 RMP (SR)		6 Asbestos-Ceme	nt 9	Other (Specif	•	Velded	
2 PVC	4 ABS		7 Flberglass			1	`hreaded	
	Diameter 5	in. to	ft., Dia	in.	to	ft., Dia in.	to ft.	
	t was and surface		welght		lbs. / ft.	Wall thickness or gauge No.	4	
!	CREEN OR PERFORA	TION MATERIAL:	5 Flberglass		PVC	10 Asbestos-ceme		
1 Steel	3 Stainless Steel		_		RMP (SR)	11 other (specify	') N/A	
2 Brass	4 Galvanized ste	el	6 Concrete tile	9	ABS	12 None used (op	pen hole)	
SCREEN OR PERFORATION OPENING ARE: 5 Gauzed					wrapped 8 Saw cut 11 None (open hole)			
1 Continous slot 3 Mill slot 6 Wire w					rapped 9 Drilled holes			
2 Louvered s	hutter 4 Key p	unched	7 Torci	ı cut		10 Other (specify) N	/A	
SCREEN-PE	RFORATION INTERV	VALS: from	n.	to	ft., Fr	rom ft. to	ft.	
		from	•	to	ft., Fr	_	ſt.	
G	RAVEL PACK INTER	VALS: from		. to	ft., F		n.	
		from		to	ft., F	•	ft.	
6 GROUT	MATERIAL: 1 Neat	cement 2 (Cement grout	3 Bei	ntonite	40ther bentonite	hole plug	
Grout Interv	als: From ()	ft. to 6	ft. From	ft.	to	ft. From 6	ft. to 15 ft.	
What is the nearest source of possible contamination:					estock pens 14 Abandon water well			
1 Septic tank 4 Lateral lines			7 Plt privy		11 Fue	1 -4	15 Oil well/Gas well	
2 Sewer lines 5 Cess pool			8 Sewage lagoon			- 150	16 Other (specify below)	
3 Watertight sewer lines 6 Seepage pit					acticida etorogo	Apparent		
Direction fro	- ·- · · ·	-gc pic				How many feet?	Apparent	
FROM TO		LITHOLOGIC LOG		FROM	ТО	PLUGGING INTE	RVALS	
				0	6	cement grout		
				6	15	bentonite hole	plug	
				15	40	chlorinated san		
				1-3	1 * 0	l little cod buil	a ana graver	
					.			
								
				 				
								
					-			
		***			1			
				-				
					_			
					_			
				_				
7 CONTRA	ACTOR'S OR LANDOWNE	R'S CERTIFICATION: Th	nis water well was f	1) construct	ed. (2) recon	structed, or (3) plugged under n	ny jurisdiction and	
was compl	leted on (mo/dav/vear	08/02/	1999	and this red	ord is true to	o the best of my knowledge and	belief. Kansas Water	
Well Contr	actor's License No	236	This Water Well R	ecord was c	ompleted on	(mo/day/yr)	4/99	
Under the	business name of His	arp Well &	Pump Serv	ice. In	እር bv /s	ignature)		
		-				Todd L	ΩP	