l co	TON ORW	A TEN MON I	FRACTION	Water Well Reco	rd Form WWC-5	KSA 82a-1212		1
LUCZ		ATER WELL:	-			Section Number	Township Number	Range Number
Sedgwick			NE 1/4		NE 1/4	31	T 26 s	R 1E E/W
Distance and direction frem nearest town or city street address of well if located within city?								
1905 W. 37th N. Wichita, Kansas								
WATER WELL OWNER: MC KEE, Grover REW ST ADDRESS ROX #: 1005 Mt 27+b bt Board of Agriculture, Divivision of Water Resource								
1905 W. 57CH N.								
					4 =	e FIE	Application Number	<u> </u>
	TE WELL'S I		DEPTH OF COM Depth(s) groundwa		45	ft. ELE ft.	VATION: 2 ft.	3 ft.
1 +		- 			-		LFACE MEASURED ON mo/day/yr	09/17/1999
	1	1 1 1	WELL'S STATIC W. Pump test					
								·
iii E			Bore Hole Diameter	gpın: Well 12 in.	to 45	n. : ft.	after hours pum and in.	ping gpm to ft.
1 Mile		1 121	WELL WATER TO E		5 Public water			njection well
			1 Domestic	3 Feedlot	6 Oil field wa		•	Other (Specify below)
	SW	SE	2 Irrigation	4 Industrial	7 Lawn and g		0 Monitoring well	
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample wa								o/day/yr sample was
S submitted Water Well Disinfected? Yes X No								
5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped								
1 Stee	el	3 RMP (SR)		6 Asbestos-Cem		Other (Specify be		Velded
2 PV	C	4 ABS		7 Fiberglass	S	DR-26	T	hreaded
Blank casing Diameter 5 in. to 35 ft., Dia in. to ft., Dia in. to ft.								
Casing height above land surface 12 in., weight 2.35 lbs./ft. Wall thickness or gauge No214								
1			ΓΙΟΝ MATERIAL:	<i>E</i> 1711 1		PVC	10 Asbestos-ceme	
1 Ste		3 Stainless Steel		5 Fiberglass		RMP (SR)	11 other (specify)
2 Bra	38	4 Galvanized stee	l	6 Concrete tile	9	ABS	12 None used (op	
SCREEN OR PERFORATION OPENING ARE: 5 Gauzed wrapped 8 Saw cut							11 None (open hole)	
1 Continous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes								
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)								
SCREEN-PERFORATION INTERVALS: from 35 ft. to 45 ft., From ft. to ft.								
from					t. to	ft., From		ft.
GRAVEL PACK INTERVALS: from 24					nt. to 45	ft., From		ft.
from ft. to ft., From ft. to ft. 6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other heart on it a hole plug								
Dent Marrie Dent Control of the Cont								
What is the nearest source of possible contamination:				ft. From ft. to		to 10 Livesto	ft. From 24	ft. to 26 ft. bandon water well
1 Septic tank 4 Lateral lines				7 Pit privy		11 Fuel sto		Dil well/Gas well
2 Sewer lines 5 Cess pool				8 Sewage lagoon		12 Fertiliz		Of well Gas wen Other (specify below)
3 Wate	rtight sew		-	9 Feedyard		13 Insecticide storage		
Direction from well? South How many feet? 75								
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS								
0	2	topsoil						
2	8	clay				1	··········	· ••••
8	15	fine san						
15	30	coarse s	and					
30	33	clay						
33	45	medium c	oarse sand			1		
						-		
						 		
						+		
					1	1		
	1							
	1							
7 CONTRACTORIS on a supersymmetry with the supersymmetry (a) and supersymmetry (b) and supersymmetry (contract of the supersymmetry).								
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year)								
Well Contractor's License No236								
Under the business name of Harp Well & Pump Service Inc by (signature)								
Todd S. Harp								