

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: Sedgwick		NE ¼ NE ¼ NW ¼		20		T 26 S		R 1 E/W	
Distance and direction from nearest town or city street address of well if located within city? 703 West 53rd Street North, Wichita, Kansas									
2 WATER WELL OWNER: Keith Goolsby RR#, St. Address, Box # : 703 West 53rd Street North City, State, ZIP Code : Wichita, KS 67204 Board of Agriculture, Division of Water Resources Application Number:									
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:			4 DEPTH OF COMPLETED WELL 31 ft. ELEVATION: 1330.18						
			Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.						
			WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr						
			Pump test data: Well water was NA ft. after hours pumping gpm						
			Est. Yield NA gpm: Well water was ft. after hours pumping gpm						
			Bore Hole Diameter 1 in. to 31 ft. and in. to ft.						
			WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well						
			Was a chemical/bacteriological sample submitted to Department? Yes.....No.....; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No ☒						
5 TYPE OF BLANK CASING USED:									
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded. ☒									
Blank casing diameter 1 in. to 26 ft. Dia in. to ft. Dia in. to ft.									
Casing height above land surface 4.2 in. weight lbs./ft. Wall thickness or gauge No. Sch. 40									
TYPE OF SCREEN OR PERFORATION MATERIAL 7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)									
SCREEN-PERFORATED INTERVALS: From 26 ft. to 31 ft. From ft. to ft. From ft. to ft. From ft. to ft.									
GRAVEL PACK INTERVALS: From 25.5 ft. to 31 ft. From ft. to ft. From ft. to ft. From ft. to ft.									
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other									
Grout Intervals: From 3 ft. to 23.5 ft. From 23.5 ft. to 25.5 ft. From ft. to ft.									
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? West How many feet? 40									
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS									
0 0.5 Asphalt,									
0.5 1 Sand, Red Brown									
1 8 Clay,									
8 11 Sand, Dark Brown									
11 11.5 Clay,									
11.5 19 Sand, Dark Brown									
19 31 Sand, Brown									
AS-5, Tag # 00295372, Abovegrade									
Project Name: Greenfield - QuikTrip #367									
GeoCore # 828, KDHE # U208710943									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11/1/99 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 2/7/2000 under the business name of GeoCore Services, Inc. by (signature) <i>Dale Rabel</i>									