, LOCATION OF WATER V	FRACTION		Water Well R		orm WWC-5	KSA 82a-1212					
		i .	> W 10	= SW S			Section Number	Township Number	*	Range Number	
Sedgwick 25W 1/4					8W	1/4	31	т 26 s	8	R 1W E/W	
Distance and direction frem nearest town or city street address of well if located within city?											
3130 N. S					Wich	<u>lita,</u>	Kansas				
WATER WELL OWNE	5212421	-									
RR#, ST. ADRESS, BOX#: 3130 N. St. Clair Board of Agriculture, Divivsion of Water Res										ivsion of Water Resource	
CITY, STATE, ZIP CODI	nsas					Application Number:					
LOCATE WELL'S LOCAT	, <u> </u>	DEPTH OF				40		LEVATION:			
AN A INSECTION BOX	 _ '	Depth(s) gro				1	ft.	2	ft.	3 ft.	
	WE	LL'S STAT					BELOW LAND S	SURFACE MEASURED ON	mo/day/yr	02/24/2000	
NW	NE	Pun	ıp test datı		ell wate		ft.	after]	hours pump	ing gpm	
ا ا و ا	Est.	Yield			ell wat		ft.	after l	hours pump	ing gpm	
w w	, L	e Hole Diam		12 in	-	40	ft.	and	in.	to ft.	
	i I I	LL WATER				ıblic wate		8 Air conditioning	'	jection well	
sw		1 Domestic		Feedlot			ter supply	9 Dewatering	12 O	ther (Specify below)	
	i I I	2 Irrigation		ndustrial			arden only	10 Monitoring well			
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was											
submitted water well Disinfected? Yes X No											
5 TYPE OF CASING				Wrought is		_	Concrete tile	CASING JOIN	GI.	ued X Clamped	
1 Steel 3 RMP (SR)				6 Asbestos-Cement 9 Other (Specif				•			
2 PVC	4 ABS		7.	Fiberglass		S	DR-26		Th	ıreaded	
Blank casing Diameter	_	to 30	1	ft., Dia		in.	to	ft., Dia	in.	to ft.	
Casing height above lar			in. ,	welgh	t 2.3		lbs. / ft.	Wall thickness or ga	uge No. bestos-cemer	.214	
TYPE OF SCREEN O		N MATERIA		iberglass			PVC RMP (SR)			ıı	
	tainless Steel			•					her (specify)		
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)									•		
SCREEN OR PERFOI		5 Gauzed wrapped			8 Saw cut 11 None (open hole) 9 Drilled holes						
1 Continous slot	3 Mill slot			0 1	Wire wr	арреа			• \		
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)											
SCREEN-PERFORAT	30		ft. to	40	ft., Fro	om	ft. to	ft.			
from				ft. to			ft., Fro	m	ft. to	ft.	
GRAVEL PACK INTERVALS: from 24				ft. to 40 ft., From			ft. to	ft.			
	•	ft. to ft., Fro				ft. to	ft.				
					nent grout 3 Bentonite			^{4 Other} bentonite hole plug			
Grout Intervals: From 4 ft. to 24 What is the nearest source of possible contamination:				ft. From ft.				ft. From		ft. to ft.	
1								11 Puel stemans		oandon water well	
1 Septic tank 4 Lateral lines 2 Sewer lines 5 Cess pool				8 Sewage lagoon				ilizer storage	15 Oil well/Gas well 16 Other (specify below)		
						secticide storage					
5 watering sewer mes 6 Seepage pit 5 recuyatu											
Direction from well? East FROM TO LITHOLOGIC LOG				FROM TO			то	How many feet? 80 PLUGGING INTERVALS			
	opsoil					110.,1			1110 1111 111	7720	
	lay										
	ine sand										
	edium coa	rse sa	and								
						P. 111 -					
was completed on (mo/day/year)	02/2	<u>24/00</u>		ar	d this re	 cord is true to	structed, or (3) plugg the best of my know	vledge and	belief. Kansas Water	
Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) Q2/25/00 Under the business name of Harp Well & Pump Service. Inc. by (signature) Todd S. Harp											