					Water Well Re	ecord Form WWC-				
1 LOCA	TION OF WA		FRACI				Section Number	Township Number	Range Number	
Sedgwick			SE		SW 1/4	NE 1/4	32	T 26 s	$_{R}$ 1E $_{E/W}$	
Distance and direction frem nearest town or city street address of well if located within city?										
33rd N. & 1/8th m. E. of Arkansas, N. side Wichita, Kansas										
water well owner: WICHITA, CITY OF										
RR#,	RR#, ST. ADRESS, BOX#: 455 N. Main							Board of Agriculture	e, Divivsion of Water Resource	
CITY, STATE, ZIP CODE: Wichita, Kans								Application Number: 20000105		
		OCATION WITH	<b>d</b> DEPTH	OF COM	IPLETED WEL	L 45		EVATION:		
AN "X	" IN SECTIO	N BOX:	Depth(s)	groundw	ater Encountere		ft.	2 ft.	3 ft.	
1 [			WELL'S ST	ATIC W	ATER LEVEL	15 FI	. BELOW LAND SI	URFACE MEASURED ON mo/day/yr	05/30/2000	
	NW	NE	]	Pump test	data: We	ell water was	ft.	after hours po	umping gpm	
۰	1 :		Est. Yield		gpm: We	ell water was	ft.	after hours po	umping gpm	
1 Mile	/	X E	Bore Hole D	iameter	12 in.	to 45	ft.	and i	n. to ft.	
-			WELL WAT	TER TO I	BE USED AS:	5 Public wate	r supply	8 Air conditioning 1	1 Injection well	
Li	sw		1 Dome	stic	3 Feedlot	6 Oil field wa		J	2 Other (Specify below)	
			2 Irriga	tion	4 Industrial	7 Lawn and a	garden only	10 Monitoring well		
1 +			Was a chem	ical/bacte	riological sample	e submitted to D	epartment? Yes	No X; If yes	, mo/day/yr sample was	
<u> </u>		<u> </u>	submitted				Wi	ater Well Disinfected? Ye	s X No	
5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped										
1 Stee	el	3 RMP (SR)			6 Asbestos-Ce	ement 9	Other (Specify	below)	Welded	
2 PVC 4 ABS 7 Fiberglass SDR-26 Threaded										
Blank c	asing Diam	eter 8	in. to 2	25	ft., Dia	in.	to	ft., Dia in.	to ft.	
Casing height above land surface 12 in., weight 5.52 lbs./ft. Wall thickness or gauge No332										
TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement										
1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 other (specify)									ify)	
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open h									(open hole)	
SCREEN OR PERFORATION OPENING ARE: 5 Gauzed						auzed wrapped		8 Saw cut	11 None (open hole)	
1 Continous slot 3 Mill slot 6 Wire wr						Vire wrapped		9 Drilled holes		
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)										
SCREEN-PERFORATION INTERVALS: from 25 ft. to 45 ft., From ft. to ft.										
				rom		ft. to	ft., Fro			
GRAVEL PACK INTERVALS: from 25					,	ft. to 45 ft., From		•••		
				rom		ft. to	ft., Fro			
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug										
Grout Intervals: From ft. to ft. From ft. to ft. From 4 ft. to 24 ft.										
What is the nearest source of possible contamination:									4 Abandon water well	
1 Septic tank 4 Lateral lines					7 Pit priv	<b>y</b>	11 Fuel s	torage 1	5 Oil well/Gas well	
2 Sewer lines 5 Cess pool					8 Sewage lagoon				6 Other (specify below)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage None Apparent									e Apparent	
Direction from well?  How many feet?										
FROM	ТО		LITHOLOG	IC LOG		FROM	TO	PLUGGING INT	ERVALS	
0	3	topsoil								
3	17	clay								
17	25	fine sar								
25	45	medium s	sand				1 1			
					-					
	-	- 1 111.2.2					<u> </u>			
<b>-</b>	-				<del></del>					
	<b> </b>	<b></b>					1 1			
	-									
<b></b>										
7 CO	NTRACTO	R'S or landowni	ER'S CERTIFICA	TION: Th	is water well wa	as (1) construc	ted, (2) reconst	ructed, or (3) plugged unde	r my jurisdiction and	
Was c	ompleted	on (mo/day/year	r)0.5	/30/	00	and this re	cord is true to	the best of my knowledge a	nd belief. Kansas Water	
Well	Contracto	r's License No	236		This Water We	II Record was	completed on (i	mo/day/yr)Q.6./	01/00	
Under the business name of Harp Well & Pump Service. Inc by (signature)										
Todd S. Harp										