li a a			Lancara	Water Well Record	Form WWC-5	KSA 82a-1212		<u>,</u>	
LOCA		ATER WELL:	FRACTION			Section Number		Range Number	
L	Sedgr		SE 1/4	SE 1/4 S	<u>c</u> 1/4	28	т 26 s	R 1E E/W	
Distance	and direction	i frem nearest town or ci	ty street address of well if loc	ated within city?					
3903 N. Hydraulic Wichita, Kansas									
WATER WELL OWNER: COVEY, Lyman									
RR#,	ST. ADRESS	,вох#: 390	3 N. Hydrau	ılic			Board of Agriculture, D	lvivsion of Water Resource	
CITY	, STATE, ZI	CODE: Wic	<u>hita, Kansa</u>			Application Number:			
		LOCATION WITH		WELL WELL	28	ft. E	LEVATION:		
MAN "X	" IN SECTIO	N BOX:	Depth(s) grounds	ater Encountered	1	ft.	2 ft.	3 ft.	
			WELL'S STATIC W	ATER LEVEL 10	FT.	BELOW LAND	SURFACE MEASURED ON mo/day/yr	06/01/2000	
1 [	NW	NE NE	Pump tes	t data: Well wa	iter was	ft.	after hours pum	ping gpm	
			Est. Yield	gpm: Well w	ater was	ft.	after hours pum	ping gpm	
1 Mile	/ <b> </b> -	E	Bore Hole Diameter	_ in. t	0	ft.	and in.	to ft.	
= "			WELL WATER	USED AS: 5	Public water	r supply	8 Air conditioning 11 I	njection well	
1 ,			1 Domestic	3 Feedlot 6	Oil field wa	ter supply	9 Dewatering 12 C	Other (Specify below)	
			2 Irrigation	4 Industrial 7	Lawn and g	arden only	10 Monitoring well		
↓		X	Was a chemical/bact	eriological sample sub	mitted to De	partment? Ye	s No X; If yes, m	o/day/yr sample was	
		S	submitted			v	Vater Well Disinfected? Yes	X No	
5 TY	PE OF CA	ASING USED:		5 Wrought iron	8	Concrete tile	CASING JOINTS: G	lued Clamped	
1 Stee	el	3 RMP (SR)		6 Asbestos-Cement	9	Other (Specify	v below)	/elded	
2 PV	<del>.</del>	4 ABS	_	7 Fiberglass			Т	hreaded	
Blank casing Diameter 1, 1/4 in. to 28 ft., Dia 4 RMP5 to 0 ft 4, to Dia 10 ft to ft.									
Casing height above land surface 60 in., weight lbs./ft. Wall thickness or gauge No.									
TYPE	OF SCREI	EN OR PERFORA	TION MATERIAL:			PVC	10 Asbestos-ceme	ent	
1 Ste	el	3 Stainless Steel		5 Fiberglass	8	RMP (SR)	11 other (specify	) N/A	
2 Bra	SS	4 Galvanized ste	el	6 Concrete tile	9	ABS	12 None used (op	en hole)	
SCREEN OR PERFORATION OPENING ARE: 5 Gauzed wrapped							8 Saw cut	11 None (open hole)	
1 Conti	nous slot	3 Mill s	lot	6 Wire w	rapped		9 Drilled holes		
2 Louve	ered shutte	er 4 Key p	unched	7 Torch	eut		10 Other (specify) N	/A	
SCREE	N-PERFO	RATION INTER	VALS: from	ft. í		ft., Fr		ft.	
			from	ft. (	_	•	_	ft.	
	GRAV	EL PACK INTER		ft.		ft., Fr ft., Fr	<b></b>		
			from	ft. 1		ft., Fr		ft. ft.	
6 GRO	OUT MAT	ERIAL: 1 Neat	•	Cement grout		tonite		hole plug	
Grout Intervals: From 0 ft. to 7 ft. From ft. to ft. From 7 ft. to 28 ft.									
What is	the neares	t source of possibl	e contamination:					bandon water well	
1 Sept	ic tank	4 Later	al lines	7 Pit privy		11 Fuel	storage 15 (	Dil well/Gas well	
2 Sewe	er lines	5 Cess	s pool	8 Sewage lagoon			ilizer storage 16 (	Other (specify below)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard						13 Insecticide storage			
Direction from well? West How many feet? 15									
FROM	ТО		LITHOLOGIC LOG		FROM	ТО	PLUGGING INTE	RVALS	
	<u> </u>		8 - Wat		0	7	cement grout		
	<u> </u>				7	28	bentonite hole	plug	
	ļ <u>.</u>			*****					
	<b>_</b>			t					
	<u> </u>				<u> </u>				
	<u> </u>								
ļ	ļ							. ,	
					ļ				
	ļ								
	<b></b>								
						1			
	<u> </u>								
<u> </u>									
L	<u> </u>								
7 00	NTRACTO	DR'S OR LANDOWN	P'S CERTIFICATION. TH	nis water well was /1	construct	ed (2) recons	structed, or (3) plugged under n	ny jurisdiction and	
Hwas n	ompleted	on (mo/dav/veai	06/01/	00 :	nd this rec	ord is true to	the best of my knowledge and	belief. Kansas Water	
							(mo/day/yr)		
Unde	r the busi	ness name of.从i	arp Well &	Pump Servi	ceIr	ໄຕ by (si	anature)	_	
			_			• •	Todd S	\ 'Ha <del>r</del> n	