		Lantaria	Water Well Record	Form WWC-5		T	1 2	
1 LOCATION OF WA		FRACTION			Section Number	Township Number	Range Number	
Sedgwick SE 1/4				E 1/4	32	т 26 s	R 1E EAW	
Distance and direction frem nearest town or city street address of well if located within city?								
33rd N. & 4/8 E. of Arkansas, N. side Wichita, Kansas								
WATER WELL OWNER: WICHITA. CITY OF  Board of Agriculture, Divivision of Water Resout  Board of Agriculture, Divivision of Water Resout								
RR#, ST. ADRESS,		N. Main	_		68000	_		
CITY, STATE, ZIP		ita, Kansa		4.0	67202	Application Numbe	<u> 20000105</u>	
LOCATE WELL'S LAN "X" IN SECTION		DEPTH OF CLA	· <b>3</b> 3	40	ft. EL ft.	EVATION: 2 ft.	3 ft.	
• r <del></del>	<del>-Y</del>	Depth(s) groundwa		1 • • • • • • • • • • • • • • • • • • •		JRFACE MEASURED ON mo/day/yr	06/21/2000	
		WELL'S STATIC W. Pump test		yater was		_	•	
NW	NE	Est. Yield		vater was vater was	ft. ft.	after hours pum after hours pum	- ·	
뱶		Bore Hole Diameter	B1	to	rt. ft.	and in.	to ft.	
W W		WELL WATER <b>FO</b>		to 5 Public wate:			njection well	
		1 Domestic		6 Oil field wa			Other (Specify below)	
		2 Irrigation		7 Lawn and g		10 Monitoring well		
		Was a chemical/bacte		_	•	ū	o/day/yr sample was	
'	S	submitted	riological sample su	onneceu to De	-	ater Well Disinfected? Yes	No	
5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped								
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (Specify below) Welded								
2 PVC	4 ABS		7 Fiberglass		(1)	•	'hreaded	
Blank casing Diame	eter 8	in. to	ft., Dia	in.	to	ft. , Dia in.	to ft.	
Casing height			weight		lbs. / ft.	Wall thickness or gauge No.		
TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement							ent	
1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 other (speci							) N/A	
2 Brass 4 Galvanized steel 6 Concrete tile				9	ABS			
SCREEN OR PERFORATION OPENING ARE: 5 Gauze				ed wrapped	wrapped 8 Saw cut 11 None (open hole)			
1 Continous slot 3 Mill slot 6 Wire w				wrapped	apped 9 Drilled holes			
2 Louvered shutter	· 4 Key pu	nched	7 Torch	cut		10 Other (specify) N	/A	
SCREEN-PERFORATION INTERVALS: from ft. to ft., From ft. to							ft.	
		from	ft.	to	ft., Fro		ft.	
GRAVEL PACK INTERVALS: from				ft. to ft., Fron			ft.	
from				to ft., From ft. to		<u>N.</u>		
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug								
Grout Intervals: From 3 ft. to 9 ft. From ft. to ft. From 9 ft. to 13 ft.								
What is the nearest source of possible contamination:			10 Livestock pens 14 Abandon water we			bandon water well		
1 Septic tank 4 Lateral lines			7 Pit privy 11 Fuel st			15 On well Gas well		
2 Sewer lines 5 Cess pool			8 Sewage lagoon 12 Fertilizer stor			20 .	To other (speem) below)	
3 Watertight sewer lines 6 Seepage plt 9 Feedyard 13 Insecticide storage None Apparent								
Direction from well? How many feet?								
FROM TO	<u>L</u>	ITHOLOGIC LOG		FROM	TO	PLUGGING INTE		
<del>                                     </del>				10	3	surface clay an	a sitt	
				3	9	<pre>cement grout bentonite hole</pre>	1	
<u> </u>				9 13	13	chlorinated san		
				173	40	CHIOLIHATEG Ball	d and graver	
					1 1			
					1 1		A THE RESIDENCE OF THE PROPERTY OF THE PROPERT	
					<del>                                     </del>			
					1			
						· · · · · · · · · · · · · · · · · · ·		
				1	1 1			
				1				
	· · ·							
7 CONTRACTO	DIS OR LANDOWS	DIS CERTIFICATION THE	e water well wee #	1) construct	ad (2) recent	ructed or (3) plugged under a	ny jurisdiction and	
OONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year)								
Well Contractor's License No								
Under the business name of Harry Well & Plimp Service, Inc. by (cignotyre)								
Todd S. Harp								