4 11 00 4 71	011 0E 1114 TEB			R WELL REC	ORD Form		KSA 82				
	ON OF WATER SEGV		Fraction NE 1/2	SE ½	. QE	% Sec	tion Numb	per Township		Range Number	Е
County: Distance an			n or city street ad	dress of well i		hin city?					
2 WATER	WELL OWNER	T&E O	IL# 11	35.	33 N BRU	ADWAT					\dashv
RR# St Ad	Idress Box#	3935 N	BROADWA	Y				Board of Ag	nculture, Div	vision of Water Resourc	æs
City, State,	ZIP Code	: WICHIT	TA, KS 6721	9				Application (
LOCATE	WELL'S LOCA N SECTION BO	TON WITH	4 DEPTH OF C		A/ELI	30) ff FI	EVATION:			
X	N SECTION BO	^.	Denth(s) Ground	water Encoun	tered 1	16.	.5	ft. 2	ft.	3	ft.
^	N		WELL'S STATIC	WATER LEV	EL 15	.22 ft.	below lan	d surface measure	d on mo/day	y/yr 9/21/00	
Α Γ	1 1	\Box								pumping gp	m
	NW	NF	Est. Yield	Gpm: \	Well water w	as		Ft. after	Hours	pumping Gr	pm
			Bore Hole Diame	ter 8.62 5	In. to	3(0	ft. and	i 	in. to	ft.
₹ w ►		╅┩╒	1 Domestic	3 Feed lot	45: 5 Pub 6 Oil:	nic water s field water	uppiy supply	9 Dewateri	ioning 1a **	in. to 11 Injection well 12 Other (Specify below	<u>~)</u>
1	sw -	! !						estic) 10 Monitori			
	5	SE X	Was a chemical/	bacteriologica	l sample sul	omitted to I	Departmei	nt? Yes No	X If yes	s, mo/day/yr sample wa	s
<u> </u>	<u> </u>		Submitted		•			Water Well Disinfed			
5 TYPE O	F BLANK ČASII	NG USED:		5 Wrough	t Iron	8 Concr	ete tile	CASING JO	INTS: Glu	ed Clamped	
1 Ste	eel	3 RMP (SR)	6 Asbesto	s-Cement	9 Other	(specify b	elow)		ided	
2 PV	C X	4 ABS		7 Fibergla	ISS				Thre	eaded X	
Blank casin	o diameter	2	in to 27.	Ft., 5 Dia		In. i	to	ft Dia		in. to	ft.
Casing heid	aht above land s	urface	Flush	in., weight	Sc	h 40	Lbs	./ft. Wall thickness	or gauge N	O	
	CREEN OR PE					7		10 As			
1 Ste	eel	3 Stainle	ess steel	5 Fibergla	iss	8	RMP (SF	R) 11 Ot	her (specify)	
2 Bra			nized steel		te tile		ABS	12 No	ne used (or	pen hole)	
	OR PERFORATI entinuous slot		Mill slot X		6 Wire wr			8 Saw cut 9 Drilled hole		11 None (open hole)	'
	uvered shutter	-	Key punched		7 Torch c						
	PERFORATED I		-		t, to		f	t. From	ft.	to	ft.
	_,,		From				f	t. From	ft.	. to	Ft.
SA	ND PACK INTE	RVALS:	From		t. to	30	f	t. From	ft.	. to	ft.
			From	f	t. to		f	t. From	ft.		ft.
6 GROUT	MATERIAL:	1 Neat o	cement 2	Cement grou	ıt X	3 Ber	ntonite X	4 Other			
Grout inten	vals From3	26	ft. to 3	Ft.	3	Ft.				ft. to	
	nearest source			1 101112						bandoned water well	11.
1 Se	eptic tank	•	4 Lateral lines	7	Pit privy			uel storage		il well/ Gas well	
2 Se	ewer lines		5 Cess pool	8	Sewage la	igoon	12 Fe	ertilizer storage	16 <u>O</u>	ther (specify below)	
3 W	atertight sewer I	ines	6 Seepage pit	9	Feedyard		13 in:	secticide storage	C	ontaminated Site	;
Direction fr						· ·		any feet?			
FROM 0	.75	CODE	PHALT	OGIC LOG		FROM	TO	F	LUGGING	INTERVALS	
.75	13		AY W SOME	SILT							
13	25	CL	AYEY SILT								
25	30		LTY SAND								
30	TD	EN	ID OF BORE	HOLE			 				
	 						 	-			
							1				_
											_
	 					[
	1						+			,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	
							<u> </u>				
			014		ter well was					nder my jurisdiction and	
	on (mo/day/yr)			9/00					•	edge and belief. Kansas	
	l Contractor's Li			585			water Wel	Record was comp	leted on (m	o/day/yr) 10/02/00	<u> </u>
INST	business name (se fill in blank	Associa	rect answers.	Send three co	pies to Kan	sas Denart	ment of Health and E	nvironment	an for D. Duncan Bureau of Water, Topeka,	_
Kansa	as 66620-0001. T	elephone: 91	3-296-5545. Send	one to WATER	WELL OWN	ER and reta	in one for	our records.`			
-		-		•							

.

. . .