4 11 00471011 05 144755 1451	WATER WELL RECORD FO			
1 LOCATION OF WATER WELL: County: SEGWICK	Fraction  NE ½ SE ½ SE	1 00	Township Number	Range Number
County: SEGWICK Distance and direction from nearest town			<b>26</b> s	R 1 E
3935 N BROADWAY				
2 WATER WELL OWNER: T&E OIL# 11				
RR#, St. Address, Box # : 3935 N E			oard of Agriculture, Divis	ion of Water Resources
City, State, ZIP Code WICHITA 3 LOCATE WELL'S LOCATON WITH 4	A, NS 6/219	A	pplication Number:	
JAN A IN SECTION BOX.	Ther I under COMPLETED MELL	25 ft. ELEVATIO	N:	
X	Depth(s) Groundwater Encountered 1	<b>17</b> ft. 2	ft. 3	ft.   <u>S</u>
NV	WELL'S STATIC WATER LEVEL 1	5.48 ft. below land surface	e measured on mo/day/y	ft. 9/21/00
<b>A</b>	Pump test data: Well water	was Ft. afte	r hours pu	mping gpm Gpm Gpm
NWNE	Est. Yield Gpm: Well water	was Ft. afte	r Hours pu	ımping Gpm n
	Jore Hole Diameter 8.625 In. to	25 ft. an	in.	to ft. S
₹ W E V	Bore Hole Diameter <b>8.625</b> In. to WELL WATER TO BE USED AS: 5 Pt 1 Domestic 3 Feed lot 6 Oi	Dilic water supply 8	Air conditioning 11 Dewatering 12	Other (Specify below)
	2 Irrigation 4 Industrial 7 La	wn and garden (domestic) 1	0 Monitoring well	AS-6
sw				
Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was Submitted Water Well Disinfected? Yes No X				
5 TYPE OF BLANK CASING USED:	5 Wrought Iron			
	R) 6 Asbestos-Cement			
2 PVC X 4 ABS	7 Fiberglass			ied X
	E+ .			
Blank casing diameter 2 i	in. to 22.5 Dia	In. to ft.,	Diai	n. toft.
Casing height above land surface	Flush in., weight 5	Ch 40 Lbs./ft. Wall	thickness or gauge No.	
TYPE OF SCREEN OR PERFORATION I	MATERIAL:	7 PVC X	10 Asbestos-cemen	t
1 Steel 3 Stainless 2 Brass 4 Galvaniz	s steel 5 Fiberglass zed steel 6 Concrete tile	8 RMP (SR) 9 ABS	11 Other (specify)	
SCREEN OR PERFORATION OPENING	S ARE: 5 Gauze	d wrapped 8 :	Saw cut 12 None used (oper	1 None (open hole)
	fill slot X 6 Wire w		Drilled holes	recite (open note)
2 Louvered shutter 4 Ke			Other (specify)	
SCREEN-PERFORATED INTERVALS:	From <b>22.5</b> ft. to	25 ft. From	ft. to	ft.
	From ft. to			
SAND PACK INTERVALS:	From <b>21.5</b> ft. to	25 ft. From	ft. to	ft.
	From ft. to		ft. to	
6 GROUT MATERIAL: 1 Neat cer	ment 2 Cement grout X	3 Bentonite X 4 Ot	her	
Crout Intervals From 2 21.5 #	Ft.	Ft.		1
Grout Intervals From3 21.5 ft. What is the nearest source of possible con				
•	1 Lateral lines 7 Pit privy	10 Livestock p	ens 14 Abai e 15 Oil w	ndoned water well
<b>.</b>	5 Cess pool 8 Sewage	-		er (specify below)
	S Seepage pit 9 Feedyard	•		taminated Site
Direction from well?	, coopage pit 5 1 codyard	How many feet?		italimiated Site
FROM TO CODE	LITHOLOGIC LOG	FROM TO	PLUGGING INT	ERVALS
	PHALT			
	W SOME CLAY			
	TY CLAY TY SAND			
	OF BOREHOLE	<del> </del>		
		<del> </del>		
7 CONTRACTOR'S OR LANDOWNER'S				
Completed on (mo/day/yr) 9/20/00 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 585 This Water Well Record was completed on (mo/day/yr) 10/02/00				
Water Well Contractor's License No.	585	This Water Well Record	was completed on (mo/d	ay/yr) 10/02/00
under the business name of	Associated Environmenta and circle the correct answers. Send three co	I, INC. By (sig	nature) A. Duncan	TOF D. Duncan
	296-5545. Send one to WATER WELL OWN			cau Oi vvaici, TOpeka,
	1			