1 LOCATION OF WATER WELL:	FRACTION	Water Well Record	Form WWC-5	KSA 82a-1212	T	T
	1			Section Number	Township Number	Range Number
Sedgwick	NW 1/4	SE 1/4 S	€ 1/4	7	T 26 s	R 1E E/W
Distance and direction frem nearest town or city street address of well if located within city?						
6213 Sullivan	Wichit	a, Kansas				
	TE, Mike					
RR#, ST. ADRESS, BOX#: 6213 N. Sullivan Board of Agriculture, Divivsion of Water Resource						
CITY, STATE, ZIP CODE: Wichita, Kansas Application Number:						
			20	~ E11		
LIANTER DISPOSITION DOV.	DEPTH OF POM	UU	28		EVATION: crawl spa	
	Depth(s) groundwa		1	ñ.	2 ft.	3 ft.
	LL'S STATIC W	ATER LEVEL 17	FT.	BELOW LAND SU	RFACE MEASURED ON mo/day/yr	11/28/2000
NWNE	Pump test	data: Well wa	iter was	ſt.	after hours pum	ping gpm
l Est.	Yield		ater was	ſt.	after hours pum	ping gpm
E Bore	Hole Diameter	_ in. t	0	ſt.	and in.	to ft.
\leq W	LL WATER 70 I	E USED AS: 5	Public wate	r supply	8 Air conditioning 11 In	njection well
1 1 i 1 i 1 i 1 i 1 i 1 i 1 i 1 i 1 i 1	1 Domestic		Oll field wa		=	ther (Specify below)
sw			Lawn and g		U	ther (Speeny below)
4 1 i 1 1 1 1 1 1 1 1	2 Irrigation				10 Monitoring well	
		riological sample sub	mitted to De	-		o/day/yr sample was
submitted Water Well Disinfected? Yes X No						
5 TYPE OF CASING USED:		5 Wrought iron	8	Concrete tile	CASING JOINTS: G	lued Clamped
1 Steel 3 RMP (SR)		6 Asbestos-Cement	. 9	Other (Specify b	elow) W	elded -
2 PVC 4 ABS		7 Fiberglass		`	•	hreaded
	4	U			_	
Blank casing Diameter 1 1/4 in.	to	ft., Dia	in.	to	ft., Dia in.	to ft.
Casing height above land surface 60	in.,	weight	_		Wall thickness or gauge No.	
TYPE OF SCREEN OR PERFORATION	MATERIAL:	£ Ethanalasa		PVC	10 Asbestos-ceme	
1 Steel 3 Stainless Steel		5 Fiberglass	8	RMP (SR)	11 other (specify) N/A
2 Brass 4 Galvanized steel		6 Concrete tile	9	ABS	12 None used (op	en hole)
SCREEN OR PERFORATION OPENIN	G ARE:	5 Gauze	d wrapped		8 Saw cut	11 None (open hole)
1 Continous slot 3 Mill slot		6 Wire w			9 Drilled holes	_
21					10 Other (specify)	/ =
1		7 Torch	cut		10 Other (specify) N/	A
SCREEN-PERFORATION INTERVALS	: from	ft. t	0	ft., Fron	n ft. to	r.
from		ft. to		ft., Fron	1 ft. to	ſt.
GRAVEL PACK INTERVALS: from		ft. to		ft., Fron		ſt.
from		ft. s	ft. to ft., Fi		n ft. to	ft.
6 GROUT MATERIAL: 1 Neat ceme	nt 2 C	ement grout	3 Bei	ntonite		hole plug
	to 5					
What is the nearest source of possible contamination:		ft. From	ft. to		ft. From 5 ft. to 28 ft. stock pens 14 Abandon weter well	
1					I storogo	
				11 Fuel st	130	oil well/Gas well
2 Sewer lines 5 Cess pool		12.7			rtilizer storage 16 Other (specify below)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage						
Direction from well? North How many feet? 10						
FROM TO LITE	IOLOGIC LOG		FROM	ТО	PLUGGING INTER	RVALS
			0	5	cement grout	
			5		bentonite hole	plug
				1-1		
				1		
					9-00-09-00-0-0-0-0-0-0-0-0-0-0-0-0-0-0-	

7 CONTRACTOR'S OR LANDOWNER'S CO	PRINCIPALION. Th	s water well was (4)	construct	ed (2) reconstr	ructed, or (3) plugged under n	ny jurisdiction and
CONTRACTOR BURLANDOWNERSCA	ERTIFICATION: Th	s water well was (1)	construct	ed, (2) reconstr	ucted, or (3) plugged under n	ny jurisdiction and
was completed on (mo/day/year)	11/28/9	<u>) ()</u> a	ind this red	ord is true to t	he best of my knowledge and	belief. Kansas Water
was completed on (mo/day/year) Well Contractor's License No2.3	11/28/9 36	<u>) ()</u> This Water Well Re	ind this red cord was c	ord is true to the completed on (n	he best of my knowledge and no/day/yr)12./.0.3	belief. Kansas Water
was completed on (mo/day/year)	11/28/9 36	<u>) ()</u> This Water Well Re	ind this red cord was c	ord is true to the completed on (n	he best of my knowledge and no/day/yr)12./.0.	belief. Kansas Water

Ę.