				Water Well Record	Form WWC-5	KSA 82a-1212		
1 LOCA		ATER WELL:	FRACTION			Section Number	Township Number	Range Number
	Sedg		SE 1/4		E 1/4	32	т 26 s	R 1E EW
Distance and direction frem nearest town or city street address of well if located within city?								
3102 N. Hood Wichita, Kansas								
WATER WELL OWNER: SHELTON, Tim								
RR#, ST. ADRESS, BOX#: 3102 N. Hood Board of Agriculture, Divivsion of Water Resource								
CIT	Y, STATE, ZI	PCODE: Wic	hita, Kansa	as			Application Number	or:
		LOCATION WITH	DEPTH OF CO	MPLETED WELL	45	ft. ELE	VATION:	
AN "X	" IN SECTION	N BOX:	Depth(s) groundy	vater Encountered	1	ft.	2 ft.	3 ft.
l Î		i i	WELL'S STATIC V	VATER LEVEL 18	FT.	BELOW LAND SUR	FACE MEASURED ON mo/day/yr	02/13/2001
	 NW	NE	Pump tes	st data: Well w	vater was	ft. a	fter hours pum	ping gpm
٠	1		Est. Yield	gpm: Well v	vater was	ft. s	after hours pum	ping gpm
M Mile	√ 	E	Bore Hole Diameter	12 in.	to 45	ft.	and in.	to ft.
-			WELL WATER TO	BE USED AS:	5 Public water	r supply 8	3 Air conditioning 11 I	njection well
3 Feedlot 6 Oil field water supply 9 Dewatering						Dewatering 12 (Other (Specify below)	
i I			2 Irrigation		7 Lawn and g	_	O Monitoring well	
+		S		eriological sample su	bmitted to De	partment? Yes	No X; If yes, n	10/day/yr sample was
submitted Water Well Disinfected? Yes X No								
		ASING USED:		5 Wrought iron		Concrete tile		lued X Clamped
1 Stee	el	3 RMP (SR)		6 Asbestos-Cemen	ıt 9	Other (Specify be	low) V	Velded
2 PV	C	4 ABS		7 Fiberglass	S	DR-26	7	`hreaded
	asing Diar	_	in. to 35	ft., Dia	in.	to	ft., Dia in.	to ft.
		ve land surface]		weight 2	.35	lbs. / ft. V	Wall thickness or gauge No.	.214
TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement								
1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 other (specify)								")
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)								
SCREEN OR PERFORATION OPENING ARE: 5 Gauzed							8 Saw cut	11 None (open hole)
1 Continous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes								
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)								
SCREE	N-PERFO	PRATION INTERV	ALS: from 35	ft.	to 45	ft., From	ft. to	ft.
			from	ft.	to	ft., From	ft. to	ft.
GRAVEL PACK INTERVALS: from 24				£n.	to 45	ft., From	ft. to	ft.
			from		ft. to ft., From		ft. to	ft.
GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug								
Grout Intervals: From ft. to ft. From ft. to ft. From 4 ft. to 24 ft.								
1		_					stock pens 14 Abandon water well	
1 Septic tank 4 Lateral lines				7 Pit privy		11 Fuel stor	- 13(Dil well/Gas well
2 Sewer lines 5 Cess pool				8 Sewage lago	on .	12 Fertilize		Other (specify below)
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage None Apparent								
Direction from well? How many feet?								
			LITHOLOGIC LOG		FROM	TO	PLUGGING INTE	RVALS
0 4	4 15	sandysoi	<u>. L</u>		-			
15	30	clay				-		
30	33	medium	sand		 		144	
33	45	clay						
33	45	meaium c	oarse sand					
				112.74	-	 		
					 	+ +		
					+			
	-				1			
		~~			1			
	<u> </u>					+ -		
	— —			<i>x</i>				
-	L	1			<u> </u>			
7 co	NTRACTO	OR'S OR LANDOWNE	R'S CERTIFICATION: Th	is water well was (1) constructe	ed, (2) reconstru	cted, or (3) plugged under n	ny jurisdiction and
was c	ompleted	on (mo/day/year)	02/13/	01	and this rec	ord is true to the	best of my knowledge and	belief. Kansas Water
Well C	ontracto	r's License No		This Water Well Re	cord was co	ompleted on (mo	o/day/yr)02/1	0./.01
Under	tne busi	ness name of.ಗಡೆ	rp Well &	T.MMDSETAT	.∺≅.v#Ŋ	M by (signa	Todd (S. Harp