I common on mum		ED A CETON	Water Well Recor	d Form WWC-5		T	
LOCATION OF WATE		FRACTION			Section Number	Township Number	Range Number
Sedgwic		NW 1/4		SW 1/4	22	T 26 s	R 1E E/W
		street address of well if lo	•				
4937 Wyndh	· · · · · · · · · · · · · · · · · · ·		chita, Kansa	18			
WATER WELL OW	2120714080	ND, John				Roard of Agricult	ture, Divivsion of Water Resource
RR#, ST. ADRESS, BO		Wyndham ta, Kansas				_	
CITY, STATE, ZIP CO			AND DONNE WALL	62	• 515	Application !	tumber:
LOCATE WELL'S LOC AN "X" IN SECTION B			MPLETED WELL vater Encountered	1	ft. ELE ft.	VATION: 2 ft.	3 ft.
t [} 	Depth(s) groundw WELL'S STATIC V				LFACE MEASURED ON mo/da	
		WELL'S STATIC W Pump tes	_	water was			
	NE	Est. Yield		water was			pumping gp pumping gp
ii w ₹		Bore Hole Diameter	12 in.	to 62	ft.	and	in. to ft
≅ w 🗡	1	WELL WATER TO		5 Public water	-	Air conditioning	11 Injection well
		1 Domestic	3 Feedlot	6 Oil field wa		Dewatering	12 Other (Specify below)
	s ic	2 Irrigation	4 Industrial	7 Lawn and	•	0 Monitoring well	
↓ <u>L</u>	L	Was a chemical/bact	eriological sample	submitted to I	Denartment? Yes	No X ; If y	es, mo/day/yr sample was
	S	submitted	on or ogrand		•		Yes X No
5 TYPE OF CASI	NG USED:		5 Wrought iron	8	Concrete tile	CASING JOINTS:	Glued X Clamped
1 Steel	3 RMP (SR)		6 Asbestos-Ceme	_	Other (Specify be	elow)	Welded
2 PVC	4 ABS		7 Fiberglass	S	DR-26		Threaded
Blank casing Diamete	er 5 i	in. to 25	ft., Dia	in.	to	ft., Dia	in, to ft.
Casing height above		in.,	weight 2	.35	lbs. / ft.	Wall thickness or gauge l	No214
TYPE OF SCREEN	OR PERFORAT	ION MATERIAL:			PVC	10 Asbestos	-cement
1 Steel 3	Stainless Steel		5 Fiberglass	8	RMP (SR)	11 other (sp	ecify)
2 Brass 4	Galvanized steel		6 Concrete tile	9	ABS	12 None use	ed (open hole)
SCREEN OR PERF	ORATION OPE	NING ARE:	5 Gau	zed wrapped		8 Saw cut	11 None (open hole
1 Continous slot	3 Mill slot	t	6 Wir	e wrapped		9 Drilled holes	
2 Louvered shutter	4 Key pur	nched	7 Torc	h cut		10 Other (specify)	
SCREEN-PERFORA	TION INTERVA	ALS: from 25	ft	. to 62	ft., From	ft	. to f
		from		. to	ft., From	ft.	. to f
GRAVEL PACK INTERVALS: from 24			f	t. to 62	ft., From	ft	t. to f
		from		t. to	ft., From		. to f
6 GROUT MATER		_ -	Cement grout	3 Be	ntonite	4 Other bentonit	
Grout Intervals: Fro		ft. to	ft. From	ft.		ft. From 4	ft. to 24 fi
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines			7 Pit privy			estock pens 14 Abandon water well el storage 15 Oil well/Cos well	
			• •			er storage	15 Oil well/Gas well
2 Sewer lines 5 Cess pool 3 Watertight sewer lines 6 Seepage pit				9 Feedyard 13 Insectició			16 Other (specify below)
Direction from well?	- 1 6	•	9 reedyard			J	
FROM TO		ITHOLOGIC LOG		FROM	то	How many feet? 13 PLUGGING I	
	opsoil	HINOLOGIC EGG		FROM	1 1	TECOGINOI	NI DICY ALS
	lay						
17 31 f	ine to me	dium sand					
31 62 g	rey shale						
							
					1		
		·					
7 CONTRACTOR'S	OR LANDOWNER'S	CERTIFICATION: Thi	s water well was	(1) construct	ted. (2) reconstr	ucted, or (3) pluaged u	nder my jurisdiction and
					the hest of my k	nowledge and belief	
Contractor's Licens	se No2361	This Water Well Re	cord was comple	ted on (mo/o	day/yr)	6-29-2001	
Contractor's Licens Under the business	s name of	Marp Well &	Pump Servic	e, Inc	by (signature)	1	
					·	To	rdd S. Harp