P-2d		WATER WELL RECORD	Form WWC-5	6 KSA 82a-	1010			
1 LOCATION OF WA	TER WELL: Frac	ion	. Sec	tion_Number	Township Numb	per Rang	e Number	
County: Sedgwick	( <i>N</i>	ENNE 450		20	т 26	S R	<b>/</b> ⊕w	
Distance and direction	from nearest town or city	street address of well if locate	ed within city?					
SE Cornery	14920 Jeanette	2. Wichita KS						
WATER WELL ON	INER: FPA REGIONAL,							
RR#, St. Address, Box # : 901 N. 5th Street				Board of Agriculture, Division of Water Resources				
City State ZIP Code KAASAS ("14" KS GADDI				Application Number:				
LOCATE WELL'S L	OCATION WITH A DEPTI	OF COMPLETED WELL.	44	# FLEVAT	ION.			
AN "X" IN SECTIO		Groundwater Encountered						
<del>,</del>	WELL'S	STATIC WATER LEVEL . 15	-2 # 1	elow land surf	ace measured on mo	1/day/yr 7/36		
†   i		Pump test data: Well wat					•	
NW	NE   Fet Viola							
<u> </u>	Boro Hole	Diameter . <b>8, 5</b> in. to	44		end	in to	fi	
w <del>  x</del>		ATER TO BE USED AS:	5 Public wate		8 Air conditioning	11 Injection w		
≦ "  ¦ 礼	1 i				•	2 Othe (Spe		
SW	SE	mestic 3 Feedlot	6 Oil field wa		9 Dewatering 0 Monitoring well			
!		gation 4 Industrial	-					
<u> </u>	· · · · · · · · · · · · · · · · · · ·	emical/bacteriological sample	submitted to De					
T 7/05 05 81 441/	s mitted				er Well Disinfected?			
TYPE OF BLANK		5 Wrought iron	8 Concre			S: Glued C	amped	
1 Steel	3 RMP (SR)	6 Asbestos-Cement		(specify below	•	Welded Ell	ish	
2 PVC	4 ABS	7 Fiberglass				(hreaded)	:T:X	
Blank casing diameter	in, to	.7 ft., Dia	in. to		ft., Dia	in. to	ft.	
	and surface FIUSh				t. Wall thickness or g	jauge No. JCM./	<i>.</i>	
	R PERFORATION MATER		OF PVC)			10 Asbestos-cement		
1 Steel 3 Stainless steel		5 Fiberglass	Fiberglass 8 RMP (SR)		11 Other (specify)			
2 Brass 4 Galvanized steel		6 Concrete tile	Concrete tile 9 ABS		12 None used (open hole)			
SCREEN OR PERFO	RATION OPENINGS ARE:	5 Gau	zed wrapped		8 Saw cut	11 None	(open hole)	
1 Continuous slot 3 Mill slot		6 Wire	6 Wire wrapped		9 Drilled holes			
2 Louvered shutter 4 Key punched		d 7 Torc	7 Torch cut		10 Other (specify)			
SCREEN-PERFORAT	ED INTERVALS: From.	-/ 4		ft., Fron	ı	ft. to		
	From.	ft. to .		ft., Fron	n	ft. to		
GRAVEL PA	CK INTERVALS: From.	ft. to .	. <b>44</b>	ft., Fron	1	ft. to		
	From	ft. to		ft., Fron	า	ft. to	ft.	
6 GROUT MATERIAI	.: 1 Neat cement		3 Bento					
Grout Intervals: Fro	m 3 ft. to !	0.5.2 Cement grout tt., From25	ft.	to 3.0	ft., From	ft. to		
	ource of possible contamina			10 Livest		14 Abandoned v		
1 Septic tank	4 Lateral lines	7 Pit privy		11 Fuel s		15 Oil well/Gas		
2 Sewer lines	5 Cess pool	8 Sewage lag	oon		zer storage	6 Othe (specif		
	ver lines 6 Seepage pit	9 Feedyard	y			Midland Refi		
Direction from well?		o i occijalu			y feet? 1300		7	
FROM TO	LITHO	LOGIC LOG	FROM	TO	PLUG	GING INTERVALS		
	Sandy Clay-drkbia							
5 85	Sand fike to med	um aranel						
8.5 11.5	Sand - Medunator	POSE Orainal						
H.5 34	Sand - Medium to co Sand - Medium to very	Croce Oranel		<del>                                     </del>				
34 44	Cond- Marco to Upl	Marie areal						
44	Sand-Coarse to very Walkered Shale- o	livo						
7/	WHATTER STUIL D	IIVC.		<del>                                     </del>				
-								

2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 15 Cetter (specify below)
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticite storage 15 Insection from well? 100 Insec

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.