DOC-	2		\A/A-TF	CONTENT DECOME		1840 S KOA 00	. 1010			
1 LOCATION	N,OF WAT	ER WELL:	Fraction	R WELL RECOR	RD Form V	Section Number		nber	Range Number	
County: Sec			NE 14		<u>SW 14</u>		T 26	s]	R / 🗇 w	
O- /			on or city street a nette , Wi(located within	city?				
		NER: EPA								
RR#, St. Add City, State, Z			s±streat City, KS 661	01			Board of Agriculture, Division of Water Resources Application Number:			
		CATION WITH	4 DEBTH OF C	OMPLETED WE	45	4 ELEV	ATION:			
AN "X" IN			Danth (a) Crauma	huster Englisher		7	2	# 2	4	
- —	- ^						urface measured on r			
1	i	i 1							nping gpm	
	NW	NE	· '	gpm: _Wel				•	nping gpm	
:	¦	<u> </u>		eter 16.5 i	1 1	مسدا	and	•		
* w -	<u> </u>			O BE USED AS		ic water supply	8 Air conditioning		njection well	
-		<u>i</u> l	1 Domestic	3 Feedlot		eld water supply	9 Dewatering		Other (Specify below)	
	sw	SE	2 Irrigation	4 Industria	al 7 Lawr	and garden only	10 Monitoring well !	nemed, a	Fion	
<u> </u>	- 1	i 1	Was a chemical/	bacteriological sai					mo/day/yr sample was sub	
	S		mitted		·	W	ater Well Disinfected	? Yes	No X	
TYPE OF	BLANK C	ASING USED:	•	5 Wrought iron	8	Concrete tile	CASING JOIN	TS: Glued	Clamped	
1 Steel	l	3 RMP (S	R)	6 Asbestos-Cer	ment 9	Other (specify belo	w)	Welde	- 1-	
2 PVC	>	4 ABS	سرب	7 Fiberglass				Thread		
			in, to	ft., Dia . ,	ويناوي ا	.in. to	ft., Dia	ir	1. to z., , , ft.	
Casing heigh	nt above la	nd surface. F.I.	(3ሳ	.in., weight 4	<i>4.</i> 7	Ibs	./ft. Wall thickness or	gauge No	. S <i>O</i> ? 7.0	
TYPE OF SC	CREEN OF	PERFORATIO	N MATERIAL:			7 PVC	10 Asbes	stos-cemer	nt	
1 Steel		3 Stainles:	s stee	5 Fiberglass		8 RMP (SR)	11 Other	(specify) .		
2 Brass	S	4 Galvaniz	ed steel	6 Concrete tile		9 ABS	12 None	used (ope	n hole)	
		ATION OPENIN		5	Gauzed wrap	ped	8 Saw cut		11 None (open hole)	
	inuous slot		ill slot		Wire wrapped	d	9 Drilled holes			
	ered shutte		ey punched	7	Torch cut 7	٠ . ـ				
SCHEEN-PE	HFOHATE	D INTERVALS:	2 .	2 .	10 42	•	om			
0.5	A)(E) DAG	N. 1417501444.0	From		10 . J.Y.	•	om			
GH	AVEL PAC	K INTERVALS:	20	ft.	11	•				
GROUT N	AATEDIAL :	1 Neat	From 30	π. 2 Cement grout	to 70	ft., Fro	Other	ft. to		
Grout Interva		2	/_	ft., From .	74	Bentonite 16	ft., From 2	8	ft to 300 ft	
	_	urce of possible					stock pens		andoned water well	
1 Seption		•	al lines	·			•	well/Gas well		
2 Sewe		5 Cess		8 Sewage lagoon			11 Fuel storage 12 Fertilizer storage		(specify below)	
		er lines 6 Seep	•	9 Feedyard			13 Insecticide storage Midland Paliner 9			
Direction from			-9- F	o i obayaid			How many feet? 1300			
FROM	то		LITHOLOGIC			ом то		IGGING IN	TERVALS	
0	5	Sandy Cla	y-drkbown,	F-coarse S	and					
5 8			to medium							
	11.5	Sand- Medit	um to coarse	grained						
			nto very coan							
34 4		Shid- COAS	to Very con	use grained						
44 4	15	weatherd S	bale-dive	. ,						
										
										
										
T										
_									er my jurisdiction and was	
completed on		•	/	<i>30[.0]</i>				27 ykno	wledge and belief. Kansas	
		License No			ater Well Rec	ord was completed		1110		
under the bus	siness nar	ne of <i>OCOTEL</i>	hnical Servi	ce, Inc.		by (sign		حم	THE VER	
INSTRUCTION	IONS: Use typ	pewriter or ball point	pen. PLEASE PRESS I Topeka, Kansas 6662	FIRMLY and <u>PRINT</u> cle P0-0001 Telephone: 91	arly. Please fill in	blanks, underline or circ d one to WATER WELL (le the correct answers. Sen OWNER and retain one for	nd top three co your records.	opies to Kansas Department	