L TRI CTION	Water Well Record	Form WWC-5	KSA 82a-1212		1 - 1
1 LOCATION OF WATER WELL: FRACTION		.	Section Number	•	Range Number
Sedgwick NW 1/4	NE 1/4 NV	1/4	4	T 26 S	R 1E E/W
Distance and direction from nearest town or city street address of well if located within city?					
615 E. 77th N. Wichita, K	ansas				
WATER WELLOWNER: HAYES CO.				Roard of Agriculture	Divivsion of Water Resource
RRM, ST. ADRESS, BOX #: 615 E. 77th N. CITY, STATE, ZIP CODE: Wichita, Kansas				_	
		30	. F	Application Numb	oer:
	MELL WELL water Encountered	1	ft. El	2 ft.	3 n.
	VATER LEVEL 18			SURFACE MEASURED ON mo/day/yr	9-12-2001
Pump te		ater was	ft.	after hours pu	mping gpm
Est. Yield		ater was	ft.	after hours pu	
Bore Hole Diameter		0	ft.	and in.	
≥ W WELL WATER	A 5	Public water		8 Air conditioning 11	Injection well
1 Domestic	3 Feedlot 6	Oil field was	er supply	9 Dewatering 12	Other (Specify below)
2 Irrigation	4 Industrial 7	Lawn and g	rden only	10 Monitoring well	
Was a chemical/bac	teriological sample sul	bmitted to D	epartment? Y	es X No ; If yes,	mo/day/yr sample was
S submitted	-		W	Vater Well Disinfected? Yes	No
5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped					
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (Specify below) Welded					
2 PVC 4 ABS	7 Fiberglass				Threaded
Blank casing Diameter, 6 in. to	ft., Dia	in.	to	ft., Dia in.	to ft.
Casing height were land surface 18 in.,	weight		lbs. / ft.	Wall thickness or gauge No. 10 Asbestos-cer	nont
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel	5 Fiberglass		PVC RMP (SR)		
1 Steel 3 Stainless Steel 2 Brass 4 Galvanized steel	6 Concrete tile		ABS	II other (speci	,
			ADS	12 None used (c	Il None (open hole)
Scale wild by the state of the				11 None (open noie)	
A Konstanting A Konstanting Control of the Control					. / >
	7 Torch				·
SCREEN-PERFORATION INTERVALS: from	ft. t	0	ft., Fro		
from	ft. (ft., Fr		
GRAVEL PACK INTERVALS: from	ft.		ft., Fr		•••
6 GROUT MATERIAL: 1 Neat cement 2 c	ft. : Cement grout	3 Ben	ft., Fr	om ft. to 4 Other bentonite	
Grout Intervals: From 18 4 to 7	ft. From			-	
What is the nearest source of possible contamination:		и. т	ft. to ft. From 7 ft. to 30 ft. 10 Livestock pens 14 Abandon water well		
1 Septic tank 4 Lateral lines 7 Pit privy			11 Fuel storage 15 Oil well/Gas well		
2 Sewer lines 5 Cess pool 8 Sewage lagoo		n	12 Fertilizer storage 16 Other (specify below)		
3 Watertight sewer lines 6 Seepage pit	9 Feedyard		13 Inse	atlalda atawawa	Apparent
Direction from well?					
FROM TO LITHOLOGIC LOG		FROM	TO	PLUGGING INT	ERVALS
		0	18"	natural earth bac	kfill
		18"	7	cement grout	
		7	30	bentonite hole pl	ng
		 			
7 CONTRACTOR'S OF LANDOWNER'S CERTIFICATION. T	ble weter well were	4) 00	lad (2) ====	naturated on (2) when and	lor my luriadiation and
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year)					
Water Well Contractor's License No		r Well Reco	rd was com	oleted on	,
(mo/day/yr) 9-14-2001					
Under the business name of Harp Well & Pump Service, Inc by (signature) Todd S. Harp					