1 LOCATION OF WATER WELL:	FRACTION	Water Well	Record Form WWC-	KSA 82s-1212 Section Number	Township Number	Range Number	
Ľ	.l	C 17	NE 1/4	18	26	1 172	
	NE 1/4	SE 1/4	NE 1/4	7.0	T 26 S	R III E/W	
Distance and direction from nearest town or cit 5944 Palm Lane		cated within city? hita, Kan	sas				
	OR, Gale	•		1000 N			
RR#, ST. ADRESS, BOX #: 5944 Palm Lane Board of Agriculture, Divission of Water Resource							
CITY, STATE, ZIP CODE: Wich		Application Number:			er:		
LOCATE WELL'S LOCATION WITH	4 DEPTH OF cd	MINATER WE	LL 26	n. El	LEVATION:		
AN "X" IN SECTION BOX:	Depth(s) grounds	vater Encounter	red 1	ft.	2 ft.	3 ft.	
	WELL'S STATIC V	VATER LEVE	L 18 FT	BELOW LAND	SURFACE MEASURED ON mo/day/yr	10-11-2001	
NW NE	Pump tes	t data: V	Vell water was	ft.	after hours pun	nping gpm	
	Est. Yield	gpm: V	Vell water was	ft.	after hours pun	nping gpm	
E E	Bore Hole Diameter	•< i	ı. to	ſt.	and in.	to ft.	
	WELL WATER	E USED AS:			•	Injection well	
	1 Domestic	3 Feedlot	6 Oil field wa		ŭ	Other (Specify below)	
	2 Irrigation	4 Industrial	7 Lawn and	garden only	10 Monitoring well		
S	Was a chemical/bac	teriological sam	ple submitted to l	•	· · ·	no/day/yr sample was	
Submitted Water Wen Districted. 165 X 170							
5 TYPE OF CASING USED: 1 Steel 3 RMP (SR)		5 Wrought	-	Concrete tile		Glued Clamped	
		6 Asbestos-C 7 Fiberglass	-	Other (Specify	,	Velded Threaded	
2 PVC 4 ABS		ŭ					
Blank casing Diameter 1 1/4 Casing height asset land surface 6	in. to	•	ia in.		ft., Dia in.	to ft.	
Casing height Reserve land surface 50 in., TYPE OF SCREEN OR PERFORATION MATERIAL:			weight lbs. / ft. Wall thickness or gauge No. 7 PVC 10 Asbestos-cement				
1 Steel 3 Stainless Steel 5 Fiberglass				8 RMP (SR) 11 other (specify) N/A			
2 Brass 4 Galvanized ste	6 Concrete tile 9 ABS		ABS	12 None used (open hole)			
SCREEN OR PERFORATION OPENING ARE:		5 Gauzed wrapped			8 Saw cut 11 None (open hole)		
1 Continous slot 3 Mill slot		6 Wire wrapped			9 Drilled holes		
2 Louvered shutter 4 Key pr	7 1	7 Torch cut 10 Other (specify) N/A			/A		
SCREEN-PERFORATION INTERV	ALS: from	•	ft. to	ft., Fro		ft.	
	from		ft. to	ft., Fro		ſt.	
GRAVEL PACK INTERVALS: from		ft. to		,	From ft. to ft.		
		ft, to ft., From			ft.		
6 GROUT MATERIAL: 1 Neat	cement 2 (Cement grout	3 Ber	ntonite	4 Other bentonite	hole plug	
Grout Intervals: From ft. to		ft. From ft. to		to	ft. From 2 ft. to 26 ft.		
What is the nearest source of possible contamination:					restock pens 14 Abandon water well		
1 Septic tank 4 Lateral lines		7 Pit privy			11 Fuel storage 15 Oil well/Gas well		
2 Sewer lines 5 Cess pool		19 1			ertilizer storage 16 Other (specify below) secticide storage None Apparent		
1			receivand and apparent			Apparent	
Direction from well? FROM TO		How many feet? FROM TO PLUGGING INTERVALS			DVALC		
	LITHOLOGIC LOG		0	2	surface clay and a		
			2	26	bentonite hole plu		
		· · · · · · · · · · · · · · · · · · ·					
				-			
					····		
				+ +			
				 			
				1			
				1			
7 CONTRACTOR'S OR LANDOWNE		hla 111-4		oted (2) ====	naturated on (9) when and a con-	nu mase legala di adi	
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year)							
Water Well Contractor's License	e No	This	Water Well Rec	ord was come	o to the best of my knowledge eleted on	, und Dellei. Italisas	
(mo/day/yr) 10-12-2001	(mo/day/yr)10-12-2001						
Under the business name of Harp Well & Pump Service, Inc by (signature) Todd S. Harp							