1 LOCATION OF WATER WELL:	FRACTION	Water Well Record	i Form WWC-5		T =	T 5
Sedgwick	l	NTW 6	17.7	Section Number 17	Township Number	Range Number
	1 #/-		SW 1/4	1/	T 26 s	R 1E E/W
Distance and direction frem nearest town or city street address of well if located within city?						
5609 N. Armstrong		ta, Kansas				
1 1	WAY, Roy				Donal of Amilantona D	dalada a CW-4 Darama
RR#, ST. ADRESS, BOX #: 5609 N. Armstrong  CITY, STATE, ZIP CODE: Wichita, Kansas  Application Number:						
	<del></del>	<u> </u>	40		Application Numbe	r:
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		IPLETED WELL	40		VATION:	
N N	Depth(s) groundwa		. 1	ft.	2 ft.	3 ft.
	WELL'S STATIC W				FACE MEASURED ON mo/day/yr	12-4-2001
NW	Pump test		water was		ifter hours pum	
	Est. Yield	OI.	water was	ft. a	after hours pum	. o or
<b>                                    </b>	Bore Hole Diameter	12 in.	to 40	ft.	and in.	to ft.
	WELL WATER TO		5 Public water		•	njection well
1	1 Domestic		6 Oil field wa		· ·	Other (Specify below)
	2 Irrigation		7 Lawn and 1	•	) Monitoring well	
Was a chemical/bacteriological sample submitted to Department? Yes  No X; If yes, mo/day/yr sample was						
submitted water well Disinfected? Yes X No						
5 TYPE OF CASING USED:		5 Wrought iron		Concrete tile	CASING JOINTS: G	lued X Clamped
1 Steel 3 RMP (SR)		6 Asbestos-Ceme	nt 9	Other (Specify be	•	Velded
2 PVC 4 ABS		7 Fiberglass	SI	DR-26	Т	`hreaded
Blank casing Diameter 5	in. to 30	ft., Dia	in.	to	ft., Dia in.	to ft.
Casing height above land surface 12		weight 2	.35	lbs. / ft.	Wall thickness or gauge No.	.214
TYPE OF SCREEN OR PERFORAT	ΓΙΟΝ MATERIAL:	# 17th 1		PYC	10 Asbestos-ceme	
1 Steel 3 Stainless Steel		5 Fiberglass		RMP (SR)	11 other (specify	•
2 Brass 4 Galvanized stee		6 Concrete tile	9	ABS	12 None used (op	oen hole)
SCREEN OR PERFORATION OPE	5 Gauz	zed wrapped		8 Saw cut	11 None (open hole)	
1 Continous slot 3 Mill slo	6 Wire wrapped			9 Drilled holes		
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)						
SCREEN-PERFORATION INTERVALS: from 30			to 40	ft., From	ft. to	ft.
	from	ft.	to	ft., From	ft. to	ft.
GRAVEL PACK INTERV	ALS: from 24		to 40	ft., From	ft. to	ft.
	from	ft.	. to	ft., From	ft. to	ft.
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug						ole plug
Grout Intervals: From	ft. to	ft. From	ft.	to	ft. From 4	ft. to 24 ft.
What is the nearest source of possible contamination:				10 Livestoc		bandon water well
1 Septic tank 4 Lateral lines		7 Pit privy		11 Fuel sto	rage 15 (	Dil well/Gas well
2 Sewer lines 5 Cess pool					ertilizer storage 16 Other (specify below)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage						
Direction from well? West How many feet? 58						
	ITHOLOGIC LOG		FROM	ТО	PLUGGING INTE	RVALS
0 3 topsoil						
3 15 fine sand						
15 25 medium san	<u>d</u>					
25 40 coarse san	d					
			<b></b>			
			_			
		····				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and						
was completed on (mo/day/year)	12-4-200	1	, <del>u constitu</del> and this	record is true to	the best of mv knowledge	and belief. Kansas
Water Well Contractor's License	No. 236	This Wat	er Well Reco	ord was complet	ed on	
(mo/day/yr) 12-5-2001						
Under the business name of Harp Well & Pump Service, Inc by (signature)						