	DD + CTION	Water Well Record	Form WWC-5			1
LOCATION OF WATER WELL:	FRACTION	GTP C'		Section Number	F	Range Number
Sedgwick Distance and direction from nearest town or c	SW 1/4	SE 1/4 SI	E 1/4	31	T 26 s	R 1E E/W
Distance and direction frem nearest town or city street address of well if located within city? 3161 Cromwell Wichita, Kansas						
	, John	Ilta, Ramaa				
1 1 022/	, John 1 Cromwell				Board of Agriculture, ?	Divivsion of Water Resource
	hita, Kansas				Application Number	
LOCATE WELL'S LOCATION WITH		Mgg Do WELL	40	ft. EI	LEVATION:	
AN "X" IN SECTION BOX:	Depth(s) groundw	~ ~	1	ft.	2 ft.	3 ft.
	WELL'S STATIC W	VATER LEVEL 18	FT.	BELOW LAND	SURFACE MEASURED ON mo/day/yr	2-20-2002
NW NE -	Pump test	t data: Well w	vater was	ft.	after hours pun	nping gpm
<u>u</u>	Est. Yield	gpm: Well w	water was	ft.	after hours pun	nping gpm
E W	Bore Hole Diameter	D C	to	ft.	and in.	to ft.
	WELL WATER 1 Domestic	TUSED AS: 5	Public water			Injection well
sw	2 Irrigation		6 Oil field wa 7 Lawn and g		9 Dewatering 12 (10 Monitoring well	Other (Specify below)
	Was a chemical/bacto	_			J	no/day/yr sample was
S	submitted	el lological sample su	Dillitted to 2		Vater Well Disinfected? Yes	_
5 TYPE OF CASING USED:		5 Wrought iron	8	Concrete tile	0.07310.000	Glued Clamped
1 Steel 3 RMP (SR)		6 Asbestos-Cemen		Other (Specify		Welded Clamped
2 PVC 4 ABS		7 Fiberglass			•	Threaded
Blank casing Diameter 6	in. to	ft., Dia	in.	to	ft., Dia in.	to ft.
Casing height above land surface 3		weight		lbs. / ft.	Wall thickness or gauge No.	
TYPE OF SCREEN OR PERFORA	5 Fiberglass	7 PVC 10 Asbestos-cement Fiberglass 8 RMP (SR) 11 other (specify) 37/3				
1 Steel 3 Stainless Steel 2 Brass 4 Galvanized ste		6 Concrete tile		ABS	11 other (specify	-1/ 11
SCREEN OR PERFORATION OPENING ARE:			7.120		12 None used (open hole) 8 Saw cut 11 None (open hole)	
1 Continous slot 3 Mill sl			ed wrapped wrapped		9 Drilled holes	
	punched	7 Torch			10 Other (specify) N/	/ 7.
SCREEN-PERFORATION INTER	•	ft.		ft., Fro	,,	/A ft.
SCREEN LESS	from	n. i		ft., Fro ft., Fro		
GRAVEL PACK INTER			ft. to ft., From			ft.
	from	ft.		ft., Fro	**	ft.
0 011001	t cement 2 C	Cement grout	3 Ben	itonite	4 Other bentonite h	
Grout Intervals: From	ft. to	ft. From	ft. t		ft. From 3	ft. to 40 ft.
What is the nearest source of possible 1 Septic tank		7 Dit neivy				Abandon water well
	ral lines	7 Pit privy 8 Sewage lagoo		11 Fuel s	150	Oil well/Gas well
2 Sewer lines 5 Cess 3 Watertight sewer lines 6 Seep	•	8 Sewage Iagoo 9 Feedyard	12 1		rtilizer storage 16 Other (specify below) secticide storage None Apparent	
3 Watertight sewer lines 6 Seep Direction from well?	page pit	y Feeuyaru			o None	Apparent
	LITHOLOGIC LOG		FROM	то	How many feet? PLUGGING INTE	RVALS
			0	3	surface clay and s	ilt
	-		3	40	bentonite hole plu	g
				1		
						40.000
	307-30-40-1		+	++		
				+		
			-	1		
						Top Page
		and the second second				
was completed on (mo/day/year Water Well Contractor's License	ar)2-20-200 se No236) 2 This Water	and this r r Well Reco	record is true ord was compl	eleted on	and belief. Kansas
(mo/day/yr)2-22-2002 Under the business name of	Harp Well &	Pump Service	, Inc	by	(signature) Todd	S. Harp