Trock	TION OF N	A MINTER SELECT Y	ED (CTION	Water Well Re	cord Form WWC-		·	
LOCATION OF WATER WELL: Sedgwick			FRACTION			Section Number	Township Number	Range Number
			NE 1/4	SW 1/4	32	T 26 S	R 1E E/W	
Distance and direction frem nearest town or city street address of well if located within city? 802 W. 32nd N. Wichita, Kansas								
WATER WELL OWNER: SHORE, Kevin								
	ST. ADRESS	BHOKE	7. 32nd N.				Board of Agriculture, I	Divivsion of Water Resource
1	, STATE, ZI		ta, Kansas				Application Number	er:
LOCAT	TE WELL'S			OMPLETED WEL	L 40	ft. EL	EVATION:	
	" IN SECTIO			lwater Encountered		ft.	2 ft.	3 ft.
l t			, .	WATER LEVEL		. BELOW LAND SU	URFACE MEASURED ON mo/day/yr	6-21-2002
	NW.	NE			ll water was	ft.	after hours pun	nping gpm
	-NW-		Est. Yield	gpm: We	ell water was	ft.	after hours pun	
l ii w			Bore Hole Diamete	r 12 in.	to 40	ft.	and in.	to ft.
= "		VI 1-1	WELL WATER T	O BE USED AS:	5 Public wat	er supply	8 Air conditioning 11 I	njection well
1	-sw-	siE	1 Domestic	3 Feedlot	6 Oil field w	ater supply	9 Dewatering 12 (Other (Specify below)
		ĪĪ	2 Irrigation	4 Industrial	7 Lawn and	garden only	10 Monitoring well	
+	Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was							
S submitted Water Well Disinfected? Yes X No								
5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped								
1 Stee		3 RMP (SR)		6 Asbestos-Cer	ment 9	Other (Specify	,	Velded
2 PVC	_	4 ABS		7 Fiberglass	S	DR-26	7	Threaded
	asing Dian		in. to 25	ft., Dia	in.	to	ft., Dia in.	to ft.
Casing height above land surface 12 in., weight 2.35 lbs./ft. Wall thickness or gauge No 214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement								
1 Stee			HON MATERIAL	: 5 Fiberglass		S RMP (SR)	10 Asbestos-cem	
2 Bras		3 Stainless Steel 4 Galvanized stee		6 Concrete tile			11 other (specify	•
						ABS	12 None used (o	
								11 None (open hole)
	red shutte	3 Mill slo			ire wrapped		9 Drilled holes	
					rch cut		10 Other (specify)	
SCREE	N-PERFU	RATION INTERV		5	ft. to 40	ft., Fron	n ft. to	ft.
			from		ft. to	ft., Fron		ft.
GRAVEL PACK INTERVALS: from 24				4	ft. to 40	ft., Fro		ft.
from ft. to ft., From ft. to ft. 6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug								
Grout Intervals: From 4 5: to 24								
				ft. From	ft.	to 10 Livesto	ft. From	ft. to ft. Abandon water well
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines			7 Pit privy			tamaa		
2 Sewer lines 5 Cess pool				8 Sewage lagoon		131	Oil well/Gas well Other (specify below)	
3 Water	rtight sew	-		_	9 Feedyard 13 Insecticide storage			Selici (specify below)
Direction from well? West How many feet? 50								
FROM TO LITHOLOGIC LOG				G	FROM			RVALS
	4	sandy soil						
4	10	clay						
	20	fine sand						
20	40	medium coa	rse sand					
						1		
 								
┝┯┵								
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and								
was completed on (mo/day/year)								
I								
(mo/day/yr)6-24-2002 Under the business name of Harp Well & Pump Service, Inc								
Under the business name of Harp Well & Pump Service, Inc by (signature) Jodd S. Harp								