LOC	ATION OF W	ATER WELL:	FRACTION	Water Well Re	cord Form WWC-				
Sedgwick			l	<b>6</b> 7		Section Number	Township Number	Range Number	
			SE 1/4	SE 1/4	34	T 26 s	R 1E E/W		
Distance and direction frem nearest town or city street address of well if located within city?									
Hwy. 96 & Hillside, 1/4 M. S., W. side Wichita, Kansas									
WATER WELL OWNER: WICHITA, CITY OF									
RR#	ST. ADRESS		. Main				Board of Agriculture, I	Divivsion of Water Resource	
CIT	Y, STATE, ZI	PCODE: Wichi	ta, Kansas			67202	Application Number	er: 20020096	
		LOCATION WITH 4	DEPTH OF CO	MPLETED WEL	L 30	ft. ELE	EVATION:		
AN ">	(" IN SECTIO	ON BOX:	Depth(s) groundw	vater Encountered	d 1	ft.	2 ft.	3 ft.	
1 1			WELL'S STATIC V	VATER LEVEL	8 гт	. BELOW LAND SUI	RFACE MEASURED ON mo/day/yr	6-17-2002	
	NW	NE	Pump tes	t data: We	ll water was	ft.	after hours pun	nping gpm	
			Est. Yield	gpm: We	ell water was	ft.	after hours pun		
Mile A	v	F B	Bore Hole Diameter	12 <sub>in.</sub>	to 30	ft.	and in.	to ft.	
= '	1		WELL WATER TO	BE USED AS:	5 Public water			njection well	
1.			1 Domestic	3 Feedlot	6 Oil field w		· ·	Other (Specify below)	
	-sw-	SE X	2 Irrigation	4 Industrial	7 Lawn and		0 Monitoring well	(1 ,	
				eriological sampl			<del>-</del>	10/dav/vr sample was	
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted water Well Disinfected? Yes X No								• • •	
TYPE OF CACING HOPP.									
1 Ste	el	3 RMP (SR)		5 Wrought iro 6 Asbestos-Cer		Other (Specify b		Aued & Clamped Velded	
2 PV	r	4 ABS		7 Fiberglass		Other (Specify b		veided Threaded	
<u> </u>	asing Dian		in. to 20	ŭ					
1	_	ve land surface 12		ft., Dia	in.	•••	ft., Dia in.	to ft.	
		EN OR PERFORAT		weight	2.35	lbs. / ft. / PVC	Wall thickness or gauge No. 10 Asbestos-cem-	.214	
1 Ste		3 Stainless Steel	ION MATERIAL.	5 Fiberglass		RMP (SR)			
2 Bra		4 Galvanized steel		6 Concrete tile		O ABS	11 other (specify		
1						ADS	12 None used (o)		
	inous slot	RFORATION OPEN			auzed wrapped		8 Saw cut	11 None (open hole)	
1		3 Mill slot		6 W	ire wrapped		9 Drilled holes		
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)									
SCREEN-PERFORATION INTERVALS: from 20 ft. to 30 ft., From ft. to							ft.		
1			from		ft. to	ft., From	ft. to	ft.	
GRAVEL PACK INTERVALS: from 20					ft. to 30	ft., From	ft. to	ft.	
<u> </u>			from		ft. to ft.,		ft. to	ft	
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug									
	ntervals:		ft. to 20	ft. From	ft. From ft. to		ft. From	ft. to ft.	
What is the nearest source of possible contamination:						10 Livesto		bandon water well	
1 Septic tank 4 Lateral lines				7 Pit privy		11 Fuel sto	orage 15 (	15 Oil well/Gas well	
2 Sewer lines 5 Cess pool				8 Sewage lagoon		12 Fertiliz		16 Other (specify below)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage None Apparent								Apparent	
Direction from well?									
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS								RVALS	
0	4	topsoil							
4	10	clay							
10	27	fine sand							
27	30	shale							
		10 W- 34-1-							
L									
							-		
							A COMPANY OF THE PROPERTY OF T		
						1			
7						<u> </u>			
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and									
was completed on (mo/day/year)									
l									
(mo/day/yr) 0-19-2002 Tall & Pump Service Inc.									
Under the business name of Harp Well & Pump Service, Inc by (signature)									