				Water Well Record	Form WWC-5	KSA 82a-1212		
1 LOCA		ATER WELL:	FRACTION			Section Number	Township Number	Range Number
Sedgwick NE 1/4			SE _{1/4} SI	E 1/4	34	T 26 S	R 1E E/W	
Distance and direction frem nearest town or city street address of well if located within city?								
Hwy. 96 & Hillside, 1/4 M. S., W. side Wichita, Kansas								
WATER WELL OWNER: WICHITA, CITY OF								
1	ST. ADRESS		N. Main nita, Kansas			C7202		Divivsion of Water Resource
	Y, STATE, ZI			CONTRACTOR STATE I	30	67202	Application Number	er: 20020096
	TE WELL'S " IN SECTIO	LOCATION WITH ON BOX:	Depth(s) groundw	MPLETED WELL	30 1	ft. ELE ft.	EVATION: 2 ft.	3 ft.
1		N T	WELL'S STATIC W	_			RFACE MEASURED ON mo/day/yr	σ π. 6-17-2002
		1	Pump tes		ater was		after hours pum	
		NE	Est. Yield		vater was	ft.	after hours pum	
1 Mile	,	E	Bore Hole Diameter	1.0	to 30	ft.	and in.	to ft.
Ξ.			WELL WATER TO	BE USED AS: 5	Public water	· supply		njection well
1	-sw-		1 Domestic		Oil field wat	er supply	9 Dewatering 12 C	Other (Specify below)
		Y	2 Irrigation	4 Industrial 7	Lawn and ga	arden only 1	10 Monitoring well	
+			Was a chemical/bact	eriological sample su	bmitted to D	•		no/day/yr sample was
S submitted Water Well Disinfected? Yes X No								
		ASING USED:		5 Wrought iron	_	Concrete tile		Glued X Clamped
1 Ste		3 RMP (SR)		6 Asbestos-Cement	t 9(Other (Specify b	•	Velded
2 PVC 4 ABS 7 Fiberglass Threaded Blank casing Diameter 5 in. to 20 ft., Dia in. to ft.								
	_	neter > ve land surface 1	in. to 20	ft., Dia	in.	to	ft., Dia in.	to ft.
			in. , ATION MATERIAL:	weight 2.		lbs. / ft. PVC	Wall thickness or gauge No. 10 Asbestos-ceme	.214 ent
1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 other (specify)								
2 Bra	iss	4 Galvanized ste		6 Concrete tile		ABS	12 None used (or	•
SCREI	EN OR PE	RFORATION OP	ENING ARE:	5 Gauze	ed wrapped		8 Saw cut	11 None (open hole)
1	inous slot	3 Mill s		6 Wire v	• •		9 Drilled holes	` -
2 Louve	ered shutte	er 4 Key p	unched	7 Torch	cut		10 Other (specify)	
SCREE	N-PERFO	RATION INTER	VALS: from 20		to 30	ft., From		ft.
			from	ft. 1		ft., From		ft.
					to 30	ft., From	•	ft.
from ft. to ft., Fro							n ft. to	ft.
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug								
Grout Intervals: From 0 ft. to 20 ft. From ft. to ft. From ft. to								
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy						10 Livestock pens 14 Abandon water well		
46 "						11 Fuel storage 12 Fertilizer storage		Oil well/Gas well
1	2 Sewer lines 5 Cess pool 8 Sewage lagoo 3 Watertight sewer lines 6 Seepage pit 9 Feedyard						aida atauau	Other (specify below) Apparent
I	_	•	oage pit	y recuyaru			None	Apparent
Direction from well? How many feet? FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS								RVALS
0	4	topsoil						
4	10	clay						
10	27	fine sand						
27	30	shale					114.0000000	
						ļ		
		*****		W. A. S. C.				
				***			Manufacture survey or a	
						 		
			1 11 11 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	THE MAN AND AND AND AND AND AND AND AND AND A			AND CONTRACTOR AND ADDRESS OF THE PARTY OF T	
1								
							12,000,000	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and								
was completed on (mo/day/year)								
Water Well Contractor's License No								
(mo/day/yr) 6-19-2002								
Under the business name of Harp Well & Pump Service, Inc by (signature)								