				Water Well Record	Form WWC-5	KSA 82a-1212		
1 LOCA		ATER WELL:	FRACTION	N NE SWSW	,	Section Number	Township Number	Range Number
	Sedgw	ick	872 , 1/4	207 _{1/4} 451	U 1/4	19	T 26 s	R 1E E/W
Distance and direction frem nearest town or city street address of well if located within city?								
2205 Timbercreek Wichita, Kansas								
WATER WELL OWNER: SHELTON, Jack								
RR#, ST. ADRESS, BOX #: 2205 Timbercreek Board of Agriculture, Divivsion of Water Resource								
CITY	, STATE, ZI	PCODE: Wichi	ita, Kansas				Application Numb	er:
	TE WELL'S		4 DEPTH OF COM	APLETED WELL	42	ft. ELE	VATION:	
1	INSECTION	N BOX.	Depth(s) groundw		1	ft.	2 ft.	3 ft.
			WELL'S STATIC W			BELOW LAND SUI	RFACE MEASURED ON mo/day/yr	5-22-2002
'	NW-	NE	Pump test		ater was	ft.	after hours pun	nping gpm
<u> </u>	i		Est. Yield		ater was		after hours pun	
N Zij	/	1 1 1	Bore Hole Diameter	•	to 42	ft.	and in.	to ft.
1			WELL WATER TO		Public water			Injection well
11	sw-		1 Domestic		Oil field wat Lawn and ga		•	Other (Specify below)
			2 Irrigation	,			0 Monitoring well	
'	<u> </u>	S	Was a chemical/bacto submitted	eriological sample su	bmitted to D			no/day/yr sample was
TYPE OF CAMPING YORD								
1 Stee		3 RMP (SR)		5 Wrought iron 6 Asbestos-Cemen	_	Concrete tile Other (Specify be		Glued X Clamped Velded
2 PV	r	4 ABS		7 Fiberglass	•	R-26	,	reided Threaded
	=_ asing Diar		in. to 22	ft., Dia	in.	to	ft., Dia in.	
t	•	ve land surface 12		weight 2.			Wall thickness or gauge No.	to ft. . 214
			TION MATERIAL:	weight = 1		PVC	10 Asbestos-cem	
1 Ste	el	3 Stainless Steel		5 Fiberglass	8	RMP (SR)	11 other (specify	y)
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS							12 None used (o	pen hole)
SCREE	N OR PE	RFORATION OPE	NING ARE:	5 Gauze	d wrapped	wrapped 8 Saw cut		11 None (open hole)
1 Continous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes								
2 Louve	ered shutte	er 4 Key pu	nched	7 Torch	cut		10 Other (specify)	
SCREEN-PERFORATION INTERVALS: from 22 ft. to 42 ft., From ft. to ft.								
			from	ft.		ft., From		ft.
GRAVEL PACK INTERVALS: from 2				ft. to 42		ft., From		ft.
—			from	ft.	to	ft., From	ft. to	ft.
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug								
Grout Intervals: From 2 ft. to 22 ft. From					ft. t	ft. to ft. From		ft. to ft.
What is the nearest source of possible contar				7 1 1 1		10 Livestoo		Abandon water well
1 Septic tank 4 Lateral lines				7 Pit privy		11 Fuel sto	15	Oil well/Gas well
2 Sewer lines 5 Cess pool				8 Sewage lagoon		12 Fertiliz		Other (specify below)
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage								
Direction from well? South How many feet? 20							DVALC	
0	4	topsoil	ATMOLOGIC LOG		FROM	 	PEUGGING INTE	KYALS
4	10	clay						
10	25	medium san	ıd					
25	42	coarse san	ıd					
							· · · · · ·	
					L			
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and								
was completed on (mo/day/year)5-22-2002 and this record is true to the best of my knowledge and belief. Kansas								
Water Well Contractor's License No								
(mo/day/yr) 5-23-2002								
Under the business name of Harp Well & Pump Service, Inc. by (signature) Todd S. Harp								