1 LOCATION OF WATER WELL:	FRACTION	Water Well Record	Form WWC-	Section Number	Township Number	Range Number
Sedgwick	SW 1/4	SE 1/4 S	E 1/4	25	26	1E
Distance and direction frem nearest town or city street address of well if loca			E 1/4		T 26 §	R IE E/W
6212 E. 37th N. Wichita, Kansas						
	TAL MANAGE					
RR#, ST. ADRESS, BOX #: 300 N. Main, Suite 201  Board of Agriculture, Divivsio					ivivsion of Water Resource	
CITY, STATE, ZIP CODE: Wichita		67202 Application Number:			r:	
LOCATE WELL'S LOCATION WITH 4 DEPTH OF COMPLETED WELL 95 ft. ELEVATION:						
AN "X" IN SECTION BOX:	epth(s) groundw	ater Encountered	1	ft.	2 ft.	3 ft.
WE	LL'S STATIC W	ATER LEVEL 40	FT	. BELOW LAND SU	URFACE MEASURED ON mo/day/yr	6-27-2002
	Pump tes		vater was	ft.	after hours pum	ping gpm
NW NE Est.	Yield		water was	ft.	after hours pum	
Pore	Hole Diameter	in.	to	ft.	and in.	to ft.
E WE	LL WATER		io Public wate			njection well
1 ' ' [ ]	1 Domestic		6 Oil field w		U	other (Specify below)
SW			7 Lawn and		ŭ	ther (Specify below)
1 1 1 1 1 1 1 1 1 1 1 1	2 Irrigation				10 Monitoring well	
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was						
submitted Water Well Disinfected? Yes X No						
5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped						
1 Steel 3 RMP (SR)		6 Asbestos-Cemer	ıt 9	Other (Specify	below) W	Velded
2 PVC 4 ABS		7 Fiberglass			Т	hreaded
Blank casing Diameter 5 in.	to	ft., Dia	jn.	to	ft., Dia in.	to ft.
Casing height above land surface 36	in.,	weight		lbs. / ft.	Wall thickness or gauge No.	
TYPE OF SCREEN OR PERFORATION	N MATERIAL:		7	7 PVC	10 Asbestos-ceme	ent
1 Steel 3 Stainless Steel		5 Fiberglass	8	RMP (SR)	11 other (specify	) N/A
2 Brass 4 Galvanized steel		6 Concrete tile	9	ABS	12 None used (or	
SCREEN OR PERFORATION OPENIN	G ARE:	5 Gauz	ed wrapped		8 Saw cut	11 None (open hole)
1 Continous slot 3 Mill slot		6 Wire wrapped		9 Drilled holes		
5 Min siot						
/ Toren cut				A		
SCREEN-PERFORATION INTERVALS	: from	ft.	to	ft., Fron	n ft. to	ft.
from		ft. to		ft., Fron	n ft. to	ft.
GRAVEL PACK INTERVALS: from		ft. to		ft., Froi	m ft. to	ft.
from		ft. to ft., Fr		ft., Fron	om ft. to ft.	
6 GROUT MATERIAL: 1 Neat ceme	nt 2 C	ement grout	3 Be	ntonite	4 Other bentonite h	ole plug
Grout Intervals: From ft.	to	ft. From	ft.	to	ft. From 3	ft. to 45 ft.
What is the nearest source of possible contamination:			10 Lives		stock pens 14 Abandon water well	
1 Septic tank 4 Lateral lines		7 Pit privy 11 Fuel		storage 15 Oil well/Gas well		
2 Sewer lines 5 Cess pool		8 Sewage lagoon 12 Fer		12 Fertili	tilizer storage 16 Other (specify below)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage None Apparent						
Direction from well?		•			How many feet?	
	OLOGIC LOG		FROM	то	PLUGGING INTE	RVALS
			0		surface clay and s	
			3		bentonite hole plu	
			45		chlorinated sand a	
						J
					* Maria ha	ALTERNATION AND AND AND AND AND AND AND AND AND AN
				T		
			-	-		
						<del>an national de la accession des constantes de la constante de</del>
						A Trippe of Court of Court of
7 CONTRACTOR'S OR LANDOWNER'S CO	EDTIFIC : TIC: Th	ie water well	(1) constr	oted (2) =====	structed or (2) plusted us de	r my juriediation and
ONTRACTOR'S OR LANDOWNER'S CO was completed on (mo/day/year)	6 - 27 - 200	us water well was ) 2				
Water Well Contractor's License No.	236	This 18/-4-	anu tnis v Well Bee	ord was compl	to the best of my knowledge	and belief. Nansas
Water Well Contractor's License No						
Under the business name of Harp Well & Pump Service, Inc. by (signature)  Jodd S. Harp						
Under the dusiness name of						