LOCA	TION OF WA	FRACTIO	N	Wa	ter Well Reco	rd Form W	WC-3	KSA 82a-1212 Section Number	Township Numl	her	Range N	umber		
Sedgwick				l		SW 1/4 SW				26		1 12		
				2. 4	<b>Σ</b> Μ 1.	/4	32	T 26	S	R	E/W			
Distance and direction from nearest town or city street address of well if located within city?  3033 Schnitzler Wichita, Kansas														
$\overline{}$	TER WELL O	<del></del>			,									
	ST. ADRESS,	KBIII,		er						Board o	of Agriculture, D	ivivsion of Water I	Resource	
CITY, STATE, ZIP CODE: Wichita, Kansas  Application Number:														
<del></del>		OCATION WITH 4			4DI ETE	PLETED WELL 40 ft. ELEVATION:								
	" IN SECTIO	N POV:							it. EL.	2	ft.	3	ft.	
1 +				oth(s) groundwater Encountered 1 ft. 2 ft. 3 ft. 2 st. 10-14-2002  L'S STATIC WATER LEVEL 15 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr 10-14-2002										
					ALEKI t data:						• •			
] '	-NW-	NE		mp tes		-	water wa		ft.	after	hours pum		gpm	
<u> </u>			. Yield		gpm: 12		water wa	18	ft.	after	hours pum		gpm	
ij w			e Hole Dia			in.		4_	ft.	and	in.	to	ft.	
			ELL WATE 1 Domesti		BE USE 3 Feed		5 Public v		er supply ater supply	8 Air conditioning 9 Dewatering		njection well ther (Specify	halaw)	
11	sw		2 Irrigatio		4 Indu					10 Monitoring well		thei (Specify	DCIOW)	
	<b>X</b>		_						<u> </u>	_		- /-l/	ala waa	
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/d submitted Water Well Disinfected? Yes X											•			
submitted water well disinfected: Yes A No														
1 Stee						ought iron		_	Concrete tile CASING JOINTS: Glued X Clamped					
										Other (Specify below) Welded R-26 Threaded				
2 PVC	_	4 ABS	. 25			J			DR-26			nreageg		
L	asing Dian		to 25		ft.,	Dia		in.		ft., Dia	in.	to	ft.	
		ve land surface 12 EN OR PERFORATIO	N MATER	in.,		weight 2	4.35	_	lbs. / ft. PVC	Wall thickness or	gauge No. sbestos-ceme	. 21	-4	
1 Ste		3 Stainless Steel	M MAIRN	IAL.	5 Fiber	glass			RMP (SR)		ther (specify			
2 Bra		4 Galvanized steel				rete tile			ABS			•		
			NG ADD		o cone			_	ADS	8 Saw cut	one used (op	11 None (o	non holo)	
1	N OK PEI nous slot	RFORATION OPENI	NG ARE:		5 Gauzed wrapped 6 Wire wrapped					9 Drilled holes		11 140116 (0	pen noie)	
1		3 Mill slot												
ł	red shutte					7 Tore				10 Other (spec	ily)			
SCREE	N-PERFO	RATION INTERVAL	S: from	m 25		fi	t. to 40		ft., Fron	n	ft. to		ft.	
ļ			fro				t. to		ft., Fron	n	ft. to		ft.	
	GRAV	EL PACK INTERVAI		m 24		f	it. to 40		ft., Froi		ft. to		ft.	
6 GROUT MATERIAL: 1 Neat cement 2 Co					ft. to				ft., From		ft. to		ft.	
_			2 <u>C</u>	ement g	ement grout 3 Be			ntonite	4 Other bent	onite hole plug				
	ntervals:		. to 24		ft.	From		ft.		ft. From		ft. to	ft.	
What is the nearest source of possible contamination:  1 Septic tank  4 Lateral lines				7 Dit aries				10 Livesto	•	14 Abandon water well		well		
				7 Pit privy				11 Fuel storage 12 Fertilizer storage		15 Oil well/Gas well				
2 Sewer lines 5 Cess pool 3 Watertight sewer lines 6 Seepage pit					8 Sewage lagoon				icide storage	16 Other (specify below)				
		F B -	pit		9.	Feedyard			15 111500	J				
Direction from well? West FROM TO LITHOLOGIC LOG					FROM			13.4	TO I	How many fee	et? 15 GING INTERVALS			
0	4	topsoil	HOLOGIC	LUG		-	FRU	) Y1	TO	PLUG	GING INTE	RVALS		
4	10	clay							1 1					
10	20	fine sand					+							
20	40	medium sand	110 153				1							
	1								1			<del></del>	****	
									i i					
			# TEC.											
					*****									
									1					
									<u> </u>					
										* *********				
			,											
17								_		-44 4			4:	
7 CO	NTRACTO	OR'S OR LANDOWNER'S	CERTIFICATI 1 0 - 1	ION: TI	nis wate 002									
was c	ompleted	l on (mo/day/year) tractor's License N		236		Th:- 14'	and	tnis	record is true	to the best of my	knowledge	and Dellet.	nansa <b>s</b>	
1	-	0 16 0000												
Undo	ay/yf) <del></del> r the buci	ness name ofH	arp Wel	1 &	Pump	Servi	ce, In	C	hv	(signature)	Toda	S. Ha	20	
I Cilue	riie nusi					······································			Бу	(B.:=,a, a)	J NINU	J. 0 120	7	