LOCATION OF WATER WELL:			FRACTION	Water Well	Record Form WWC-	Section Number		Range Number	
Sedgwick			NW 1/4	NW 1/4	NE 1/4	27	26	112	
Sedgwick NW 1/4 NW 1/4 NE 1/4 Z/ T 20 S R LE E/W Distance and direction frem nearest town or city street address of well if located within city?									
Intersection of 45th N. & Hillside, 3/8 m. W. on S. side Wichita, Kansas									
WATER WELL OWNER: WICHITA, CITY OF									
RR#, ST. ADRESS, BOX #: 455 N. Main Board of Agriculture, Division of Water Resource									
CITY	, STATE, ZU	CODE: Wichi	ta, Kansas				Application Number:		
LOCATE WELL'S LOCATION WITH 4 DEPTH OF COMPLETED WELL 30 ft. ELEVATION:									
AN "X	IN SECTIO	N .	, .	dwater Encounte		ft.	2 ft.	3 ft.	
			WELL'S STATIC		L		SURFACE MEASURED ON mo/day/		
1	NW	NE	•	_	Vell water was	ft.	•	oumping gpm	
N Kije	'		Est. Yield Bore Hole Diamete	81	Well water was n. to 30	ft. ft.		oumping gpm in. to ft.	
≥ w		1 , 121	WELL WATER T	- ·-				n. to tt. 1 Injection well	
	;		1 Domestic	3 Feedlot	6 Oil field w			2 Other (Specify below)	
	-sw-	- SE-	2 Irrigation	4 Industrial	7 Lawn and	garden only	10 Monitoring well		
	Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample wa								
S submitted Water Well Disinfected? Yes X No									
5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped									
1 Stee		3 RMP (SR)		6 Asbestos-C	-	Other (Specify	y below)	Welded	
2 PVC 4 ABS 7 Fiberglass SDR-26 Threaded									
	ising Dian		in. to 20		ia in		ft., Dia in		
	_	ve land surface 12 EN OR PERFORAT			ght 2.35	lbs. / ft. 7_PVC	Wall thickness or gauge No 10 Asbestos-c		
1 Stee		3 Stainless Steel		5 Fiberglass		RMP (SR)	11 other (spe	cify)	
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)									
SCREEN OR PERFORATION OPENING ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)									
1 Continous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes									
2 Louve	red shutte	er 4 Key pur	nched	7 3	Forch cut		10 Other (specify)		
SCREE	N-PERFO	RATION INTERVA	ALS: from 2	0	ft. to 30	ft., Fr	om ft.	to ft.	
			from		ft. to	ft., Fr	om ft.	to ft.	
GRAVEL PACK INTERVALS: from 20				20	ft. to 30		om ft.		
from ft. to ft., From ft. to GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug									
Crout Intervals, Even 0 6 4 20									
What is the nearest source of possible contamination:				ft. From	ft. From ft. to		ft. From stock pens 1	ft. to ft. 4 Abandon water well	
1 Septic tank 4 Lateral lines				7 Pit pr	7 Pit privy			15 Oil well/Gas well	
2 Sewer lines 5 Cess pool				8 Sewage	8 Sewage lagoon		ilizer storage	16 Other (specify below)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage None Apparent									
Direction from well? How many feet?									
FROM	TO 4	topsoil	<u>ITHOLOGIC LO</u>	G	FROM	ТО	PLUGGING IN	TERVALS	
0 4	15	clay							
15	22	fine sand	· · · · · · · · · · · · · · · · · ·						
22	30	shale		-					
	w					1			

					<u> </u>				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and									
was completed on (mo/day/year)1-20-2003									
Water Well Contractor's License No									
(mo/day/yr) 1-22-2003 Under the business name of Harp Well & Pump Service, Inc by (signature) **Todd S. Harp**									
Under the business name of naip well a rump service, lic by (signature)									