	WATER WE	LL RECORD	Form WV	VC-5 K	(SA 82a-121	2		
1 LOCATION OF WATER WELL:	FRACTION	NE co		TION NUMBE	1	_	RANGE N	
Sedgwick	SE 1/4	NE 1/4 SE	1/4	21	T 26	5 S	R 1E	: E/W
Distance and direction from nearest 4821 N. Hydraulic	Wichita, Kans	sas						
2 WATER WELL OWNER:	SERVICEMASTE	R				Board of Agric	culture, Division of W	/ater Resource
RR#,ST. ADDRESS,BOX #: CITY, STATE:	4821 N. Hydraulic Wichita, Kansas			P CODE:	57219	Application Num		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BO	4 DEPTH OF COMPL	ETED WELL:	67 ft.		ELEVATION:			
N N	Depth of groundwater I		ft.			ft.		ft.
	WELL'S STATIC WAT	ER LEVEL 33	FT. BELC	W LAND S	URFACE MEASU	RED ON mo/d	ay/yr: 4/3 /	03
NE NW	1	p test data: Well w	ater was		ft. after		of pumping @	gpm
w Wile	Est. Yield:	01	ater was		ft. after		of pumping @	gpm
2 W	Bore Hole Diameter WELL WATER TO BE	in. LISED AS:	to	fi	and	in.	to 11 Injer	ft. ction well
swse2	\1 I		ater supply	7. Lawn	and garden only	> Dewaterir	12. Other (Sp	
	2. Irrigation 4. I	ndustrial 6. Oil field	water supply	8. Air co	nditioning	10. Monitorin	g weli	
S	submitted	ological sample submitted to	Department?	YES Was	NO Water Well Disinfo		/hat mo/day/yr w	vas sample NO
5 TYPE OF CASING USI	ED: 5. Wrought II	ron 7. Fiberglas	s 9. O	ther (Specif	y below) CAS	ING JOINTS:	Glued	Threaded
_	4. ABS 6. Asbestos-	Cement 8. Concrete	tile				Welded	Clamped
Blank casing diameter	5 in. to	ft., Dia.	in.	to	ft., [Dia. i	n. to	ft.
Casing height above land sur	face: 36 in.,	Weight:	11	bs. / ft.		ckness or gaug	e No.	
TYPE OF SCREEN OR PERF			"	55. 7 11.				
1. Steel 3. Stainle	ss Steel 5. Fiberglass	7. PVC	9. A	BS	11. Oth	ner (specify) N	l/A	
2. Brass 4. Galvan	ized 6. Concrete Til	e 8. RMP (SR)	10. A	sbestos-Ce	ment 12. No	ne used (open l	nole)	
SCREEN OR PERFORATION	OPENINGS ARE:							
1. Continuous slot	3. Mill slot 5. G	auzed wrapped	7. To	rch cut	9. Drille	ed holes	11. None (o	pen hole)
2. Louvered shutter	4. Key punched 6. W	ire wrapped	8. Sa	w cut	10. Othe	er (specify) N/	Α	
SCREEN - PERFORATION IN	TERVAL From	ft.	to	ft.,	From	ft.	to	ft.
	From	ft.	to	ft.,	From	ft.	to	ft.
GRAVEL PACK INTE	RVALS: From	ft.	to	ft.,	From	ft.	to	ft.
	From	ft.	to	ft.,	From	ft.	to	ft.
6 GROUT MATERIALS:	1. Neat cement	2. Cement Grout		3. Bentonite		Other bente	onite hole plu	ıg
Grout Intervals: From ft. to ft., From ft. to ft., From 3 ft. to 35 ft.								
What is the nearest source of p	oossible contamination: 4. Lateral lines 7.	Pit privy	10. Livestoc	k pens	13. Insectio	cide storage	15. Oil well/G	ias well
1	4. Laterar illies	Sewage lagoon	11. Fuel sto	rage		on water well	16. Other (sp	ecify below)
None Apparent								parent
3. Watertight sewer line Direction from well?	o. Seepage pit	,	,		How ma	ny feet?		
From To	LITHOLOGIC	LOG	From	То	I	LITHOLO	GIC LOG	******
			0	0.5	concrete flo	or		
			0.5	3	surface clay			
			35	35 67	bentonite ho chlorinated		vol	
			1 33	V /	Ciliorniated	Sanu & gra	YEI	
			-	ļ	ļ			
					 			
			†					
			_				·	
								-
7 Contractor's or Landows	er's Certification: This water w	vell was 1 construct	ed 2 re	constructe	d or 3, (olugged t	ınder my jurisdict	ion and
	4.2.2002				knowledge and b		,,	
was completed on (mo/day/					-		2002	
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 4-7-2003								
under the business name of Harp Well & Pump Service Inc. by (signature) Jodd S. Jarp								