WATER WELL RECORD Form WWC-5 KSA 82a-1212 LOCATION OF WATER WELL: SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER Sedgwick SE SE NE 1E 22 26 E/W 1/4 1/4 1/4 Т S Distance and direction from nearest town or city street address of well if located within city? 53rd N. & Hillside, 1/2 mile South of 53rd on West side, Falcon Falls Addition Wichita, Kansas RUSSELL, J. DEVELOPMENT WATER WELL OWNER: Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: 13701 Onewood Wichita, Kansas CITY, STATE: ZIP CODE: Application Number: 100 **ELEVATION:** 4 DEPTH OF COMPLETED WELL: ft. LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: Depth of groundwater Encountered: ft ft. ft. N 20 WELL'S STATIC WATER LEVEL FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 4/28/04 Pump test data: Well water was ft. after hours of pumping @ gpm ΝW NE hours of pumping @ gpm Est. Yield: Well water was ft. after apm Ξ 12 to 100 ft Bore Hole Diameter and in. WELL WATER TO BE USED AS: 11. injection well 9. Dewatering 5. Public water supply 7. Lawn and garden only SW SE 3. Feedlot 1. Domestic 12. Other (Specify below) 10. Monitoring well 4. Industrial 6. Oil field water supply 8. Air conditioning ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO) (YES Was Water Well Disinfected? submitted 5 TYPE OF CASING USED: CASING JOINTS: Glued Threaded 9. Other (Specify below) 5. Wrought Iron 7. Fiberglass 3. RPM (SR) 1. Steel Welded Clamped SDR-26 8. Concrete tile Asbestos-Cement 2. PVC 4. ABS Blank casing diameter 5 to 30 Dia. ft., Dia. ft. ft.. in. 12 Casing height above land surface: in., 2.35 Wall thickness or gauge No. Weight: lbs. / ft. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 11. Other (specify) 3. Stainless Steel 9. ABS 1. Steel 5. Fiberglass 8. RMP (SR) 12. None used (open hole) 2. Brass 4. Galvanized 6. Concrete Tile 10. Asbestos-Cement SCREEN OR PERFORATION OPENINGS ARE: 9. Drilled holes 11. None (open hole) 1. Continuous slot 3. Mill slot 7. Torch cut 5. Gauzed wrapped 8. Saw cut 2. Louvered shutter 4. Key punched 6. Wire wrapped 10. Other (specify) SCREEN - PERFORATION INTERVAL 30 100 ft. to ft., From ft. to ft From to ft., From ft. GRAVEL PACK INTERVALS: 24 100 ft. to ft. From ft.. From ft. From ft. to From ft. ft. Other **GROUT MATERIALS:** bentonite hole plug 2. Cement Grout 1. Neat cement 3. Bentonite Grout Intervals: 4 ft. 24 ft.. ft., ft. ft. to From What is the nearest source of possible contamination: 10. Livestock pens 15. Oil well/Gas well 7. Pit privv 13. Insecticide storage 1. Septic tank 4. Lateral lines 16. Other (specify below) 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 5. Cess Pool 2. Sewer lines 9. Feed yard 12. Fertilizer storage 3 Watertight sewer line 6. Seepage pit How many feet? 11 Direction from well? From LITHOLOGIC LOG LITHOLOGIC LOG Τо From Τo 0 4 topsoil 4 10 clav 10 20 lfine sand 90 20 shale 90 100 llimestone under my jurisdiction and Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged 4/28/2004 and this record is true to the best of my knowledge and belief. was completed on (mo/day/year) 4/30/2004 This water well record was completed on (mo/day/year) 236 Kansas Water Well Contractor's License No. by (signature) Jodd S. Harp under the business name of Harp Well & Pump Service Inc.