WATER WELL RECORD Form WWC-5 KSA 82a-1212 1 LOCATION OF WATER WELL: SECTION NUMBER TOWNSHIP NUMBER FRACTION RANGE NUMBER Sedgwick NE NW 1/4 1/4 1/4 30 Т 26 S 1E E/W Distance and direction from nearest town or city street address of well if located within city? 45th N. and Meridian, 1/4 E. on South side Wichita, Kansas WICHITA, CITY OF WATER WELL OWNER: Board of Agriculture, Division of Water Resource 455 N. Main RR#,ST. ADDRESS,BOX #: 20040103 Wichita, Kansas CITY, STATE: Application Number: ZIP CODE: LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 48 4 DEPTH OF COMPLETED WELL: **ELEVATION:** ft. Depth of groundwater Encountered: ft. WELL'S STATIC WATER LEVEL 12 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 5/12/04 Well water was Pump test data: ft. after hours of pumping @ apm NE NW hours of pumping @ Est. Yield: Well water was ft. after gpm ≌ Bore Hole Diameter 12 48 and ft, WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering 5. Public water supply 7. Lawn and garden only SW SE 3. Feedlot 12. Other (Specify below) 6. Oil field water supply 8. Air conditioning 10. Monitoring well 2. Irrigation 4. Industrial ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO YES NO submitted Was Water Well Disinfected? TYPE OF CASING USED: 9. Other (Specify below) CASING JOINTS: Glued Threaded 5. Wrought Iron Fiberglass 3. RPM (SR) 1. Steel Welded Clamped SDR-26 6. Asbestos-Cement 8. Concrete tile 2. PVC 4. ABS Blank casing diameter 20 Dia. ft., Dia. ft. in. to ft., in. to in. to 10 Casing height above land surface: in., 5.52 Weight: lbs. / ft. Wall thickness or gauge No. .332 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 1. Steel 3. Stainless Steel 5. Fiberglass 9. ABS 11. Other (specify) 8. RMP (SR) 2. Brass 12. None used (open hole) 6. Concrete Tile Galvanized 10. Asbestos-Cement SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 9. Drilled holes 11. None (open hole) 5. Gauzed wrapped 7. Torch cut 2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify) SCREEN - PERFORATION INTERVAL From to ft. From ft ft. From ft. to ft.. From ft ft. 20 GRAVEL PACK INTERVALS: ft. 48 From ft., From ft. to ft. From ft to From ft.. ft. **GROUT MATERIALS:** Other 1. Neat cement 2. Cement Grout 3. Bentonite bentonite hole plug Grout Intervals: From U 20 ft From From ft. What is the nearest source of possible contamination: 10. Livestock pens 15. Oil well/Gas well 7. Pit privy 13. Insecticide storage 1. Septic tank 4. Lateral lines 16. Other (specify below) 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 2. Sewer lines 5. Cess Pool None Apparent 9. Feed yard 12. Fertilizer storage 3. Watertight sewer line 6. Seepage pit Direction from well? How many feet? From . Τо LITHOLOGIC LOG From To LITHOLOGIC LOG sandy soil 10 3 clay 10 18 medium sand 18 40 coarse sand 40 48 medium coarse sand under my jurisdiction and Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. 5/12/2004 and this record is true to the best of my knowledge and belief. was completed on (mo/day/year) 236 This water well record was completed on (mo/day/year) 5/14/2004 Kansas Water Well Contractor's License No. under the business name of Harp Well & Pump Service Inc. by (signature) Jodd S. Harn