Form WWC-5 WATER WELL RECORD KSA 82a-1212 LOCATION OF WATER WELL: SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER Sedgwick NE 1/4 NW1/4 NW 1/4 30 Т 26 S R 1**E** E/W Distance and direction from nearest town or city street address of well if located within city? 43rd N. & Meridian then East (Harbour Isle) Wichita, Kansas WICHITA, CITY OF WATER WELL OWNER: Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: 455 N. Main 20040103 Wichita, Kansas CITY, STATE: Application Number: ZIP CODE: LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 4 DEPTH OF COMPLETED WELL: 47 **ELEVATION:** ft. ft. ft. Depth of groundwater Encountered: WELL'S STATIC WATER LEVEL 12 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: Pump test data: Well water was ft. after hours of pumping @ apm -NW NE Est. Yield: Well water was ft. after hours of pumping @ gpm apm ≌ Bore Hole Diameter 12 ft. and to WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering - SW SE 7. Lawn and garden only 1. Domestic 3. Feedlot 5. Public water supply 12. Other (Specify below) 10. Monitoring well 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO) (YES) submitted Was Water Well Disinfected? NO TYPE OF CASING USED: CASING JOINTS: Glued Threaded 9. Other (Specify below) 7. Fiberglass 5. Wrought Iron 1. Steel 3. RPM (SR) Welded Clamped SDR-26 6. Asbestos-Cement 8. Concrete tile 2. PVC 4. ABS 8 Blank casing diameter in. 27 ft.. Dia. in Dia to to ft.. in to ft. Casing height above land surface: Weight: 5.52 lbs. / ft. Wall thickness or gauge No. .332 TYPE OF SCREEN OR PERFORATION MATERIAL: 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify) 1. Steel 12. None used (open hole) 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 6. Wire wrapped 8. Saw cut 10. Other (specify) 4. Key punched SCREEN - PERFORATION INTERVAL ft., From From to ft. From ft. to From ft., ft. ft. GRAVEL PACK INTERVALS: 20 From ft.. From ft. to ft. From ft to ft.. From ft. **GROUT MATERIALS:** Other bentonite hole plug 1. Neat cement 2 Cement Grout 3. Bentonite Grout Intervals: 0 From ft 20 ft., ft. From to ft.. What is the nearest source of possible contamination: 7. Pit privy 10. Livestock pens 15. Oil well/Gas well 13. Insecticide storage 1. Septic tank 4. Lateral lines 16. Other (specify below) 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 2. Sewer lines 5. Cess Pool None Apparent 9. Feed yard 12. Fertilizer storage 3. Watertight sewer line 6. Seepage pit Direction from well? How many feet? From Τо LITHOLOGIC LOG LITHOLOGIC LOG From To 0 topsoil 4 clav fine sand 15 20 20 30 gravel 30 47 medium sand under my jurisdiction and plugged Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. 5/20/2004 and this record is true to the best of my knowledge and belief. was completed on (mo/day/year) 236 This water well record was completed on (mo/day/year) Kansas Water Well Contractor's License No. by (signature) Jodd S. Haro under the business name of Harp Well & Pump Service Inc.