			WATERW	ELL REC	CORD F	orm WV	VC-5 P	(SA 82a-12	12			
111	ON OF WATE	R WELL:	FRACTION	NIXXI .	37337	I .	TION NUMBE			RANGE N		
Sedg			NE 1/4		1/4 NW	1/4	30	T 2	6 S	R 1	E E/W	
Distance and direction from nearest town or city street address of well if located within city? 45th North and 1/4 mile East of Meridian on South side Wichita, Kansas												
2 WATER WELL OWNER: WICHITA, CITY OF												
	ADDRESS		N. Main	-					Board of Agric	culture, Division of		
	CITY,	STATE: Wich	iita, Kansas			Z	P CODE:		Application Num	nber: 200	40103	
	E WELL'S LC	CATION 4	DEPTH OF COMP	LETED WEL	L: 4'	7 ft.		ELEVATION:				
T WITH	AN "X" IN SEC N	TION BOX:	oth of groundwate	r Encountere	d:	ft			ft.		ft.	
	X	WE	ELL'S STATIC WA	ATER LEVEL	. 8	FT. BELC	W LAND S	JRFACE MEASU	JRED ON mo/d	ay/yr: 6/2	:/04	
	-MM	NE	Pu	mp test data:	Well wat	er was		ft. after	hours	of pumping @	gpm	
w Mile			Est. Yield:	gpm	Well wa			ft. after	hours	of pumping @	gpm	
\ _		'	ore Hole Diameter ELL WATER TO E		in.	to 4	17 ft	. and	in.	to	ft.	
l`. }-	-sw	I B		Feedlot	: 5. Public wa	ter supply	7. Lawn	and garden only	9. Dewaterin	المستقد	ction well pecify below	
	'	2.	. Irrigation 4.	Industrial	6. Oil field w	ater supply	8. Air co	nditioning	10. Monitorin	g well		
' -	s		/as a chemical/bacte	riological samp	le submitted to [Department?	YES	NO		vhat mo/day/yr	•	
	DE 05 04 0		bmitted				Was	Water Well Disin		=	NO	
<u> </u>	PE OF CAS 1. Steel	SING USED: 3. RPM (SR	5. Wrought	Iron	7. Fiberglass	9. O	ther (Specif	y below) CAS	ING JOINTS: (Glued	Threaded	
·	2. PVC	> 4. ABS	6. Asbesto	s-Cement	8. Concrete ti	le SD	R-26			Welded	Clamped	
	sing diamete	-	in. to	24 ft.,	Dia.	in.	to	ft.,	Dia. i	in. to	ft.	
Casing h	eight above	land surface;	12 _{in}		Weight:	5.52	bs. / ft.	Wall th	ickness or gaug	je No. .332	!	
Casing height above land surface: 12 in., Weight: 5.52 lbs. / ft. Wall thickness or gauge No332 TYPE OF SCREEN OR PERFORATION MATERIAL:												
1. Stee	el 3	. Stainless Steel	Fiberglass		7. PVC	9. A	BS	11. Ot	her (specify)			
2. Bra	ss 4	. Galvanized	6. Concrete 1	Tile 8	B. RMP (SR)	10. A	sbestos-Ce	ment 12. No	ne used (open	hole)		
SCREEN	OR PERFO	RATION OPENING	SS ARE:									
1. Cont	1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7.							7. Torch cut 9. Drilled holes 11. None (open hole)				
2. Louv	2. Louvered shutter 4. Key punched 6. Wire wrapped 8. S							10. Oth	er (specify)			
SCREEN	- PERFORA	TION INTERVAL	From	24 ft	. to	38	ft.,	From	ft.	to	ft.	
			From	ft			ft.,	From	ft.	to	ft.	
6	RAVEL PA	CK INTERVALS:	From	20 ft.	. to	47	ft.,	From	ft.	to	ft.	
			From	ft.	. to		ft.,	From	ft.	to	ft.	
6 GRO	UT MATERI	ALS: 1 Neat o	cement	2 Comor	at Grout		3. Bentonite					
7. Near center. 2. Centers Grout 5. Bentonite Best on the prug											6 ft.	
What is the nearest source of possible contamination:												
1. Septi	1. Septic tank 4. Lateral lines						46. Other (energy balon					
2. Sewer lines 5. Cess Fool None Appears												
	rtight sewe from well?	r line 6. Seepag	ge pit 9	. Feed yard	1	2. Fertilize	r storage	L I marria mara		Tione 24	ppurciic	
From	To		LITHOLOGIC	CLOG		From	То	How ma	ITHOLO	GIC I OG		
0	4	topsoil	LITTOLOGIC	0 100		1 10111	10		LITTIOLO	GIC LOG		
4	8	sandy soil										
8	47	sand										
						-		1		,		
	 				-	-		<u> </u>				
												
						<u> </u>						
<u></u>	-					 	-		······································			
-												
<u> </u>				<u> </u>								
Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and												
was completed on (mo/day/year) 6/2/2004 and this record is true to the best of my knowledge and belief.												
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 6/4/2004												
under the business name of Harp Well & Pump Service Inc. by (signature) Jo d d S. Harp												