WATER WELL RECORD Form WWC-5 KSA 82a-1212 LOCATION OF WATER WELL: SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER Sedgwick NE 1/4 NW NW30 26 1E E/W 1/4 1/4 Т S R Distance and direction from nearest town or city street address of well if located within city? 45th North and 1/4 mile East of Meridian on South side Wichita, Kansas WICHITA, CITY OF WATER WELL OWNER: Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: 455 N. Main 20040103 Wichita, Kansas CITY, STATE: ZIP CODE: Application Number: 4 DEPTH OF COMPLETED WELL: 47 ft. **ELEVATION:** LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: ft. ft. Depth of groundwater Encountered: ft. Ν WELL'S STATIC WATER LEVEL 6/2/04 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: Pump test data: Well water was ft. after gpm -NW NF-Est. Yield: Well water was ft. after hours of pumping @ gpm apm Ξ 12 to 47 Bore Hole Diameter ft. and in WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering 7. Lawn and garden only SW SE-1 Domestic 3. Feedlot 5. Public water supply 12. Other (Specify below) 10. Monitoring well 2. Irrigation 8. Air conditioning 4. Industrial 6. Oil field water supply ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO) (YES Was Water Well Disinfected? 5 TYPE OF CASING USED: CASING JOINTS: Glued 9. Other (Specify below) Threaded 7. Fiberglass 5. Wrought Iron 3. RPM (SR) 1. Steel Welded Clamped SDR-26 8. Concrete tile 6. Asbestos-Cement 4. ABS 2. PVC Blank casing diameter 8 24 Dia. ft. in. to ft.. to Dia in 18 Casing height above land surface: Weight: 5.52 lbs. / ft. Wall thickness or gauge No. .332 TYPE OF SCREEN OR PERFORATION MATERIAL: 3. Stainless Steel 7. PVC 9. ABS 11. Other (specify) 5. Fiberglass 1. Steel 2. Brass 6. Concrete Tile 8. RMP (SR) 12. None used (open hole) 4. Galvanized 10. Asbestos-Cement SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 7. Torch cut 9. Drilled holes 11. None (open hole) 5. Gauzed wrapped 8. Saw cut 2. Louvered shutter 10. Other (specify) 6. Wire wrapped 4. Key punched SCREEN - PERFORATION INTERVAL 24 37 fŧ From to ft., From to ft. ft. From to ft., From ft. 24 GRAVEL PACK INTERVALS: ft. to From ft.. From ft. From ft. to ft., From ft. ft. 6 **GROUT MATERIALS:** Other bentonite hole plug 1. Neat cement 2. Cement Grout 3. Bentonite Λ Grout Intervals: ft From 20 ft., ft. ft. to ft.. From What is the nearest source of possible contamination: 10. Livestock pens 15. Oil well/Gas well 7. Pit privy 13. Insecticide storage 1. Septic tank 4. Lateral lines 16. Other (specify below) 11. Fuel storage 14 Abandon water well 5. Cess Pool 8. Sewage lagoon 2 Sewer lines None Apparent 9. Feed yard 12. Fertilizer storage 6. Seepage pit 3. Watertight sewer line Direction from well? How many feet? From To LITHOLOGIC LOG LITHOLOGIC LOG From То 4 0 topsoil 4 8 lsandy soil 47 8 sand plugged under my jurisdiction and Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 6/2/2004 was completed on (mo/day/year) and this record is true to the best of my knowledge and belief. 236 This water well record was completed on (mo/day/year) Kansas Water Well Contractor's License No. Jodd S. Harp by (signature) under the business name of Harp Well & Pump Service Inc.