	WATER WELL RE	CORD For	rm WWC-5	KSA 82a-1212	<u> </u>		
1 LOCATION OF WATER WELL:	FRACTION		SECTION NU	MBER TOWNSHIP	NUMBER	RANGE NUMB	ER
Sedgwick	NE 1/4 NW		1/4 30	Т 26	S	R 1E	E/W
Distance and direction from nearest town or							
45th North and 1/4 mile		ıth side		Wichita, Kan	sas		
	ICHITA, CITY OF				December Accionships	Divinion of Motor	. Daa
_	55 N. Main				Board of Agriculture		
	ichita, Kansas		ZIP COD	E: .	Application Number:	2004010	03
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WI	ELL: 47	ft.	ELEVATION:			
N N SECTION BOX:	Depth of groundwater Encounter	red:	ft.		ft.		ft.
	WELL'S STATIC WATER LEVE	L 10 F	T. BELOW LAN	D SURFACE MEASUR	ED ON mo/dav/vr:	6/9/04	
NW	Pump test dat			ft. after	hours of pu	****	gpm
1 ' 1 '- 1 1	Est. Yield: gpm	Well water		ft. after	hours of pu		gpm
W Hile	Bore Hole Diameter 12		to 47	ft. and	in.	to	ft.
-	WELL WATER TO BE USED A	S:			9. Dewatering	11. Injection	
swse	1. Domestic 3. Feedlot	5. Public water	supply 7. La	wn and garden only		2. Other (Specif	
	2. Irrigation 4. Industrial	6. Oil field water	ersupply 8. Ai	r conditioning	10. Monitoring we	11	
S	Was a chemical/bacteriological san	nple submitted to Dep				mo/day/yr was s	sample
	submitted			Vas Water Well Disinfe	ted? YES	<u>ои</u>	
5 TYPE OF CASING USED:	5. Wrought Iron	7. Fiberglass	9. Other (Sp	pecify below) CASIN	IG JOINTS: Glu	ed Thr	readed
1. Steel 3. RPM	(SR) 6. Asbestos-Cement	8. Concrete tile	SDR-26		Weld	ded Cla	amped
2. PVC 4. ABS							
Blank casing diameter 8	in. to 20 ft.,	Dia.	in. to	ft., Di	a. in.	to	ft.
Casing height above land surface:	18 _{in.,}	Weight: 5.	52 lbs. / ft.	Wall thick	ness or gauge No.	.332	
TYPE OF SCREEN OR PERFORAT	TON MATERIAL:						
1. Steel 3. Stainless Stee	el 5. Fiberglass 🤇	7. PVC	9. ABS	11. Othe	r (specify)		
2. Brass 4. Galvanized	Concrete Tile	8. RMP (SR)	10. Asbestos	S-Cement 12. None	used (open hole)		
SCREEN OR PERFORATION OPEN	IINGS ARE						
<u> </u>	ll slot 5. Gauzed wr	anned	7. Torch cut	9. Drilled	l holes 1	I1. None (open	hole)
		••		_		······································	,
2. Louvered shutter 4. Ke	y punched 6. Wire wrapp	oed	8. Saw cut) 10. Other	(specify)		
SCREEN - PERFORATION INTERVA	AL From 20	ft. to	37 ft.,	From	ft.	to	ft.
	From	ft. to	ft.,	From	ft.	to	ft.
GRAVEL PACK INTERVALS	S: From 20	ft. to	47 ft.,	From	ft.	to	ft.
		ft. to					
I apply	rioin	11. 10	ft.,	From	ft.	to	ft.
GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole plug							
Grout Intervals: From 0 ft. to 20 ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination:							
1	7 Di4 mateur	10.	Livestock pens	13. Insectici	de storage 15	5. Oil well/Gas v	well
1. Septic tank 4. Lateral lines 4. Company of the first state of the f						v below)	
None Apparent							
1	epage pit 9. Feed yard	1 12.	Fertilizer storaç			· · · · · · · · · · · · · · · · · · ·	·
Direction from well?	LITUOLOGICLOG			How many			
From To	LITHOLOGIC LOG		From To)	<u>LITHOLOGIC</u>	LOG	
0 4 topsoil							
4 10 sandy clay					· · ·		
10 46 sand 46 47 clay							
46 47 clay							
				·			
			<u> </u>				
				- I			
7 Contractor's or Landowner's Ce	ertification: This water well was 1	. constructed	2. reconstru	acted or 3. plu	u gged under	my jurisdiction a	and
				•		my jurisdiction a	and
was completed on (mo/day/year)	6/9/2004	and this record is t	rue to the best o	f my knowledge and be	lief.		and
	6/9/2004	and this record is t	rue to the best o	•			and
was completed on (mo/day/year)	6/9/2004 cense No. 236	and this record is t	rue to the best o	f my knowledge and be leted on (mo/day/year)	lief.	4	and