CORRECTION(S) TO WATER WELL RECORD (WWC-5)

(to rectify lacking or incorrect information)

Location listed as:	County: <u>Sedawick</u> Location changed to:
Section-Township-Range: 265-1E	1
Fraction (1/4 1/4 1/4):	31-265-1E NW NW NW
Other changes: Initial statements:	
Changed to:	
Comments:	
verification method: Written description, Wichita Fast & Valley Cente	Wichita city map, and - 1:24,000 topo. maps. initials: DRL date: 10/15/2004

submitted by: Kansas Geological Survey, Data Resources Library, 1930 Constant Ave., Lawrence, KS 66047-3726 to: Kansas Dept of Health & Environment, Bureau of Water, 1000 SW Jackson, Suite 420, Topeka, KS 66612-1367.

35	5 D	· .	WATE	R WELL RECOR	RD Form \	/WC-5	KSA 82	a-1212			
LOCATION			Fraction			Sec	tion Number	Township	Number	Range	e Number
County: SP				address of well if	NW W			TZ	(s)	R	(E)W
Uistanos and o	T	Ath Ot			•		Merid	i'an			
WATER WE	ELL OW	NER: City	of Wichi		12-12-1		101.101		· · · · · · · · · · · · · · · · · · ·		
RR#, St. Addr	-			67206				Board (of Agriculture	Division of V	Vater Resource
City, State, ZIF			nita Ks		1100				tion Number:		
AN "X" IN S	SECTION	CATION WITH BOX:		COMPLETED WE							
<u>X</u> ,	 	NE E	WELL'S STATION Purities. Est. Yield Bore Hole Diam WELL WATER 1 Domestic 2 Irrigation	4 Industri	ili water was ili water was in. to	ic wate	elow land su ft ft ft supply ter supply garden only	after	i on mo/day/y hours p hours p hours p ining 1:	oumping bumping in. to 1 Injection we 2 Other (Spec	gprff
<u> </u>	 -		Was a chemical	Vbacteriological sa	ımple submitt	ed to De		YesNo. /ater Well Disinf	-		1
5 TYPE OF E	SLANK C	ASING USED:	Trinted	5 Wrought iron	n 8	Concre				No	lamped
1 Steel		3 RMP (8	SR)	6 Asbestos-Ce	-		(specify belo				<u>,</u>
2)PVC		4 ABS	2	7 Fiberglass					Thr	readed	7 .
				ft., Dia							
		R PERFORATION	ルタム ON MATERIAL:	in., weight	• • • • • • • • •	(F)PV			ess or gauge . Asbestos-cer		• • • • • • • • • •
1 Steel	, •.	3 Stainles		5 Fiberglass			IP (SR)				• • • • • • • • • • •
2 Brass		4 Galvani		6 Concrete tile) .	9 AB		. 12	None used (open hole)	
SCREEN OR 1 Contin		RATION OPENII	NGS ARE: Mill slot		Gauzed wra	• •		8 Saw cut	1	11 None	(open hole)
2 Louve			Mill slot Key punched 🔍		Wire wrappe Torch cut,	9Q		9 Drilled ho			• • • • • • • • • • •
GROUT MA	ATERIAL s: From earest so tank	m ource of possible 4 Late	From	2 Cement grout ft., From 7 Pit pr	t. to t	3 Bento	to	om 4 Other ft., From estock pens el storage	n	ft. to . Abandoned to Oil well/Gas	water well
		ver lines 6 See		9 Feed	ige lagoon vard	-		tilizer storage ecticide storage		Other (speci	•
Direction from	well?							any feet?			
FROM	TO	toosa	LITHOLOGIC	CLOG	F	ROM	то		PLUGGING	INTERVALS	3
1'	8'	2117	L.I				<u> </u>				
81 4	15'	Sand									
							ļ				
	<u>-</u> -		· · · · · · · · · · · · · · · · · · ·	.			 				
			— 						RE	CEIVE)
									ΔUG	1 8 2004	<u> </u>
									AUU	0.200	
			,				 	ļ	BURFA	U OF WA	<u>rer</u>
		ļ						· · · · · · · · · · · · · · · · · · ·			
				····································			 				
Water Well Counder the bus	ontractor siness na	r's License No.	onmodel P	tionity Ser	Vater Well Flo	cord w	and this re as complete by (sig	d on (mo/day/yr	ne best or my n7.130 mat	Knowledge a	nd belief. Kans
INSTRUCTION	ONS: Use t	ypewriter or ball pol	nt pen. PLEASE PRES	S FIRMLY and PRINT of 3620-0001. Telephone:	clearly. Please fill	in blanks.	underline or ci	role the correct answ	vers. Send too th	ree copies to Kar ords.	nsas Department