		WATER WI	ELL RECO	RD F	orm WV	VC-5 K	SA 82a-12	12			
1 LOCATION OF WATE Sedgwick	R WELL:	FRACTION SE	sw 5/4	NW	1/4 SECT	TION NUMBER	T 2	NUMBER 6 S	RANGE N R 11		
Distance and direction from	m nearest town or city :	100			777	17	<u> </u>	-			
1909 Harbor Lite Ct. Wichita, Kansas											
2 WATER WELL C	Board of Agriculture, Division of Water Resource										
RR#,ST. ADDRESS	S,BOX #: 1909 Harbor Lite Ct. STATE: Wichita, Kansas					P CODE:	E: Application Number:				
3 LOCATE WELL'S LO		DEPTH OF COMP	LETED WELL:	40		CODE.	ELEVATION:				
WITH AN "X" IN SEC	CTION BOX:	oth of groundwater			ft.			ft.		ft.	
		ELL'S STATIC WA		15	FT. BELO	W LAND SU	JRFACE MEASU	JRED ON mo/d	ay/yr: 12/1	0/04	
NW	NE	Pun	np test data:	Well wate	er was		ft. after	hours	of pumping @	gpm	
w X		Est. Yield:	gpm $oldsymbol{12}$ ir	Well water		Δ	ft. after		of pumping @	gpm	
		ore Hole Diameter ELL WATER TO BI	"	n.	to 4	0 ft.	and	in.	to 11_Inie	ft. ction well	
	<u> </u>			Public wate	er supply	7. Lawn a	and garden only	⊳ ^{9. Dewaterii}	י שי	pecify below)	
		_				8. Air cor		10. Monitorin	g well vhat mo/day/yr v	was sample	
S		/as a chemical/bacteri bmitted	iological sample su	ubmitted to De	epartment?	YES Was V	NO Vater Well Disin			was sample NO	
5 TYPE OF CAS	SING USED:	5. Wrought	Iron 7 F	Fiberglass	9. Ot	her (Specify	below) CAS	SING JOINTS: (Glued	Threaded	
1. Steel	3. RPM (SR	κ) -		_	SDI	R-26	,		Welded	Clamped	
2. PVC	> 4. ABS er 5	6. Asbestos		Concrete tile		-		D'.			
Blank casing diamete		16	25 ft.,	Dia.	in.	to	ft.,		n. to	ft.	
Casing height above land surface: 16 in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No214											
TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify) N/A											
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)											
SCREEN OR PERFORATION OPENINGS ARE:											
1. Continuous slot 3. Mill slot 5. Gauzed wrapped						rch cut	9. Dril l	ed holes	11. None (open hole)	
2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify) N/A											
SCREEN - PERFORA	TION INTERVAL	From	25 ft.	to	35	ft.,	From	ft.	to	ft.	
		From	ft.	to		ft.,	From	ft.	to	ft.	
GRAVEL PA	CK INTERVALS:	From	24 ft.	to	40	ft.,	From	ft.	to	ft.	
		From	ft.	to		ft.,	From	ft.	to	ft.	
6 GROUT MATERI	IALS: 1. Neat o	cement	2. Cement G	rout	3	B. Bentonite		Other bent	onite hole pl	ug	
Grout Intervals: From 4 ft. to 24 ft., From						ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination: 1. Septic tank 4. Lateral lines 7. Pit privy					. Livestoc	k pens	13. Insecti	cide storage	15. Oil well/0	Sas well	
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (sp							ecify below)				
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage											
Direction from well?	South						How ma	any feet? 12			
From To		LITHOLOGIC	LOG		From	То		LITHOLO	GIC LOG		
0 4 4 15	topsoil clav					<u> </u>					
15 40	coarse sand										
			•••								
							1				
							·				
						,					
	ļ-										
					· · · · · · · ·						
7	Landoure de C-d'C-	notion: Thist.	ا مسالمین		\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	constructor	1 01 2	plugged (under my jurisdic	tion and	
	Landowner's Certific	12/10/2004	_			constructed			ander my junealo	aon and	
was completed on						-	knowledge and l		1/2004		
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 12/13/2004											
under the business name of Harp Well and Pump Service by (signature) So d d S. Harp											