	WATER WELL	RECORD F	orm WW	/C-5 K	SA 82a-1212		
1 LOCATION OF WATER WELL:	FRACTION	TE CTT		ION NUMBER		RANGE N	
Sedgwick		E 1/4 SW	1/4	19	T 26 S	R 11	E E/W
Distance and direction from nearest town or city street address of well if located within city? 4601 N. Driftwood Ct. Wichita, Kansas							
	CHMAN INC., Br						
	7 N. Meridian					f Agriculture, Division of \	Water Resource
	chita, Kansas		ZIF	CODE: 6	7204 Application	Number:	
3 LOCATE WELL'S LOCATION 4	DEPTH OF COLUMN	WELL: 2	8 ft.		ELEVATION:		
WITH AN "X" IN SECTION BOX:	Depth of groundwater End	ountered:	ft.		ft.		ft.
	WELL'S STATIC WATER	LEVEL 13	FT. BELO	W LAND SU	RFACE MEASURED ON	mo/day/yr: 2/4	1/05
NWNE	Pump te	est data: Well wa	ter was			ours of pumping @	gpm
W W		gpm Well wa				nours of pumping @	gpm.
≥ W E .	Bore Hole Diameter WELL WATER ₩₩AB ₽US	in.	to	ft.		n. to	ft.
SW SE	WELL WATER WORD US 1. Domestic 3. Fee		ter supply	7. Lawn a	9. Dewa	atomig -	ection well specify below)
	2. Irrigation 4. Indu					toring well	heculy neiow)
S	Was a chemical/bacteriologi			YES	NO ; If y	ves, what mo/day/yr	
	submitted			Was V	Vater Well Disinfected?		NO
TYPE OF CASING USED:	5. Wrought Iron	7. Fiberglass	9. Ot	her (Specify	below) CASING JOIN		Threaded
1. Steel 3. RPM (3. 2. PVC 4. ABS	6. Asbestos-Cer	ment 8. Concrete t	ile			Welded	Clamped
Blank casing diameter 2	in. to	ft., Dia.	in.	to	ft., Dia.	in. to	ft.
Casing height to case and surface:	26	•					
TYPE OF SCREEN OR PERFORATION	,	Weight:	IC	os. / ft.	Wall thickness or	gauge No.	
1. Steel 3. Stainless Steel	5. Fiberglass	7. PVC	9. Al	BS	11. Other (specify	y) N/A	
2. Brass 4. Galvanized	6. Concrete Tile	8. RMP (SR)	10. A	sbestos-Cer	ment 12. None used (c	ppen hole)	
SCREEN OR PERFORATION OPENII	NGS ARE:						
1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut					9. Drilled holes	11. None (open hole)
2. Louvered shutter 4. Kev		wrapped	8. S a	w cut	10. Other (specify) N/A	
SCREEN - PERFORATION INTERVAL		ft. to		ft.,	From ft.	to	ft.
000000000000000000000000000000000000000	From	ft. to		ft.,	From ft.	to	ft.
GRAVEL PACK INTERVALS:		ft. to		ft.,	From ft.	to	ft.
	From	ft. to		ft.,	From ft.	to	ft.
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout						entonite hole pl	_
Grout Intervals: From ft. to ft., From ft. to ft., From 3 ft. to 28 ft.							
What is the nearest source of possible contamination: 1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas w						Gas well	
				el storage 14. Abandon water well 16. Other (specify below)			
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage None Apparent							
Direction from well? How many feet?							
From To	LITHOLOGIC L	OG	From	То		LOGIC LOG	V II.
			0	3	surface clay and sil		
			3	28	bentonite hole plug		
							<u> </u>
						· · · · · · · · · · · · · · · · · · ·	
			+				

			-				
7 Contractor's or Landowner's Cer		was 1. constructed	d 2. re	constructe	d or 3. plugged	under my jurisdic	ction and
7 Contractor's or Landowner's Cer was completed on (mo/day/year)	tification: This water well 2/4/2005				d or 3. plugged knowledge and belief.	under my jurisdic	ction and
	2/4/2005	and this record	is true to the	e best of my	knowledge and belief.	under my jurisdic	ction and
was completed on (mo/day/year)	2/4/2005 ense No. 236	and this record This water w	is true to the	e best of my	knowledge and belief.		ction and