

1	LOCATION OF WATER WELL: Sedgwick	FRACTION SW 1/4 NE 1/4 SW 1/4	SECTION NUMBER 20	TOWNSHIP NUMBER T 26 S	RANGE NUMBER R 1E E/W
---	--	---	-----------------------------	----------------------------------	---------------------------------

2	WATER WELL OWNER:	CABRALES, George	Board of Agriculture, Division of Water Resource
	RR#, ST. ADDRESS, BOX #:	717 W. 47th St. North	
	CITY, STATE:	Wichita, Kansas	Application Number:
		ZIP CODE:	

N

NW	NE
SW	SE

S

1 Mile

Depth of groundwater Encountered: _____ ft.

WELL'S STATIC WATER LEVEL **15** FT. BELOW LAND SURFACE MEASURED ON **4/20/05**

Pump test data: Well water was _____ ft. after _____ hours of pumping @ _____ gpm

Est. Yield: _____ gpm Well water was _____ ft. after _____ hours of pumping @ _____ gpm

Bore Hole Diameter **12** in. to **40** ft. and _____ in. to _____ ft.

WELL WATER TO BE USED AS:

1. Domestic

2. Irrigation

3. Feedlot

4. Industrial

5. Public water supply

6. Oil field water supply

7. Lawn and garden only

8. Air conditioning

9. Dewatering

10. Monitoring well

11. Injection well

12. Other (Specify below)

Was a chemical/bacteriological sample submitted to Department? **YES** ; If yes, what mo/day/yr was sample submitted _____

Was Water Well Disinfected? **NO** **YES** **NO**

TYPE OF CASING USED:				CASING JOINTS:				
1. Steel	3. RPM (SR)	5. Wrought Iron	7. Fiberglass	9. Other (Specify below)	Glued	Threaded		
2. PVC	4. ABS	6. Asbestos-Cement	8. Concrete tile	SDR-26	Welded	Clamped		
Blank casing diameter		5 in.	to 30 ft.,	Dia.	in.	to ft.,	Dia. in. to ft.	
Casing height above land surface:		12 in.,	Weight:	2.35 lbs. / ft.	Wall thickness or gauge No.			.214
TYPE OF SCREEN OR PERFORATION MATERIAL:								
1. Steel	3. Stainless Steel	5. Fiberglass	7. PVC	9. ABS	11. Other (specify)			
2. Brass	4. Galvanized	6. Concrete Tile	8. RMP (SR)	10. Asbestos-Cement	12. None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:								
1. Continuous slot	3. Mill slot	5. Gauzed wrapped	7. Torch cut	9. Drilled holes	11. None (open hole)			
2. Louvered shutter	4. Key punched	6. Wire wrapped	8. Saw cut	10. Other (specify)				
SCREEN - PERFORATION INTERVAL		From	30 ft.	to	40 ft.,	From	ft. to ft.	
		From	ft.	to	ft.,	From	ft. to ft.	
GRAVEL PACK INTERVALS:		From	24 ft.	to	40 ft.,	From	ft. to ft.	
		From	ft.	to	ft.,	From	ft. to ft.	

6	GROUT MATERIALS:		1. Neat cement	2. Cement Grout	3. Bentonite	Other	bentonite hole plug		
	Grout Intervals:	From	4 ft.	to	24 ft.	From	ft.	to	ft.
	What is the nearest source of possible contamination:								
	1. Septic tank	4. Lateral lines	7. Pit privy	10. Livestock pens	13. Insecticide storage	15. Oil well/Gas well			
	2. Sewer lines	5. Cess Pool	8. Sewage lagoon	11. Fuel storage	14. Abandon water well	16. Other (specify below)			
	3. Watertight sewer line	6. Seepage pit	9. Feed yard	12. Fertilizer storage					
	Direction from well?		East		How many feet?		50		

[illegible]

7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. **reconstructed** or 3. **plugged** under my jurisdiction and was completed on (mo/day/year) **4/20/2005** and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. **236** This water well record was completed on (mo/day/year) **4/22/2005**

under the business name of **Harp Well & Pump Service Inc.** by (signature) *J o d d S. H a r p*