		LL RECORD	For	m vv vv		SA 82a-121			
1 LOCATION OF WATER WELL:	E 1/2 1/4	SE -1/4	SE 1	- 1	17 100 NUMBE	T 26		RANGE NU	
Sedgwick Distance and direction from nearest town or cit			3E 1	/4	17	1 1 20	5	R 1E	E/W
Intersection of 53rd N. & 1	•	•	North		Park	City, Kansas			
	RK CITY, CITY		1101 641	V	1411	erry, realisad	· · · · · · · · · · · · · · · · · · ·		
	N. Hydraulic						Board of Agric	culture, Division of W	ater Resource
	k City, Kansas			ZIF	P CODE: 6	7219	Application Num	nber: 2005	0108
3 LOCATE WELL'S LOCATION 4	DEPTH OF COMPL	ETED WELL:	40	ft.		ELEVATION:			-
WITH AN "X" IN SECTION BOX:	l epth of groundwater l			ft.			ft.		ft.
1 1	ELL'S STATIC WAT		2 F		W I AND SI	JRFACE MEASU		lay/yr: 5/24	
			ell water v		** LAIND 00	ft, after		of pumping @	gpm
	Est. Yield:		ell water			ft. after		of pumping @	gpm
W Wille	Bore Hole Diameter	12 in.		to 4	0 ft.		in.	to	ft.
	ELL WATER TO BE	USED AS:					9. Dewaterin	11. Injed	ction well
sw se-	1. Domestic 3. F	eedlot 5. Publ	ic water	supply	7. Lawn a	ınd garden only		12. Other (Sp	ecify below)
	•			er supply		ditioning	10. Monitorin	i g well vhat mo/day/yr w	ne cample
1	Was a chemical/bacterion ubmitted	ological sample submitt	ed to Depa	artment?	YES Was V	NO Vater Well Disinfe			io 10
5 TYPE OF CASING USED:				0.00				Glued	Threaded
1. Steel 3. RPM (S	(R) 5. Wrought I	ron 7. Fiber	glass		her (Specify	below) CAS	ING JOINTS: (Welded	Clamped
2. PVC 4. ABS	6. Asbestos-	Cement 8. Conc	rete tile	SDF	R-26			**Cided	Clamped
Blank casing diameter 8	in. to 2	20 ft., Dia	a.	in.	to	ft., [Dia. i	in. to	ft.
Casing height above land surface:	12 in	Weight	: 5. :	. 52 lb	s. / ft.	Wall thi	ckness or gaug	e No332	
TYPE OF SCREEN OR PERFORATIO	,							.552	
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)									
2. Brass 4. Galvanized	6. Concrete Tile	e 8. RMP (SR)	10. As	sbestos-Cer	nent 12. No	ne used (open l	hole)	
SCREEN OR PERFORATION OPENIN	IGS ARE:					•			
1. Continuous slot 3. Mill s		auzed wrapped		7. Tor	rch cut	9. Drille	d hoies	11. None (o	pen hole)
2. Louvered shutter 4. Key	ounched 6. W	ire wrapped		(8. Sav	w cut	10. Othe	r (specify)		
1				_			. (5655)		
SCREEN - PERFORATION INTERVAL	From	20 ft.	to	35	ft.,	From	ft.	to	ft.
	From	ft.	to		ft.,	From	ft.	to	ft.
GRAVEL PACK INTERVALS:	From	20 ft.	to	40	ft.,	From	ft.	to	ft.
	From	ft.	to		ft.,	From	ft.	to	ft.
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hol						onite hole plu	ıg		
Grout Intervals: From 0 ft. to 20 ft., From ft. to ft., From ft. to							ft.		
What is the nearest source of possible of	7	Pit privy	10. I	Livestock	k pens	13 Insection	ide storage	15. Oil well/G	ias well
1. Septic tank 4. Lateral lines 4. Septic tank 4. Lateral lines 4. Cateral lines 4. Lateral lines 5. Lateral lines 5. Lateral lines 5. Lateral lines 6. Lateral									
2. Sewer lines 5. Cess Pool None Apparent									
5. Watertight Sewer line 6. Occupage pit					storage	Haw ma	nu faat?		
Direction from well? From To	LITHOLOGIC	LOG		From	То	How ma	LITHOLO	GIC I OG	
0 2 topsoil	LITHOLOGIC	LOG		110111	10		LITTIOLO	GIC LOG	
2 10 clay			\dashv						
10 20 medium san	d								
20 30 coarse sand									
30 32 clay									
32 40 medium san	d		_						
						7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7			
			-						
					1				
		724							
7 Contractor's or Landowner's Certif		rell was 1. constr	ucted	2. rec	constructed	1 or 3. F	olugged t	under my jurisdicti	ion and
7 Contractor's or Landowner's Certification (mo/day/year)	ication: This water w					or 3. p		under my jurisdicti	ion and
—	5/24/2005	and this re	cord is tr	rue to the	best of my		elief.	under my jurisdicti	ion and
was completed on (mo/day/year)	5/24/2005 nse No. 230	and this re This wa	cord is tr	rue to the ecord was	best of my	knowledge and b	elief.	/2005	ion and