WATER WELL RECORD	Form WWC-5	SA 82a-1212	
1 LOCATION OF WATER WELL: FRACTION	SECTION NUMBER		RANGE NUMBER
Sedgwick E 1/2 1/4 SE 1/4 SI	E 1/4 17	T 26 S	R 1E E/W
Distance and direction from nearest town or city street address of well if located within city?			
Intersection of 53rd N. & Broadway-660' West & 1320' N	orth Park	City, Kansas	
2 WATER WELL OWNER: PARK CITY, CITY OF Board of Agriculture, Division of Water Resource			
RR#,ST. ADDRESS,BOX #: 6110 N. Hydraulic		•	.,
CITY, STATE: Park City, Kansas	ZIP CODE: 6	Application Nur	nber: 20050108
3 LOCATE WELL'S LOCATION 4 DEPTH OF COMPLETED WELL:	40 ft.	ELEVATION:	
WITH AN "X" IN SECTION BOX: Depth of groundwater Encountered:	ft.	ft.	ft.
WELL'S STATIC WATER LEVEL 12		URFACE MEASURED ON mo/o	
	water was		
	water was		s of pumping @ gpm
			s of pumping @ gpm
Bore Hole Diameter 12 in. WELL WATER TO BE USED AS:	to 40 fi		to ft.
The state of the s	water supply 7. Lawn	and garden only 9. Dewateri	
X NOTICE OF THE STATE O		nditioning 10. Monitoria	12. Other (Specify below)
			what mo/day/yr was sample
S Was a chemical/bacteriological sample submitted submitted		Water Well Disinfected?	YES NO
5 TYPE OF CASING USED: 5 Wrought Iron 7 Fiberals	O Other (Specif	v below) CASING JOINTS: (Glued Threaded
1. Steel 3. RPM (SR) 5. Wrought Iron 7. Fibergla		y below) CASING JOINTS.	
2. PVC 4. ABS 6. Asbestos-Cement 8. Concre	te tile SDR-26		Welded Clamped
Blank casing diameter 8 in. to 20 ft., Dia.	in. to	ft., Dia.	in. to ft.
10			
Tolgrin	5.52 lbs. / ft.	Wall thickness or gaug	ge No332
TYPE OF SCREEN OR PERFORATION MATERIAL:	0.400	11 Other (enecify)	
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC	9. ABS	11. Other (specify)	
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SI	R) 10. Asbestos-Ce	ment 12. None used (open	hole)
SCREEN OR PERFORATION OPENINGS ARE:			
1. Continuous slot 3. Mill slot 5. Gauzed wrapped	7. Torch cut	9. Drilled holes	11. None (open hole)
2. Louvered shutter 4. Key punched 6. Wire wrapped	8. Saw cut	10. Other (specify)	
		(
SCREEN - PERFORATION INTERVAL From 20 ft.	to 35 ft.,	From ft.	to ft.
From ft.	to ft.,	From ft.	to ft.
GRAVEL PACK INTERVALS: From 20 ft.	to 40 ft.,	From ft.	to ft.
From ft.	to ft.,	From ft.	
			to ft.
GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole plug			
Grout Intervals: From 0 ft. to 20 ft., From	n ft. to	ft., From	ft. to ft.
What is the nearest source of possible contamination: 1. Septic tank 4. Lateral lines 7. Pit privy	10. Livestock pens	13. Insecticide storage	15. Oil well/Gas well
9 Sawaga laggan	11. Fuel storage	14. Abandon water well	16. Other (specify below)
2. Sewer lines 5. Obss 7 obt	-	14. Abalicon Water Well	None Apparent
3. Watertight sewer line 6. Seepage pit 9. Feed yard	12. Fertilizer storage		Trong Tappur on
Direction from well?	T = T =	How many feet?	010100
From To LITHOLOGIC LOG	From To	LITHOLC	GIC LOG
0 2 topsoil			
2 10 clay	 		
10 20 medium sand			
20 30 coarse sand 30 32 clay			
30 32 clay 32 40 medium sand			
52 40 medium 8200			
7 Contractor's or Landowner's Certification: This water well was 1. constructed 2, reconstructed or 3, plugged under my jurisdiction and			
was completed on (mo/day/year) 5/24/2005 and this record is true to the best of my knowledge and belief.			
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 5/31/2005			
under the business name of Harp Well & Pump Service Inc. by (signature)			
		1. 1 1	