1 LOCATION OF WATER WELL:	Fraction SE SE SE	Section Number	Township Number	Range Number	
County: Sedgwick	NAN X NOW X NOW	· · · · · · · · · · · · · · · · · · ·	т 26 s	R 1 EW	
Distance and direction from nearest toy	wn or city street address of well if located v				
Hills 66, 5403 North Broadway, Wichita, Ks					
2 WATER WELL OWNER: Lewis Williams					
RR#, St. Address, Box # : 15490	13 th St.		Board of Agriculture, Divi	ision of Water Resources	
City, State, ZIP Code : Perry,					
3 LOCATE WELL'S LOCATON WITH					
AN "X" IN SECTION BOX:	DEPTH OF COMPLETED WELL	32 ft. ELEVAT	ion: 1	331.20	
N	Depth(s) Groundwater Encountered 1	ft. 2	ft.	3 ft.	
A	WELL'S STATIC WATER LEVEL	ft. below land surfa	ice measured on mo/day/	/vr	
	Pump test data: Well water was ft. after hours pumping gpm				
NWNE	Est Yield anm: Well water was fit after hours numbing a				
₹ W E	E Bore Hole Diameter 4.25 in. to 32 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)				
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 injection well					
1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)					
2 Imigation 4 Industrial 7 Lawn and garden (domestic) 10 Monitoring well 4'15 Spara 8					
	Was a chemical/bacteriological sample of	ushmitted to Department? Ver	No X If you	moldayar cample une	
s	•				
	_		CASING JOINTS: Glue		
1 Steel 3 RMP		t 9 Other (specify below)			
2 PVC 4 ABS	7 Fiberglass		Threa	aded X	
Blank casing diameter 2	in. to 28 ft., Dia	in. to	t., Dia	in. to ft.	
Blank casing diameter 2 in. to 28 ft., Dia in. to ft., Dia in. to ft. Casing height above land surface 0 in., weight .716 ibs./ft. Wall thickness or gauge No154					
TYPE OF SCREEN OR PERFORATIO	IN MATERIAL:	[7]PVC	10 Asbestos-ceme	ent i	
1 Steel 3 Stainl	less steel 5 Fiberglass inized steel 6 Concrete tile	8 RMP (SR)	11 Other (specify)		
	inized steel 6 Concrete tile	9 ABS	12 None used (ope	en hole)	
SCREEN OR PERFORATION OPENII			Saw cut	11 None (open hole)	
		wrapped 9	Drilled holes		
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 28 ft. to 30 ft. From ft. to ft.					
GRAVEL PACK INTERVALS:	From	32 4 5		υπ.	
GIVALE PACK INTERVALS.	F1011 1. 10	ii. From	π. τ		
6 000174477044	From ft. to	ft. Fron	1 ft. t	to ft.	
GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Bentonite Pellets Grout Intervals From 1 ft. to 15 ft. From 15 26 ft. From ft. to ft.					
Grout Intervals From 1 ft. to 15 ft. From 15 26 ft. From ft. to ft.					
What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well					
1 Septic tank	4 Lateral lines 7 Pit privy	11 Fuel store		weil/ Gas weil	
2 Sewer lines		lagoon 12 Fertilizer	storage 16 Oth		
3 Watertight sewer lines	6 Seepage pit 9 Feedyar	d 13 Insecticid	e storage Co	ntaminated site	
Direction from well? How many feet?					
FROM TO CODE	LITHOLOGIC LOG	FROM TO	PLUGGING IN	ITERVALS	
	op Soil				
1 7 Sa	andy Silt				
7 10 Si	ity very fine grained Sand				
	ery fine grained loose Sand				
20 32 Lo	ose Mixed Sand w/s. gravel				
		 			
		 -			
		 			
 		 	· · · · · · · · · · · · · · · · · · ·		
		 			
7 10017794070710 05 14170110	DIS CERTIFICATION. THE	(1)	and (0) -11		
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was					
completed on (mo/day/yr)	4-18-05	and this record is true t	o the best of my knowled		
Water Well Contractor's License No.	554	This Water Well Record			
under the business name of	554 Woofter Pump & Well I	nc. by (si	anature) Sew (a l	411 1411	
INSTRUCTIONS: Please fill in blank	cs and circle the correct answers. Send three o	copies to Kansas Department of I	lealth and Environment Bu	neau of Water 1000 S.W.	
Jackson St., Ste. 420, Topeka, Kansas 66612-1367. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records/					