1 LOCATION OF WATER WELL:	IF	VC-5 R5A 624-1212 ID NO. 740-0
County: Sedgwick	Fraction SE 1/4 SE 1/4	Section Number Township Number Range Number
Distance and direction from nearest to	vn or city street address of well if located within	17 T 26 S R 1 EM
Hills 66, 5403 North Broadway,	Wichita Ke	city?
2 WATER WELL OWNER: Lewis	Williame	
TAGE	40th o4	
RR#, St. Address, Box # : 15490		Board of Agriculture, Division of Water Resources
City, State, ZIP Code : Perry	Ks 66073	Application Number:
3 LOCATE WELL'S LOCATON WITH	4 DEDTH OF COMPLETED WELL	30 A ELEVATION 1331 34
N	Denth (s) Crownductor Francisco d	30 ft. ELEVATION: 1331.34
	Depth(s) Groundwater Encountered 1	fl. 2ft. 3ft.
		ft. below land surface measured on mo/day/yr
	Pump test data: Well water was	ft. after hours pumping gpm
	Est. Yield apm: Well water was	ft. after hours pumping opm
₹ W E	Bore Hole Diameter 4.25 In. to 30	ft. and in. to ft. water supply 8 Air conditioning 11 Injection well water supply 9 Dewatering 12 Other (Specify below)
	WELL WATER TO BE USED AS: 5 Public	water supply 8 Air conditioning 11 Injection well
sw sE	1 Domestic 3 Feed lot 6 Oil fiek	water supply 9 Dewatering 12 Other (Specify below)
	2 Irrigation 4 Industrial 7 Lawn a	and garden (domestic) 10 Monitoring well + 1 Y > DA Y BA
	Was a chemical/bacteriological sample submi	tted to Department? Yes No X If yes, mo/day/yr sample was
S	submitted	Water Well Disinfected? Yes No X
5 TYPE OF BLANK CASING USED:		Concrete tile CASING JOINTS: Glued Clamped
	(SR) 6 Asbestos-Cement 9	

Blank reging diameter 2	in to 28 A hi-	in. to ft., Dia in. to ft. Ibs./ft. Wall thickness or gauge No154
Carlos to take the take to the take to the take to take the tak	π., Dia	in. toft., Diain. toft.
Casing neight above land surface	in., weight .710	bs./ft. Wall thickness or gauge No
2 Brass 4 Galva	ass steel 5 Fiberglass	8 RMP (SR) 11 Other (specify) 9 ABS 12 None used (open hole)
SCREEN OR PERFORATION OPENIN	nized steel 6 Concrete tile	9 ABS 12 None used (open hole) apped 8 Saw cut 11 None (open hole)
	Mill slot 6 Wire wrapp Key punched 7 Torch cut	ed 9 Drilled noies
SCREEN-PERFORATED INTERVALS		()
SCREEN-PERFORATED INTERVALS		30 ft. From ft. to ft.
	From ft. to	ft. From ft. to ft. 30 ft. From ft. to ft.
GRAVEL PACK INTERVALS:	From 26 ft. to	30 ft. From ft. to ft.
	From ft. to	ft. From ft. to ft.
6 GROUT MATERIAL: 1 Neat	cement 2 Cement grout	3 Bentonite 4 Other Bentonite peliets ft. to 26 ft. From ft. to ft.
Grout Intervals From 0	3 15 ft. From 15	ft. to 26 ft. From ft. to ft.
What is the nearest source of possible	contamination:	10 Livestock pens 14 Abandoned water well
1 Septic tank	4 Lateral lines 7 Pit privy	11 Fuel storage 15 Oil well/ Gas well
2 Sewer lines	5 Cess pool 8 Sewage lagor	
3 Watertight sewer lines	6 Seepage pit 9 Feedyard	13 Insecticide storage Contaminated site
Direction from well?	a coopage pit a recuyate	^
FROM TO CODE	LITHOLOGIC LOG	How many feet? ROM TO PLUGGING INTERVALS
	cement, clay	ROM TO PLUGGING INTERVALS
	ightly friable, sandy clay	
	ne to very fine grained loose	
	and, some gravel at 26	
	Jim Jim Lu	
	was the same of th	
7 CONTRACTOR'S OR LANDOWNE	R'S CERTIFICATION: This water wall was /1) o	onstructed, (2) reconstructed, or (3) plugged under my jurisdiction and was
completed on (mo/day/yr)	4-07-05	
Water Well Contractor's License No.	AEA	and this record is true to the best of my knowledge and belief. Kansas
under the humane name of	554 Woofter Mamp & Well Inc.	This Water Well Record was completed on (mo/day/yr) 9-2-05
INSTRUCTIONS: Places fill in blank	s and circle the correct to the corr	by (signature) Say (a Woofftto
INSTRUCTIONS: Please fill in blanks and circle the correct artificiers. Send three copies to Kansas Department of Health and Environment, Bureau of Water, 1000 S W Jackson St., Ste. 420, Topeka, Kansas 66612-1367. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.		