IL OCATION OF	WATER WELL:	VVAI			N	T			
JEOCATION OF ounty:	Sadawick		SE % S	E 1/4 Secti	on Number				
stance and direc	tion from neares	t town or city street ac	ddress of well if located	within city?	- 17	T 26	S R 1	€w	
ls 66, 5403 l	orth Broady	ay, Wichita, Ks	and or work in boates	a with an only ?				. }	
		vis Williams							
	Box# : 154					Board of Agricults	ina Division of Water	Resources	
. Class 710 0-	Class 710 Octo . Dormi Ve 88072					Board of Agriculture, Division of Water Resources Application Number:			
LOCATE WELL	'S LOCATON W	ITH							
AN "X" IN SEC	TON BOX:	JOEF IN OF	COMPLETED WELL						
	N	Depth(s) Ground	dwater Encountered	1	ft	2	ft. 3	ft.	
		WELL'S STATIC	C WATER LEVEL	15.16 ft. i	below land s	urface measured on r	no/day/yr		
NW-	NE	Pum	np test data: Well wat	ter was	f	. after	hours pumping	gpm	
i	,	Est. Yield	gpm: Well wat	ter was	f	. after	hours pumping	gpm	
w		E Bore Hole Diam	eter 6.25 in. to	22		ft. and	in. to	ft,	
1 !		WELL WATER	neter 6.25 in. to TO BE USED AS: 5 ic 3 Feed lot 6	Public water su	pply	8 Air conditioning	11 Injection we	ll haland	
sw	SE	2 Irrigation	A Industrial 7	I am and cord	supply on (domesti	5 Dewatering	iz Other (Spec	aly below)	
		'							
La constant	<u></u> X	1	/bacteriological sample	e submitted to D				1	
TYPE OF BLAI	IK CASING USE	submitted	P 141			ter Well Disinfected?			
1 Steel			5 Wrought Iron				Glued Cla		
2 PVC		MP (SR)	6 Asbestos-Ceme	-		•	Welded		
	4 A		7 Fiberglass			A DI-	Threaded		
nk casing diam	ner 4	in. to	ft., Dia	in. to)	m., Dia	in. to		
SING N ei ght abo	NG ISING SUITSCE	TION MATERIAL	in., weight	2.0/1	ibs./ft.	Wall thickness or gau	ıge No∠.	3/	
1 Steel	1 OR PERFORM 2	TION MATERIAL:	5 Fiberglass	اليا	PVC	10 Asbesto	s-cement		
2 Brass		alvanized steel	-	9	ARS	12 None u	specify) sed (open hole)		
REEN OR PER	FORATION OP		5 Gar	uzed wrapped			11 None (op	en hole)	
1 Continuo	s slot	3 Mill slot	6 Win	e wrapped		9 Drilled holes		,	
2 Louvered	shutter	4 Key punched		ch cut		10 Other (specify)			
CREEN-PERFO	RATED INTERV	ALS: From	7 ft. to	22		rom	ft. to	ft.	
		From	ft. to		ft. F	rom	ft. to	ft.	
GRAVEL	PACK INTERVA	LS: From	14 ft. to	22	ft. F	rom	ft. to	ft.	
		From	ft. to		ft. F	rom	ft. to	ft.	
GROUT MATE	RIAL: 1 N	eat cement 2	2 Cement grout	3 Bent	onite	4 Other 10/20 g	ravel		
out intervals	From 1	ft. to 6	ft. From	6 ft. to	o 14	ft. From	ft. to	ft.	
hat is the neares	t source of poss	ible contamination:				tock pens	14 Abandoned water	r well	
1 Septic tar		4 Lateral lines			11 Fuel:	storage	15 Oil well/ Gas well		
2 Sewer lines		-	8 Sewa				16 Other (specify be		
•	sewer lines	6 Seepage pit	9 Feedy	rard		-	Contaminate	d site	
rection from well	O CODE	LITUO	LOGIC LOG	FROM	How many		CINC INTERVALE		
	CODE	Blow sand	LOGIC LOG	FROM	10	PLUG	GING INTERVALS		
	.5	Dense hard cla	av		1				
1 5		Silty clay							
5.5	2	Quity olay				~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~			
5.5	2 2		ed loose sand		<u> </u>				
5.5			ed loose sand						
5.5			ned loose sand						
5.5			ned loose sand						
5.5			ned loose sand						
5.5			ned loose sand						
5.5			ned loose sand						
5.5			ned loose sand						
5.5			ned loose sand						
5.5 1 12 2	2	Very fine grain							
5.5 1 12 2 CONTRACTOR	2 2 2'S OR LANDOV	Very fine grain	FION: This water well w	vas (1) construct	ed. (2) recor	structed, or (3) plugge	nd under my jurisdiction	n and was	
5.5 1 12 2 CONTRACTOR mpleted on (mo.	2 L'S OR LANDOV day/yr)	Very fine grain	FION: This water well w				ed under my jurisdiction		
5.5 1 12 2 CONTRACTOR mpleted on (mo.	2 2 2'S OR LANDOV	Very fine grain VNER'S CERTIFICAT 4-1	FION: This water well w	and thi	s record is t		knowledge and belief.		