1 LOCATION OF WATER WELL:		Fraction				on Number	Township Number		Range Number		
	Sedgy d direction from			4 NW 3	4 NW		21	т 26		,	1 EW
stance an	d direction from	nearest tow	n or city street	address of well	if located within	n city?					- ∀
	uto, 5360 N.				·						
	WELL OWNER:		•								
	dress, Box #			y				Board of Age	riculture, Div	ision of Water	r Resources
y, State, 2	ZIP Code :	Wichita	a, Ks					Application !	lumber:		
LOCATE	WELL'S LOCA	TON WITH				24.5			4	220.22	
AN "X" IN	N SECTION BOX	١.		FCOMPLETED	WELL	24.5	ft. ELE	VATION:		330,33	
	N		Depth(s) Grou	ındwater Encour	ntered 1		f	t. 2	ft.	3	ft.
- 1^	`							surface measure			
]		E						ft. after			
- 1	i		Est. Yield	gpm:	Well water was	S		ft. after	hours	pumping	gpm
w L		Ε	Bore Hole Dia	meter 4.25	in. to	24.	5	ft. and	<u>.</u> !	n. to	ft.
1			1 Dome	R TO BE USED A	AS: 5 Publik t 6 ∩il fle	c water su Id weter e	pply	ft. and 8 Air condit 9 Dewateri	ioning 1 na 1	1 Injection w	ell acifu helow)
-	sws	E	2 Infosti	ion 4 Industri	el 7 tawn	and same	uppy un (domaeti	ic) 10 Monitori	nawali //	L' - C and	a a
1	1										
-	S							Yes No			
TYPE O		0.11000	supmitted	F 144				ater Well Disinfed			
1 Ste	F BLANK CASIN			-				CASING JO			
				6 Asbesto		-	-		vvek	ded	·
2 PV		4 ABS		7 Fibergla	18S				Thre	aded	
ank casing	g diameter	4	in. to	2.5 ft., Dis	ا - -	in. to		ft., Dia Wall thickness of 10 As 11 Ot 12 No		_ in. to	ft.
asing heig	ht above land su	Irface	<u>U</u>	in., weight		<u>. </u>		Wall thickness	or gauge No		154
YPE OF S	CREEN OR PE	RECRATION	N MATERIAL:	e en		إليّا	PVC	10 As	bestos-cem	ent	
2 Br) (1	4 Cohor	ized steel	5 Fibergia	188 10 190	8 1	KMP (SK)	11 Ot	ner (specity)		
CREEN C	R PERFORATION	ON OPENIN	GS ARF	o Concre	te ule 5 Gauzed w	vranned	100	8 Saw cut	ine useu (op	11 None (o	nen hole)
1 Co	R PERFORATIO	3	Mill slot		6 Wire wrap	napped		9 Drilled hole	ns.		pon noio,
2 Lo	uvered shutter	4	Key punched		7 Torch cut			9 Drilled hok 10 Other (spe From	ecify)		
	ERFORATED IN		From	22.5 f	t. to	24.5	ft.	From	ft.	to	ft.
			From	1	t. to		ft.	From	ft.	to	ft.
GR	AVEL PACK INT	ERVALS:	From	19 f	t. to	24.5	ft.	From	ft.	to	ft.
			From	1	t. to		ft.	From	ft.	to	ft.
GROUT	MATERIAL:	1 Neat o	ement	2 Cement grou	ut	3 Bent	onite	From 4 Other Ben	tonite Po	ellets	
rout interv	rals From	2	ft. to 15	5 ft. From	15	ft. to	19	ft. From		ft. to	ft.
Vhat is the	nearest source	of possible of	contamination:					stock pens			
			4 Lateral line		Pit privy			storage		well/ Gas we	
2 Se	wer lines		5 Cess pool		Sewage lage	oon	12 Ferti	lizer storage	16 Ot	her (specify b	elow)
3 Wa	itertight sewer lin	es	6 Seepage p	oit 9	Feedyard		13 insec	lizer storage cticide storage	Çc	ontaminat	ed site
irection fro	m well?						How many	/ feet?			
FROM		ODE		OLOGIC LOG		FROM	TO	P	LUGGING I	NTERVALS	
0	3	fill	clay								
3 14	14 24.5		sand								
24.5	24.5	FII	athered sh	ine grained	sand						····
24.5	 -	We	attiered Si	1916				<u> </u>			
	 										
	 								 		
***************************************	 		*								

II OO!			L.C 125-								
CONTR	ACTOR'S OR L	NDOWNE			ter well was (1)			nstructed, or (3) p			
				-12-04		••		rue to the best of	•	•	
/ater Well	Contractor's Lice	ense No.		554		This W	ater Well R	ecord was compl	eted on (mo	/day/yr)	9-9=Q5
						_				4 . (
	usiness name of					_		oy (signature) nt of Health and Er		4 . (ortur