LOCATION OF WATER WELL:	Fraction			on Number	Township Nu	mber	Range Number
county: Sedgwick	NW ½	NW % NW	74	21	T 26	S	R 1 E
distance and direction from nearest tov	m or city street addr	ress of well if located w	ithin city?				
Vally's Auto, 5360 N. Broadwa							
WATER WELL OWNER: Rosea	nn Harpster						
R#, St. Address, Box # : 5650 N					Board of Agricu	ılture. Div	rision of Water Resource
ity, State, ZIP Code : Wichit					Application Nur		
LOCATE WELL'S LOCATON WITH	T						
AN "X" IN SECTION BOX:	DEPTH OF CO	MPLETED WELL	20	ft. ELE	VATION:	1	1330.64
N					2	*	3 f
1 X 	Depuis Continue	WATER LEVEL 1	2 03		· · ·	n moldov	3f /yr
NW NE							pumping gpn
	Est. Yield	gpm: Well water	was	(t. after	_ hours r	pumpinggpr
₿ ₩ !	Bore Hole Diamet	er 4.25 in to	20		ft. and	ìr	n. to f
	WELL WATER TO	BE USED AS: 5 Pu	iblic water su	pply	8 Air condition	ing 1	n. to f 11 Injection well 12 Other (Specify below
se	1 Domestic	3 Feed lot 6 Oi	l field water s	upply	9 Dewatering	1	12 Other (Specify below
SVV SE	2 Irrigation	4 Industrial 7 La	wn and gard	en (domesti	c) 10 Monitoring	welf	
, , , , , ,							s, mo/day/yr sample was
S	i	actoriological sample s					
	submitted				ter Well Disinfected		
TYPE OF BLANK CASING USED:		5 Wrought Iron					ed Clamped
1 Steel 3 RMP	(SR)	6 Asbestos-Cement	9 Other (specify belo	ow)	Wek	ded
2 PVC 4 ABS		7 Fiberglass				Thre	eaded X
Nank sesing diameter 2	10.0	# Dia	in to		ft Dia		in to
Hatik Casing Claimeter		IL., Dia	746				454
dasing height above land surface	U	n., weight	./ 10	ibs./ft.	Wall thickness or	jauge No.)
slank casing diameter 2 Casing height above land surface YPE OF SCREEN OR PERFORATIO	N MATERIAL:		[7]	PVC	10 Asbe	stos-ceme	ent
1 Steel 3 Stainl	ess steel	£ Elbaroloss	8	RMP (SR)	11 Other	r (specify)) pen hole)
2 Brass 4 Galva	inized steel	6 Concrete tile	- 9	ABS			
SCREEN OR PERFORATION OPENII			ed wrapped		8 Saw cut		11 None (open hole)
1 Continuous slot 3	Mili siot		vrapped		9 Drilled holes		
2 Louvered shutter 4	Key nunched	7 Torch	cut		10 Other (speci	fv)	
SCREEN-PERFORATED INTERVALS	: From	10 ft. to	20	ft.	From	ft.	to
	From	ft to		A	From	R	to
ODANEL DAOK INTERVALO.	F	4 <i>E</i>	20		F		to to
GRAVEL PACK INTERVALS:	From	15 ft. to	20	II.		H.	
	From	ft. to		ft.	From	π.	to
GROUT MATERIAL: 1 Neat	cement 2	Cement grout	3 Bent	onite	4 Other		
Grout Intervals From 1	ft. to 9	ft. From	ft. t	0	ft. From		ft. to
What is the nearest source of possible	contamination:			10 Live	stock pens	14 AI	bandoned water well
1 Septic tank	4 Lateral lines	7 Dit netwo		11 Fuel	•		il well/ Gas well
					•		
2 Sewer lines	•	8 Sewage			lizer storage	16 01	ther (specify below)
3 Watertight sewer lines	6 Seepage pit	9 F ee dyar			cticide storage		ontaminated site
Direction from well?				How man	y feet?		
FROM TO CODE		OGIC LOG	FROM	TO	PLU	IGGING I	INTERVALS
0 3 Fi	II clay						
	ll sand						
14 20 Fi	ne to very fine	grained sand					
			1	 			
			1	 			
	4.4.		+	 			· · · · · · · · · · · · · · · · · · ·
				 			
			+	 			
				 		·····	
				-			
				ļ			
				ļ			
				}			
7			43		-1-1-1-1-1		
CONTRACTOR'S OR LANDOWNE							
	11-11	-05					dge and belief. Kansas
Water Well Contractor's License No.		554	This W	ater Well R	ecord was complete	om (mc	o/day/уг) 9-9≖05
inder the business name of	Wooff	er Pump & Well			by (signature)		
INSTRUCTIONS: Please fill in blan	ks and circle the corre	ct answers. Send three	opies to Kans	as Départme	nt of Health and Envi	ro ment	sureau of Water, 1000 S W
Lasteria Dr. Mrs. 100 March 114	00040 4007 T-I-			TED MELL	CHAIFE and salain a	4	a anno and a