			WATER WE	ELL REC	ORD 1	orm WV	VC-5 P	KSA 82a-12	12		
1 LOCATION Sedge	ON OF WATE wick	R WELL:	FRACTION NW	NE 1	/4 NW	1/4	TION NUMBE		P NUMBER	RANGE N	
Distance and direction from nearest town or city street address of well if located within city?											
2005 W. Driftwood Wichita, Kansas 2 WATER WELL OWNER: BACHMAN HOMES INC.											
	ER WELL (. ADDRESS		MAN HOM I. Meridian	ES INC.					Board of Agric	culture, Division of V	/ater Resource
KK#,51.			a, Kansas			z	IP CODE:		Application Num	iber:	
	E WELL'S LO	CATION 4 DE	PTH OF COMPL	ETED WEL	L: 3			ELEVATION:			
WITH	AN "X" IN SEC	CTION BOX: Depth	of groundwater	Encountered	i:	f	t.		ft.		ft.
	X	WEL	L'S STATIC WAT	TER LEVEL	10	FT. BELO	OW LAND S	SURFACE MEAS	URED ON mo/d	lay/yr: 12/1	6/05
<u> </u>	- NW	NE		np test data:	Well wa			ft. after		of pumping @	gpn
w Mie			Est. Yield: e Hole Diameter	gpm 12	Well wa	iter was	35 f	ft. after ft. and	in.	of pumping @ to	gpm ft.
-		, ,	L WATER TO BE						9 Dewaterii	44 lata	tion well
11 1	- SW	1						and garden on		12. Other (S)	ecify below
			rrigation 4. I a chemical/bacterion		6. Oil field v e submitted to		y 8. Alfco YES	onditioning	10. Monitorin ; If yes, v	v <u>hat mo</u> /day/yr v	as sample
<u> </u>		subm						Water Well Disir	fected?	YES I	10
 	PE OF CAS 1. Steel	SING USED: 3. RPM (SR)	5. Wrought I	ron	7. Fiberglass	9. C	ther (Specif	fy below) CA	SING JOINTS: (Glued	Threaded
	2. PVC	> 4. ABS	6. Asbestos-	-Cement	8. Concrete t	_{ile} SD	R-26			Welded	Clamped
	sing diamete	_	. to 2	24 ft.,	Dia.	in.	to	ft.,	Dia. i	n. to	ft.
Casing h	neight above	land surface:	12 in.,		Weight:	2.35	lbs. / ft.	Wall th	nickness or gaug	e No214	
TYPE OF SCREEN OR PERFORATION MATERIAL:											
1. Stee 2. Bras	•	S. Stainless Steel	FiberglassConcrete Til	_	PVC		ABS		ther (specify)	holo)	
		. Galvanized		ie o	. RMP (SR)	10. 7	Asbestos-Ce	ement 12. N	one used (open	noie)	
SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole)											pen hole)
2. Louve	ered shutte			lire wrapped	•		aw cut		er (specify)	•	
SCREEN	- PERFORA	ATION INTERVAL	From	24 ft.	to	-	ft.,	From		4-	4
	-1 214 010	WIOW IN LEWAL	From	ft.			ft.,	From	ft. ft.	to to	ft. ft.
GRAVEL PACK INTERVALS: From 24 ft.					to		ft.,	From	ft.	to	ft.
1			From	ft.	to)	ft.,	From	ft.	to	ft.
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole pl									ıg		
	Intervals:	From 4	ft. to	24 ft.,	From	ft.	to	ft.,	From	ft. to	ft.
What is the nearest source of possible contamination: 1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens							13, Insect	icide storage	15. Oil well/G	as well	
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (spec									ecify below)		
3. Water	rtight sewe		pit 9.	Feed yard		12. Fertilize	r storage				
	from well?	North	THOI COIC	100		1 -		How m	any feet? 50 f		
From 0	10	fine sand	THOLOGIC	LOG		From	То	<u> </u>	LITHOLO	GIC LOG	
10	25	coarse sand								· · · · · · · · · · · · · · · · · · ·	
25	_35	large gravel									
						 	 				
	-										
						 		-			
Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and											
was completed on (mo/day/year) 12/16/2005 and this record is true to the best of my knowledge and belief.											
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 12/19/2005											
under th	e business	name of Harp W	ell & Pump	Service I	nc.	by (si	gnature)	7,	dd S.	Harp	