bunty: Sedwick stance and direction from nearest to	CIA/				Township N			Number
stance and direction from nearest to	344 1/4	SW 14 SW	1 1/4	18	т 26	S	R	1 (Ê)W
100 North Meridian	wn or city street add	ress of well if located v	vithin city?					
WATER WELL OWNER: John	eon'e Gonoral	Store Inc						·
R#, St. Address, Box # : PO B		Store, inc			Deard of Aust	andreas Dist		Dana
ty State ZID Code . Wichi	ita KS 67277				Board of Agri		ision of vvai	er Resources
LOCATE WELL'S LOCATON WITH	HI.				Application N	umber.		
AN "X" IN SECTION BOX:	DEPTH OF C	OMPLETED WELL	21	ft. ELEV	ATION:			
N	Depth(s) Groundy	vater Encountered 1		ft.	2	ft.	3	ft.
	WELL'S STATIC	WATER LEVEL	NA ft. b	elow land s	urface measured	on mo/day/	/yr	
NW NE		test data: Well wate						
1 1 1	Est. Yield	gpm: Well wate	r was	fi	. after	hours r	oumpina	apm
W	Bore Hole Diame	rer 8 in. to D BE USED AS: 5 F 3 Feed lot 6 C	21		ft. and	ir	n. to	ft.
	WELL WATER TO	D BE USED AS: 5 F	ublic water sur	oply	8 Air condition	oning 1	1 Injection	well
SWSE	1 Domestic	3 Feed lot 6 C	oil field water su	upply	9 Dewaterin	g 1	2 Other (S	pecity below)
\mathbf{x}		4 Industrial 7 L						
S	l l	acteriological sample	submitted to De					
	submitted				ter Well Disinfect			
TYPE OF BLANK CASING USED:		5 Wrought Iron			CASING JO			
1 Steel 3 RMF	• •	6 Asbestos-Cemen	t 9 Other (s	specify below	w)	Weld	ded	-
PVC 4 ABS		7 Fiberglass				Thre	aded	X
ank casing diameter 4 asing height above land surface (PE OF SCREEN OR PERFORATION	in. to6	ft., Dia	in. to		ft., Dia		in. to	ft.
asing height above land surface	0	n., weight	2.071	lbs./ft.	Wall thickness o	r gauge No.		.237
PE OF SCREEN OR PERFORATION	ON MATERIAL:		9 F	PVC	10 Ast	estos-ceme	ent	
1 Steel 3 Stair 2 Brass 4 Galv	nless steel	5 Fiberglass	8 1	RMP (SR)	11 Oth	er (specify)		
Z DIASS 4 GAIV	anized steel	o Concrete tile	ed wranned	182	12 Nor 8 Saw cut	ie usea (op	en noie) 11 None	(open hole)
CREEN OR PERFORATION OPEN 1 Continuous siot 3	Mill slot	6 Wire	ed wrapped wrapped		9 Drilled hole		11 Hone	(open noic)
2 Louvered shutter 4	Key punched	7 Torch	cut		10 Other (spe	cify)		
CREEN-PERFORATED INTERVAL	S: From	6 ft. to	21	ft. F	rom	ft.	to	ft.
		ft. to						
GRAVEL PACK INTERVALS:	: From	4 ft. to	21	ft. F	rom	ft.	to	ft.
	From				rom		to	
GROUT MATERIAL: 1 Nea	t cement 2	Cement grout	3 Bento	onite	4 Other	· · · · · · · · · · · · · · · · · · ·	 	
GROUT MATERIAL: 1 Nearout Intervals From 0	ft. to 6	ft. From	ft. to		ft. From	, ,	ft to	ft.
hat is the nearest source of possible	contamination:			10 Livest	lock pens	14 Ab	andoned w	ater well
1 Septic tank	4 Lateral lines	7 Pit privy		11 Fuels	storage		well/ Gas v	
2 Sewer lines	5 Cess pool	8 Sewage	lagoon	12 Fertili	zer storage	16 Ot	her (specify	below)
3 Watertight sewer lines	Seepage pit	9 Feedya	rd	13 Insect	ticide storage			
rection from well?				How many	feet?			
FROM TO CODE		OGIC LOG	FROM	TO	PL	UGGING II	NTERVALS	
0 7 C	lay, Silty in Pl	aces, Stiff						
7 42 S	lightly Plastic	to Plastic						
7 13 S 13 21 S	ilty Sand, Very	tine grained						
13 21 3	and, Coarse w	ith fine gravel			*			
			_					
	************	······································						
						·		
								3 1
	EDIO OFFICIO							
CONTRACTORIO OD LAVIDOUR	ERS CERTIFICATION	אכ: I his water well wa			structed, or (3) pl	ugged unde	r my jurisdic	tion and was
CONTRACTOR'S OR LANDOWN	40 7	O.E.						
empleted on (mo/day/yr)	12-7	-05	and this		ue to the best of	my knowled	ige and beli	ef. Kansas
CONTRACTOR'S OR LANDOWN ompleted on (mo/day/yr) /ater Well Contractor's License No. nder the business name of INSTRUCTIONS: Please fill in blar	12-7	-05 -554	This Wa	ater Well Re	ue to the best of cord was comple	my knowled ted on (mo/	ige and beli /day/yr)	ef. Kansas 12-22-05