

1 LOCATION OF WATER WELL: County: Sedgwick		Fraction: SW 1/4 NE 1/4 NW 1/4	Section Number: 33	Township Number: T 26 S	Range Number: R 1 W
Distance and direction from nearest town or city street address of well if located within city? 3600 N Santa Fe					
2 WATER WELL OWNER: Love Box Company, Inc.					
RR#, St. Address, Box # : Jim Schmidt City, State, ZIP Code : P.O. Box 546 Wichita, KS 67201				Board of Agriculture, Division of Water Resources Application Number:	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 30 ft. ELEVATION: 1320.01			
		Depth(s) Groundwater Encountered 1 ~ 14.5 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL NM ft. below land surface measured on mo/day/yr NM Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well Air Sparge Well			
		Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes No (No)			
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
2 PVC		4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded Threaded X
Blank casing diameter in. to 2 in. Dia 30 ft., Dia in. to ft., Dia in. to ft.		Casing height above land surface - 3.60 in., weight lbs./ft. Wall thickness or gauge No SCH 40 PVC			
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel		3 Stainless Steel	5 Fiberglass	8 RMP (SR)	10 Asbestos-Cement
2 Brass		4 Galvanized Steel	6 Concrete tile	9 ABS	11 Other (Specify) 12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot		3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter		4 Key punched	6 Wire wrapped	9 Drilled holes	
			7 Torch cut	10 Other (specify)	
SCREEN-PERFORATED INTERVALS: From 25.5 ft. to 28 ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 24 ft. to 30 ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 1 ft. to 28.4 ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank		4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines		5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines		6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
				13 Insecticide storage	EXIST SITE
Direction from well? How many feet?					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	0.5	Asphalt			
0.5	7	Clay			
7	10	Silty clay			
10	11.4	sand, very fine grained			
11.4	11.8	Silty clay			
11.8	22	sand, very fine grained			
22	30	Gravel, medium to large			
					ASW 1

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was **(1) constructed**, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) **5-24-96** and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No **594** This Water Well Record was completed on (mo/day/yr) **8/2/06** under the business name of **Coranco Great Plains, Inc.** by (signature) **Meleem E. Freeman**