	WATER WELL	RECORD	orm WW	70-5 K	(SA 82a-1212			
1 LOCATION OF WATER WELL:	FRACTION	_		ION NUMBE			RANGE N	
☐ Sedgwick		E 1/4 NW	1/4	19	T 26	S	R 11	E E/W
Distance and direction from nearest town or		•						
53 St. North and Sherida			5 plugs of	ı 1 perm	it)			
	ICHITA, CITY OF	ı				Doord of Assi	multura Division of 1	M-1 D
	5 N. Main					Board of Agri	culture, Division of V	
CITY, STATE: \mathbf{W}	ichita, Kansas		ZI	P CODE:		Application Num	nber: 2006	50140
3 LOCATE WELL'S LOCATION	DEPTH OF COMPLETE	D WELL: 4	8 ft.		ELEVATION:			
WITH AN "X" IN SECTION BOX:	Depth of groundwater Enc		ft.			ft.		ft.
	WELL'S STATIC WATER			W I AND SI	URFACE MEASUR		iay/yr 12/1	1/06
				W LAND 3	ft, after			
NE	Pump te Est. Yield:						of pumping @	gpm
Wile w		51	ater was		ft. after		of pumping @	gpm
	Bore Hole Diameter	in.	to	ft	and	in.	to to	ft.
	WELL WATER WASE US 1. Domestic 3. Feed		ater sunniv	7. Lawn	and garden only	9. Dewateri	19	ction well
	2. Irrigation 4. Indu				-	10. Monitorin		pecify below)
S	Was a chemical/bacteriologi			YES	NO		vhat mo/day/yr v	was sample
5	submitted	car sample sooniked to	Department:		Water Well Disinfed			NO
5 TYPE OF CASING USED:			0.0	har (Cnasif	L bolow) CASIN	G JOINTS:	Glued	Threaded
1. Steel 3. RPM	(SR) 5. Wrought Iron	7. Fiberglass	g. 01	her (Specif	y below) CASIN	G JOINTS.	Welded	
2. PVC 4. ABS	6. Asbestos-Cer	nent 8. Concrete	tile				vveided	Clamped
Blank casing diameter 8	in. to	ft., Dia.	in.	to	ft., Di	a i	in. to	ft.
	26							11.
Casing height land surface:	,,,,	Weight:	It	s. / ft.	Wall thick	ness or gaug	je No.	
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify) N/A								
1. Steel 3. Stainless Stee	3	7. PVC	9. A					
2. Brass 4. Galvanized	Concrete Tile	8. RMP (SR)	10. A	sbestos-Ce	ment 12. None	used (open	hole)	
SCREEN OR PERFORATION OPEN	INGS ARE:							
1. Continuous slot 3. Mill slot 5. Gauzed wrapped			7. To	7. Torch cut 9. Drilled holes 11. None (open ho				open hole)
2. Louvered shutter 4. Key	punched 6. Wire	wrapped	8 Sa	w cut	10. Other	(specify) N	/A	
2. 20040100 3110101 4. 1(6)	patienea o. vine	тарреа	0. 00	out	10. 01.101	(opeon)) 11/	**	
SCREEN - PERFORATION INTERVA	L From	ft. to)	ft.,	From	ft.	to	ft.
	From	ft. to)	ft.,	From	ft.	to	ft.
GRAVEL PACK INTERVALS	: From	ft. t	0	ft.,	From	ft.	to	ft.
	From	ft. t	0	ft.,	From	ft.		
1				···,			to	ft.
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hol						•	ug	
Grout Intervals: From ft. to ft., From ft. to ft., From 3 ft. to 2.4							24 ft.	
What is the nearest source of possible contamination: 1 Sentic tank 4 Lateral lines 7. Pit privy 10. Livestock pens 13. Ins					13. Insecticio	de storage	15. Oil well/0	Gas well
1. Septic tank 4. Lateral lines				40 Other (constitute				
2. Sewer lines 5. Cess Pool None						None A		
	page pit 9. Fee	d yard	12. Fertilize	storage			rone A	ppar care
Direction from well?					How many			
From To	LITHOLOGIC LO	OG	From	То			GIC LOG	
			0	3	surface clay a			
 			3	24	bentonite hol			
			24	48	chlorinated s:	and and g	ravel	
			+					
								···
			-					
 			+					
			+					
			<u> </u>					
							······································	
7 Contractor's or Landowner's Co.	rtification: This water wall	was 1 constructs	d o ro	constructs	d or 3. plu	Inged	under my jurisdic	tion and
was completed on (mo/day/year) 12-11-2006 and this record is true to the best of my knowledge and belief.								
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 12-15-2006								
under the business name of Harn Well and Dumn Sarvice business business name of Harn Well and Dumn Sarvice								
under the business name of Harp Well and Pump Service by (signature) Todd S. Horb								