WATER WELL RECORD Form WWC-5 KSA 82a-1212									
1				ECTION NUMBER TOWNSHIP NUMBER			RANGE NUMBER		
Sedgwick	NE 1/4 NE	1/4 NE	1/4	2	T 26	S	R 1E	EW	
Distance and direction from nearest town or city street address of well if located within city? 4511 E. 77th Valley Center, Kansas									
2 WATER WELL OWNER: LEE BUILDERS									
	Board of Agriculture Division of Water Resource								
CITY, STATE: Valley	Center, Kansas		ZIP	CODE:		Application Num	nber:		
3 LOCATE WELL'S LOCATION 4 DE	PTH OF COMPLETED W	ELL: 55	ft.		ELEVATION:				
WITH AN "X" IN SECTION BOX: N Depth	of groundwater Encounte	ered:	, ft.			ft.		ft.	
X WELL	L'S STATIC WATER LEVE	EL 15	FT. BELOV	V LAND SU	RFACE MEASUR	ED ON mo/d	lay/yr: 6/6/0	7	
'NW NE	Pump test da				ft. after		of pumping @	gpm	
I.≐	Est. Yield: gpm • Hole Diameter 12	Well wate 2 in.	erwas to 55		ft. after		s of pumping @	gpm	
1 1 . 1 . 1 .	Hole Diameter 12 L WATER TO BE USED A		10 3.	5 ft.	and	in.	to na 11. Inject	ft. ion well	
	5. Dewatering								
	2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well								
Was a chemical/bacteriological sample submitted to Department? YES NO; If yes, what mo/day/yr was sample submitted Was Water Well Disinfected? YES NO									
5 TYPE OF CASING USED: CASING JOINTS: Glued Threaded									
1. Steel 3. RPM (SR) SDP 26 Welded Clamped									
2. PVC 4. ABS	6. Asbestos-Cement	8. Concrete til	e SDA	-20					
Blank casing diameter 5 in.			in.	to	ft., D	ia.	in. to	ft.	
Casing height above land surface:	12 in.,	Weight:	2.35 lb	s. / ft.	Wall thic	kness or gauç	ge No214		
TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)									
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify) 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cernent 12. None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole)									
2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify)									
SCREEN - PERFORATION INTERVAL		ft. to	55	ft.,		• •	4		
SCREEN - PERFORMATION INTERVAL	From 25	ft. to	33	ft.,	From From	ft.	to	ft.	
GRAVEL PACK INTERVALS:	From 24	ft. to	55	ft.,	From	ft. ft.	to to	ft.	
GRAVEE FACK INTERVALS.	From	ft. to		ft.,	From			ft.	
6 GROUT MATERIALS: 1 Neat ce						ft. Other hend	tonita hala nlu	ft.	
GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole plug Grout Intervals: From 4 ft. to ft., From ft. to						g ft.			
What is the nearest source of possible cont	amination:	•			-				
1. Septic tank 4. Lateral lines				ock pens 13. Insecticide storage 15. Oil well/Gas well storage 16. Other (specify below)					
2. Sewer lines 5. Cess Pool 5. Cess Pool 6. School 14. Abandon water well									
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage Direction from well? North How many feet? 1					nv feet? 10	0 ft. plus			
Direction near well.	ITHOLOGIC LOG		From	То			OGIC LOG		
0 3 topsoil									
3 7 clay									
7 10 clay and fine sa 10 20 medium grave									
20 55 gray shale									
			1						
			<u> </u>						
			<u> </u>						
						-			
Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and									
was completed on (mo/day/year) 6-6-2007 and this record is true to the best of my knowledge and belief.									
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 6-8-2007									
under the business name of Harp Well and Pump Service by (signature) Todd S. Harb									