	WATER WELL RE	CORD FO	rm www		A 82a-1212					
LOCATION OF WATER WELL:	FRACTION			ON NUMBER	TOWNSHIP		RANGE NU			
Sedgwick	SW 1/4 NW		1/4	29	T 26	<u>s</u>	R 1E	E/W		
Distance and direction from nearest town or city street address of well if located within city?										
4358 N. Arkansas Wichita, Kansas										
2 WATER WELL OWNER: BET	HEL PRESBYTARI	AN				Deced of A	nothing Division of the	-t D		
								ater Resource		
CITY, STATE: Wich	CITY, STATE: Wichita, Kansas ZIP C					ODE: Application Number:				
	DEPTH OF COMPLETED W	VELL: 40	ft.		ELEVATION:					
WITH AN "X" IN SECTION BOX:	oth of groundwater Encounter	ered.	ft.			ft.		ft.		
	ELL'S STATIC WATER LEV			VIAND SHE	RFACE MEASUR		lay/yr: 6/20			
				V LAND SUP	ft. after					
NW NE	Pump test da						of pumping @	gpm		
⊕ w ■ ■ ■ ■	Est. Yield: gpm ore Hole Diameter 1	Well wate		n	ft. after		s of pumping @	gpm		
			to 40) ft.	and	in.	to	ft.		
	ELL WATER TO BE USED A . Domestic 3. Feedlot	5. Public wate	ersunnly S	7. Lawn ar	nd garden only	9. Dewateri	9	tion well		
	2. Irrigation 4. Industria					10. Monitorii	12. Other (Sp na well	ecity below)		
	Vas a chemical/bacteriological sa			YES	NO		what mo/day/yr w	as sample		
· ·	bmitted	p.o oabilitied to be			ater Well Disinfe			10		
TYPE OF CASING USED:	F 144	7 [:	a O#	ner (Specify I	helow) CASI	NG JOINTS: (Glued	Threaded		
1. Steel 3. RPM (Si	S. Wrought Iron	7. Fiberglass			0.011)		Welded	Clamped		
2. PVC 4. ABS	6. Asbestos-Cement	8. Concrete tile	_e SDR	k-26			,	J		
Blank casing diameter 5	in. to 25 ft	., Dia.	in.	to	ft., D	ia.	in. to	ft.		
_	10	•								
.217										
TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)										
1. Occi										
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)										
SCREEN OR PERFORATION OPENINGS ARE:										
1. Continuous slot 3. Mill si	lot 5. Gauzed v	vrapped	7. Tor	ch cut	9. Drille	d holes	11. None (o	pen hole)		
2. Louvered shutter 4. Key p	unched 6. Wire wra	pped	8. Sav	v cut	10. Othe	r (specify)				
SCREEN - PERFORATION INTERVAL	From 25	ft. to	40	6	Erom					
SCREEN - PERFORMITION INTERVAL			40	ft.,	From	ft.	to	ft.		
	From	ft. to		ft.,	From	ft.	to	ft.		
GRAVEL PACK INTERVALS:	From 24	ft. to	40	ft.,	From	ft.	to	ft.		
	From	ft. to		ft.,	From	ft.	to	ft.		
6 GROUT MATERIALS: 1. Neat	cement 2 Ce	ment Grout	3	Bentonite		Other ben	tonite hole plu	19		
							5 ft.			
What is the nearest source of possible c	ontamination:			to .	ft.,					
1. Septic tank 4. Latera	7 Dit meise	y 1	0. Livestoc	k pens	13. Insection	ide storage	15. Oil well/G			
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below)										
2. Sewel lines 5. Several 12 Eartilizer storage										
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage Direction from well? East How many feet? 75 ft. plus										
From To	LITHOLOGIC LOG		From	ТоТ			OGIC LOG			
0 3 topsoil			1	 			3.0 200			
3 7 clay										
7 12 sandy clay										
12 20 fine sand										
20 40 medium san	d									
			ļ							
						-				
Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and										
was completed on (mo/day/year) 6-20-2007 and this record is true to the best of my knowledge and belief.										
under the business name of Harp	nse No. 236	This water we	ell record wa	•	on (mo/day/yea	r) 6-2	2-2007 S. Hart			